

Flushing, Suction and Tubing

SSU-2 Simple Suction Unit

Features

- Ergonomically designed for easy operation
- Suitable for all endoscopic procedures
- Large autoclavable bottle — 1.5 liter capacity
- Compatible with Olympus Fluid Management System (reusable/disposable suction jar/liner options)
- Easy change autoclavable bottle cap/float assembly
- Easy change microbial filter
- Vacuum gauge

Specifications

- Dimensions: 8.7" (W) x 8.9" (H) x 18.7" (D)
- Weight: 5.1 kg
- Maximum vacuum level: -85 kPa (-0.85 bar)
- Bottle capacity: 1.5 liters
- Power supplies:
 - 115 V ± 10%, 60 Hz
 - 230 V ± 10%, 50 Hz
- Power consumption:
 - 115 V: 190 VA
 - 230 V: 130 VA
- Electrical safety:
 - 115 V unit designed in conformance with UL544
 - 230 V unit designed in conformance with BS EN 60601-1 Class I, Type BF
- Spares: Replacement filters and bottles available

Accessories

Part #	Description
7317778	Filter bottle tube KV-2/SSU-2
55423	Microbial filter (10 pack)
55421	1.5 L suction jar
7146337	Suction jar cleaning brush
55453	Patient tubing
K10004950	Suction jar cap assembly



SSU-2