

Kare Medical proudly presents the new Oxybreath Mini series, Mini 3 and Mini 5.

Both with the non medical look, low volume design that saves transportation costs of providers and makes the therapy easier for patients. Mini 3 is specially designed for low flow patients in order to save them from the cost of 5 liter machines. Mini 5 is for patients that require regular therapy in a smaller and power efficient platform.



Mini 3 Technical Specifications

Part Number	OXY6300
Operating Voltage	220-240V / AC
Mains Frequency	50-60 Hz.
Power	165 W
Oxygen Flow	0,5-3 LPM
Oxygen Saturation	1-3 L 93 ± 3%
O ₂ Monitor	<ul style="list-style-type: none"> - High Oxygen %O₂ > 82% - Low Oxygen %O₂ < 82% - Technical Service Required < 70%
Operating Pressure	0,07-0,09 Mpa
Operating Temp.	5-40° C
Gross Weight	14,4 Kgs
Net Weight	12 Kgs.
Type	B
Class	II

3 - 5



Key Points

- Ultra low volume decreases shipping costs (288 pcs in a 20' container)
- Very small visual appearance and non medical look
- Low power consumption & less heat production
- 3 liter version is available for low flow patients, saves from unnecessary power cost and extra weight of 5 liter machines
- No maintenance required for 2 years
- Silent operation

Mini 5 Technical Specifications

Part Number	OXY6500
Operating Voltage	220-240V / AC
Mains Frequency	50-60 Hz.
Power	330 W
Oxygen Flow	0,5-5 LPM
Oxygen Saturation	1-5 L 93 ± 3%
O ₂ Monitor	- High Oxygen %O ₂ > 82% - Low Oxygen %O ₂ < 82% - Technical Service Required < 70%
Operating Pressure	0,07-0,09 Mpa
Operating Temp.	5-40° C
Gross Weight	17,5 Kgs
Net Weight	15,1 Kgs.
Type	B
Class	II

