

Product specification

MPS C · Cooling module

Item No.: 10175000 230 V, 50/60 Hz
Item No.: 10177000 115 V, 60 Hz



Specifications

	115 V	230 V
Nominal supply voltage	115 V AC +/-10 %	230 V AC +/-10 %
Nominal frequency	60 Hz	50 / 60 Hz
Power draw	150 VA	
Protective Class (I)	I	
Power fuses	2xT10 A	2xT4 A
Pollution degree (I)	2	
Overvoltage installation category	II	
Maximum heat emission	150 J / s	
Operating temperature range	+10 to +35 °C	
Temperature range during storage	+5 to +55 °C	
Relative humidity	max. rel. 80 % non-condensing	
Humidity during storage	max. rel. 80 % non-condensing	
Dimensions (w x d x h)	400 x 590 x 300 mm	
Weight	26 kg	
Temperature range cool plate	down to -15 °C, programmable*	
Cooling gas	R290	

Specifications

Work area (2)	270 x 370 mm, approx. 80 cassettes, 250 moulds, Sakura 84 – 90 pcs., Engelbrecht Super Mega Cassettes 16 – 18 pcs.
Installation requirements	< 2.000 m NN, 15 cm distance to wall

(1) According to IEC 1010, EN 61010

(2) Sakura cassettes 40 x 25 x 10 mm, Engelbrecht Super Mega Cassettes 53.8 x 75 x 18 mm. All other quantities refer to standard cassettes and moulds.

* All temperature specifications refer to an ambient temperature of +20 °C and a relative humidity of 60 %.

Optional accessories

Item No.

Transparent hood for cooling area MPS C

10175100

Comments / additional information:

In case of further questions, please feel free to contact us at every time.

SLEE medical GmbH • Am Neuberg 14
55268 Nieder-Olm • Germany
www.slee.de

T: +49 (0) 6136 76997-0
E: mail@slee.de



www.slee.de



[YouTube](#)



[LinkedIn](#)



[Instagram](#)