

COMMUNICATION



106R-000734

issued by : Ministry of Transport
L.Svobody 1222/12
110 15 Praha 1
Czech Republic

concerning: ^{1/}

~~APPROVAL GRANTED~~
APPROVAL EXTENDED
~~APPROVAL REFUSED~~
~~APPROVAL WITHDRAWN~~
~~PRODUCTION DEFINITELY DISCONTINUED~~

of a type of pneumatic tyre for agricultural vehicles pursuant to Regulation No. 106

Approval No.: **106R-000734**

Extension No. : **III.**

1. Manufacturer's name or trade mark (s) of the tyre: **PETLAS / STARMAXX / HARVESTER / MILESTONE**
2. Tyre type designation by the manufacturer: **IND25 / SM-I25 / HR-15 / ML-15**
3. Manufacturer's name and address: **PETLAS TIRE INDUSTRY AND TRADE COMPANY
Kindam Mah.
Ankara-Kayseri Cad. No. 2/1
Kirsehir
TURKEY**
4. If applicable, name and address of manufacturer's representative: **N/A**
5. Summarized description:
 - 5.1. Size of tyre: **see tyre dimensions list**
 - 5.2. Category of use: **Construction applications (IND)**
 - 5.3. Structure: **diagonal (bias-ply)/bias-belted/radial ^{1/}**
 - 5.4. Speed category symbol: **see tyre dimensions list**
 - 5.5. Load-capacity index: **see tyre dimensions list**
 - 5.5.1. for traction (implement only):
 - 5.5.2. for trailer (implement only):



5.6. Whether the tyre is to be fitted with or without an inner tube ~~TUBE TYPE~~ / TUBELESS

5.7. The supplementary service description, if applicable: -

6. Technical Service and, where applicable,
test laboratory approved for purposes
of approval or of verification of conformity:

IGTT a.s.
Šternberská 446, Louky,
763 02 ZLÍN
CZECH REPUBLIC

7. Date of report issued by that service: -

8. Number of report issued by that service: -

9. Reason(s) of extension (if applicable): **New size added**

10. Any remarks: -

11. Place: **Praha**

12. Date: **03. 10. 2018**

13. Signature: **Marek B r á z d a**

14. Annexed to this communication is a list of documents in the approval file deposited at the Administrative Services having delivered the approval and which can be obtained upon request

List of attached documents

- Application for approval

^{1/} Strike out what does not apply.



Annex No.1

Tyre dimensions list from the same range

12.5/80-18 12PR TL 142 A8 L2
12.5/80-18 14PR TL 146 A8 L2
340/80-18 12PR TL 142 A8 L2
16.0/70-20 14PR TL 154 A8
16.0/70-20 16PR TL 156 A8
16.0/70-24 14PR TL 152B
405/70-20 14PR TL 154 A8
405/70-24 14PR TL 152B
19.5 L-24 12PR TL 151 A8
440/80-24 12PR TL 149 A8 L2
16.9-24 12PR TL 149 A8 L2
16.9-24 14PR TL 152 A8 L2
16.5/85-24 12PR TL 149 A8
16.5/85-24 16PR TL 156 A8
16.9-28 12PR 152 A8 L2
16.9-28 12PR TL 152 A8 L2
16.9-28 14PR TL 156 A8 L2
440/80-28 12PR TL 152 A8 L2
480/80-26 14PR TL 158 A8 L2
18.4-26 12PR TL 156 A8 L2
18.4-26 14PR TL 158 A8 L2
18.4-26 16PR TL 160 A8 L2
14.5-20 14PR TL 143 D



APPLICATION FOR APPROVAL REGARDING ECE R106

1. Manufacturer's name or trade mark(s) on the tyre type : PETLAS/STARMAXX/HARVESTER/MILESTONE
2. Tread pattern designation by the manufacturer : IND-25 / SM-I25 / HR-15 / ML-15
3. Manufacturer's name and address : PETLAS TYRE INDUSTRY AND TRADE COMPANY.
Kindam Mah.
Ankara-Kayseri Cad. No.2/1
Kirsehir TURKEY
4. Summarised description for worst case tyre
 - 4.1. Size : 14.5-20 (14.5/75-20) IND 14PR TL 143 D
 - 4.2. Category of use : Construction applications (IND)
 - 4.3. Structure : Diagonal (Bias-Ply)
 - 4.4. Speed Category symbol : D
 - 4.5. The load – capacity index : 143
 - 4.6. Tube or Tubeless type : TUBELESS
 - 4.7. Cold inflation pressure(psi) : 51
 - 4.8. Inflation Pressure(psi) : 51
 - 4.9. Water Burst Test Pressure (kpa) : 878
 - 4.10. Load/Speed Test Pressure(kpa) : 352



APPLICATION FOR APPROVAL REGARDING ECE R106

5. WORST CASE REPRESENTATIVE TYRES:5.1. WATER BURST AND LOAD SPEED TEST:

WATER BURST AND LOAD/SPEED TEST REPRESENTATIVE TYRE		
SIZE	LOAD / SPEED INDEX	REASON TO BE WORST CASE
14.5-20 (14.5/75-20) 14PR TL	143 D	SPEED CATEGORY

6. LIST OF SIZES COVERED BY REPRESENTATIVE TYRES:

12.5/80-18 12PR TL 142 A8 L2
12.5/80-18 14PR TL 146 A8 L2
340/80-18 12PR TL 142 A8 L2
16.0/70-20 14PR TL 154 A8
16.0/70-20 16PR TL 156 A8
16.0/70-24 14PR TL 152B
405/70-20 14PR TL 154 A8
405/70-24 14PR TL 152B
19.5 L-24 12PR TL 151 A8
440/80-24 12PR TL 149 A8 L2
16.9-24 12PR TL 149 A8 L2
16.9-24 14PR TL 152 A8 L2
16.5/85-24 12PR TL 149 A8
16.5/85-24 16PR TL 156 A8
16.9-28 12PR 152 A8 L2
16.9-28 12PR TL 152 A8 L2
16.9-28 14PR TL 156 A8 L2
440/80-28 12PR TL 152 A8 L2
480/80-26 14PR TL 158 A8 L2
18.4-26 12PR TL 156 A8 L2
18.4-26 14PR TL 158 A8 L2
18.4-26 16PR TL 160 A8 L2
14.5-20 14PR TL 143 D

lsh