

PARAMETRI PRODUSE SEMIFABRICATE	PARAMETERS OF SEMI-FINISHED PRODUCTS FROM GLUED LAMINATED TIMBER NUMBER
<p>1. Vanzator: HOLVER SRL, Brasov, Bucegi nr 16, county Braşov Romania, Jo8/745/2000, CUI RO 13312578</p> <p>2. Comparator: Wood Glass SRL, Sat Tărlungeni, Comuna Tărlungeni, str. Zizinului, Nr. 625, judeţ Braşov, Romania Jo8/729/2011, CUI RO 28396216</p> <p>3. Denumirea semifabricatului din lemn stratificat Elementele stratificate de pin si meranti lipite conform specificatiei dimensiunilor (latime /grosime , lungime) inscise pe facturile nr. F9002958/20.03.2024 si F9003235/26.03.2024</p> <p>4. Scopul si destinatia produsului Productia de ferestre si usi, alte intrebuintari care necesita utilizarea de elemente semifabricate lipite. In timpul productiei produsului final este necesara selectarea clasei corespunzatoare de elemente stratificate (lipite)</p> <p>5. Specificatii tehnice PN-EN 942:2008 (Appendix A, B, C, D) PN-EN 204:2002</p> <p>6. Caracteristici tehnice declarate ale semifabricatului din lemn stratificat lipit -marginile stratului lipit sunt drepte , abaterea pana la 1.5 mm / ml -umiditatea straturilor individuale nu este mai mare de 15% , diferenta de umiditate a lemnului intre straturi nu depaseste 2 % -toate straturile sunt lipite corespunzator -imbinarile lipite nu se vor separa in timpul despicarii la o lungime min de 5 cm prin ruperea panii cu ungiul de taiere 30 grade -greutatea specifica medie a lemnului de meranti si a lemnului de pin este de 450 KG</p>	<p>1. Seller : HOLVER SRL, Brasov, Bucegi street nr 16, Romania, Jo8/745/2000, CUI RO 13312578</p> <p>2. Buyer: Wood Glass SRL, Village Tărlungeni, Zizinului street, no. 625, county Braşov, Romania Jo8/729/2011, CUI RO 28396216</p> <p>3. Name of semi-finished product from glued laminated timber : Glued laminated meranti timber and pine timber according to dimension specification (width, thickness, length) written on invoices no. F9002958/20.03.2024 and F9003235/26.03.2024</p> <p>4. Purpose and range of product application. Windows and doors production, other applications requiring the use of glued laminated timber. Selection of the appropriate class quality glued laminated timber is required during production of final product.</p> <p>5. Technical specification : PN-EN 942:2008 (Appendix A, B, C, D) PN-EN 204:2002</p> <p>6. Declared technical characteristics of semi-finished product from glued laminated timber: - edges of glued laminated scantling are straight, deviation from the straight line is not more than 1.5 mm per linear meter - moisture timber of the individual layers is not more than 15% , the difference in moisture of timber between glued laminated layers do not exceed 2% - all layers are properly glued, continuous welds and filled glue, - layer glue joints in laminated timber will not separate or delaminate during splitting to samples length 5 cm by spalling wedge cutting edge angle 30° - average specific gravity for meranti timber and pine timber is 450kg (technical data sheet and description of timber species available by request).</p>

Brasov, 24.04.2024,

HOLVER SRL prin administrator Fredy Adrian Mărie

