

# BCS-P-EIP14FSR3L3-Ai1

Index: **13061** GTIN13/EAN13: 5904890716858

URL: <https://bcs.pl/gb/4mpx/4677-bcs-p-eip14fsr3l3-ai1-5904890716858.html>



# BCS-P-EIP14FSR3L3-Ai1

## Product Details

<b>Product</b>	BCS-P-EIP14FSR3L3-Ai1
<b>Brand</b>	BCS POINT
<b>NDAA</b>	National Defense Authorization Act
<b>Camera type</b>	Dome
<b>Resolution</b>	4 Mpx
<b>Sensor</b>	1/3" CMOS
<b>Scanning system</b>	Progressive Scan
<b>Pixels</b>	2688(H)×1520(V)
<b>Lens</b>	fixed
<b>Focal length</b>	2.8 mm
<b>Aperture</b>	F1.6
<b>Focus</b>	fixed
<b>Iris</b>	fixed
<b>Angle of view</b>	H: 97° V: 52.2° D: 107.5°
<b>DORI</b>	Detect 63m / Observe 25.2m / Recognize 12.6m / Identify 6.3m
<b>Min illumination</b>	0.003Lux(F1.6,AGC) 0Lux(B/W,IR)
<b>S/N ratio</b>	52dB
<b>White balance</b>	(AWB) Auto / manual
<b>WDR</b>	120dB
<b>Backlight compensation</b>	BLC / HLC / WDR(120dB)
<b>Shutter</b>	Auto / manual 1~1/100000s
<b>Gain control</b>	(AGC) Auto / manual
<b>Noise reduction</b>	2D/3D DNR
<b>Roi</b>	Region of Interest
<b>Defog</b>	Digital
<b>Image rotate</b>	Mirror, Flip 0°/90°(corridor mode)/180°/270°
<b>Stream support</b>	2
<b>Resolutions</b>	4M(2688×1520)(2560×1440) / 3M(2304×1296) / 2M(1920×1080) / 720P(1280×720) / D1(720×576) / (640×360) / 2CIF(704×288) / CIF(352×288)
<b>Main stream</b>	2688×1520@25fps 2560×1440@25fps 2304×1296@30fps 1920×1080@30fps 1280×720@30fps
<b>Second stream</b>	720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
<b>Bitrate</b>	128Kbps~16Mbps
<b>Video compression</b>	H.265 / H.265+ / H.264 / MJPEG
<b>Day/night</b>	ICR
<b>Illuminator type</b>	IR LED + WhiteLight
<b>IR range</b>	30m
<b>WhiteLight range</b>	30m
<b>NightColor</b>	Yes
<b>Microphone</b>	Yes
<b>Loudspeaker</b>	Yes
<b>Audio compression</b>	G.711A / G.711U
<b>Storage</b>	NAS(NFS)

<b>Memory card slot</b>	microSD 512GB
<b>Support</b>	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
<b>Motion detect</b>	4
<b>Privacy masking</b>	4
<b>Network</b>	RJ-45 10/100Mbps
<b>Compatibility</b>	ONVIF(S/G/T)
<b>Protocols</b>	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP, QoS
<b>Network security</b>	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic/digest authentication RTSP, Digest authentication HTTP, TLS 1.2, WSSE/digest authentication ONVIF
<b>Power supply type</b>	12V DC / PoE(802.3af)
<b>Power consumption</b>	max 8W
<b>Housing color</b>	White
<b>IP class</b>	IP67
<b>Surge protection</b>	4kV
<b>Working environment</b>	-30°C~+60°C max 95% RH
<b>Dimensions</b>	Ø118×98mm
<b>Weight</b>	0.32kg
<b>Ai - Built-in intelligent functions</b>	Built-in intelligent algorithm of image analysis
<b>Ai - Perimeter protection</b>	Crossline, intrusion
<b>Ai - Human/vehicle detection</b>	Recognition of people entering the area and crossing the line reduces false alarms.
<b>Ai - SMD - Smart Motion Detection</b>	Intelligent Ultra Motion Detection with human/vehicle recognition

# BCS-P-EIP14FSR3L3-Ai1

## Accessories

BCS-ATU-B




BCS-P-U113



BCS-ADU-B



BCS-B-SEIP(2.0)



BCS-ADU125



BCS-ADU170

