










# PRE-ASSEMBLED EEG HEAD CAPS WITH STANDARD-THICKNESS ELECTRODES AND WIRES LOCATED EXTERNALLY

**REUSABLE**

**Packaging: box containing 1 piece.**

CODE	WIRES	SIZE	Number of electrodes	DESCRIPTION	COLOUR
<b>CUEE60S</b>	external	58-62 cm	21, standard thickness	Extra large, adult	Blue 
<b>CUEE56S</b>	external	54-58 cm	21, standard thickness	Large, adult	Red 
<b>CUEE52S</b>	external	50-54 cm	21, standard thickness	Medium-small, adult	Yellow 
<b>CUEE48S</b>	external	46-50 cm	21, standard thickness	Large, child	Green 
<b>CUEE44S</b>	external	42-46 cm	21, standard thickness	Medium, child	L. Blue 
<b>CUEE41S</b>	external	38-42 cm	21, standard thickness	Small, child	Pink 
<b>CUEE38S</b>	external	34-38 cm	11, standard thickness	Large, neonatal	Brown 
<b>CUEE34S</b>	external	32-34 cm	11, standard thickness	Medium, neonatal	Orange 
<b>CUEE32S</b>	external	30-32 cm	11, standard thickness	Small, neonatal	White 



**CUSTOMIZED CONNECTION CABLES ARE AVAILABLE UPON REQUEST.**

YOU CAN ORDER EEG HEAD CAPS WITH DIRECT CONNECTION TO THE EEG BOX.  
JUST REPLACE THE PRODUCT CODE'S LAST LETTER (**S**) WITH THE LETTER STANDING FOR THE  
DESIRED CONNECTION. SEE THE CHART BELOW.

<b>A</b>	INTERNATIONAL		<b>N</b>	NEUROSOFT
<b>M</b>	MICROMED		<b>XX</b>	CUSTOM-MADE

# INTERFACE CABLE FOR PRE-ASSEMBLED EEG HEAD CAPS **REUSABLE**

This INTERFACE CABLE (standard length 400 mm) plugs the EEG head cap into the EEG box.

At the end of the interface cable there are 21 marked cables (**universal connection**) which are plugged into the EEG box. The final connector is a touchproof Ø 1.5 mm DIN42802. The cables are marked following the INTERNATIONAL 10-20 system.

**Packaging: box containing 1 piece.**

CODE	NUMBER OF ELECTRODES	HEAD CAP END	EEG BOX END
<i><b>CUEFD1RS</b></i>	11	SEI (S) sub-D25 female	touchproof DIN42802
<i><b>CUEFD1S</b></i>	21	SEI (S) sub-D25 female	touchproof DIN42802
<i><b>CUEFD1A</b></i>	21	INTERNATIONAL (A)	touchproof DIN42802
<i><b>CUEFMCS</b></i>	21	SEI (S) sub-D25 female	MICROMED sub-D25 male
<i><b>CUEFMZS</b></i>	21	SEI (S) sub-D25 female	MDR50
<i><b>CUEFLIS</b></i>	21	SEI (S) sub-D25 female	MDR36



**CUSTOMIZED CONNECTION CABLES ARE AVAILABLE UPON REQUEST.**