ViewSonic MA2432-MHD


Key Features

- SuperClear® IPS Technology for richer, sharper colors at wide angles
- Full HD 1080p resolution
- 75Hz Refresh rate delivers fluid visuals
- Adaptive sync to eliminate screen tearing & reduce stuttering
- Three-sided frameless design for seamless viewing



Product **Description**

The ViewSonic VA2432-MHD is a 24" (23.8" viewable) Full HD Monitor with IPS technology and flexible connectivity for use in the office or at home. With SuperClear® IPS technology and Full HD resolution, images are clear and detailed from a wide range of viewing angles. Integrated speakers ensure a crisp and clear sound while Display Port, HDMI, and VGA inputs allow for increased setup flexibility when connecting with other devices. The VA2432-MHD's three-sided frameless bezel delivers a seamless viewing experience and comes equipped with Eye Care technology to help eliminate eye strain resulting from extended viewing periods. VESA compatibility guarantees easy adaption to both multimonitor or wall-mount set ups.







Panel Type:IPS TechnologyGross (Resolution:Resolution:1920 x 1080WEIGHResolution Type:FHD (Full HD)Net (kgStatic Contrast Ratio:1,300:1 (typ)Net WitDynamic Contrast Ratio:50M:1Gross (JIMENLight Source:LEDDIMENBrightness:250 cd/m² (typ)PackagColor Space Support:8 bit (6 bit + FRC)PhysiceAspect Ratio:16:9DIMENViewing Angles:178° horizontal, 178° verticalPhysiceBacklight Life (Hours):30000 Hrs (Min)PhysiceCurvature:FlatGENERRefresh Rate (Hz):100RegularVariable Refresh Rate Technology:FreeSyncPacKagBlue Light Filter:YesPACKARFilcker-Free:YesPACKARColor Gamut:NTSC: 75% size (Typ) sRGB: 105%	iout Stand (lbs): (METRIC) iout Stand (kg): ig): SIONS (IMPERIAL) (1 ing (in.): (in.): Without Stand (in.): SIONS (METRIC) (W2 ing (mm): (mm): Without Stand (mm): AL ons: SE CONTENTS: (Disposal:	23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4
Panel Type:IPS TechnologyGross (Resolution:1920 x 1080WEIGHResolution Type:FHD (Full HD)Net (kgStatic Contrast Ratio:1.300:1 (yp)Net (kgDynamic Contrast Ratio:1.300:1 (yp)Net WilDynamic Contrast Ratio:EDDIMENStatic Contrast Ratio:1.300:1 (yp)ProbageDynamic Contrast Ratio:16.7 MProbageColors:16.7 MProbageColor Space Support:8 bit (6 bit + FRC)ProbageResponse Time (MPRT):1msProbageStatic Life (Hours):30000 Hrs (Min)ProbageSacklight Life (Hours):30000 Hrs (Min)ProbageCurvature:FlatGENERRefresh Rate (H2):100RegulatYariable Refresh RateFreeSyncRegulatColor Gamut:YsS: 75% size (Typ) sRGB: 105%RecycleSult Life IF Hite:YesRecycleProbage0.275 mm (H) x 0.275 mm (Y)NarranOMPATIBILITY1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080NarranProbage1920x1080	bbs): (METRIC) : inout Stand (kg): (g): SIONS (IMPERIAL) (M ing (in.): (in.): Without Stand (in.): SIONS (METRIC) (W2 ing (mm): (mm): Without Stand (mm): AL ons: SE CONTENTS: (Disposal:	8.2 2.7 2.4 3.7 XXXDD 23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 XXDD 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UKRSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (y1.4, Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws. "Warranty offered may differ from
Resolution:1920 x 1080VEIGH Net (kg Net (kg)Resolution Type:FHD (Full HD)Net (kg Net (kg)Static Contrast Ratio:1,300:1 (typ)Net Wit Opamic Contrast Ratio:50M:1Goos (DINEN PackagGolors:16.7MPhysicaColors Space Support:8 bit (6 bit + FRC)Dinen PackagSappet Ratio:16.9Dinen PackagResponse Time (MPRT):1nsPackagSacklight Life (Hours):30000 Hrs (Min)PackagSacklight Life (Hours):30000 Hrs (Min)PackagCurvature:FlatGENER PackagRefresh Rate (H2):100RegulatCurvature:YesPackagSacklight Life (Hours):90000 Hrs (Min)PackagSacklight Life (Hours):100RegulatSacklight Life (Hours):100RegulatSacklight Life:YesPackagColor Gamut:Yes'PackagColor Gamut:1920x1080PackagSufface Treatment:Anti-Glare, Hard Coating (3H)OMPATIBILTY1920x1080PC Gesolution (max):1920x1080PC Operating System:100Sufface Resolution (max):1920x1080Power in:DC Socket (Center Positive)DisplayPort:15WSufface Stand-by:15WConserve):15WConserve):15WConserve):15WConserve):15WConserve):15WConserve):15W<	r (METRIC) : iouut Stand (kg): ig): SIONS (IMPERIAL) (1 ing (in.): (in.): Without Stand (in.): SIONS (METRIC) (W2 ing (mm): (mm): Without Stand (mm): ML ons: SE CONTENTS: /Disposal:	2.7 2.4 3.7 XXHXD) 23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 XHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4, Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws. "Warranty offered may differ from
Resolution Type:FHD (Full HD)Net (kg Net (kg) Net With Dynamic Contrast Ratio:1,300:1 (typ)Net With Oras (Gross (Light Source:LEDNet With Gross (LeDDynamic Contrast Ratio:50M:1Gross (Dynamic Contrast Ratio:Fackag PhysicaColors:16.7MPhysicaColors:16.7MPhysicaColorsace Support:8 bit (6 bit + FRC)PhysicaAspect Ratio:16:9PhysicaColorsers:16:9PhysicaAspect Ratio:178' horizontal, 178' verticalPhysicaBacklight Life (Hours):30000 Hrs (Min)PhysicaCurvature:FlatGENERRefresh Rate (H2):100PhysicaColor Gamut:YesPhysicaColor Gamut:NTSC: 75% siza (Typ) sRGB: 105% Size / 99% coverage (Typ)PhysicaPicker-Free:YesPhysicaColor Gamut:1920x1080PhysicaPicker Size:0.275 mm (H) x 0.275 mm (V)WarranSurface Treatment:Anti-Glare, Hard Coating (3H)OMPATIBILITY1920x1080PC Resolution (max):1920x1080PC Goperating System:Windows 10/11 certified; macOSPicker Size:1Obser Size (Operating System:1Outser Size (Conserve):1Sism Audio Out:111DisplayPort:1Power In:0C Socket (Center Positive)DiplayPort:15WConsumption (max):25WConsumption	: is in the set of th	2.4 3.7 XXHXD) 23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 XHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws. "Warranty offered may differ from
Number of the set	iout Stand (kg): ig): iONS (IMPERIAL) (f ing (in.): Without Stand (in.): CIONS (METRIC) (W2 ing (mm): (mm): Without Stand (mm): AL ons: SE CONTENTS: /Disposal:	2.4 3.7 XXHXD) 23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 XHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance will local, state or federal laws. "Warranty offered may differ from
Note of (p)Gross (Gross (Jonamic Contrast Ratic):SOM:1Gross (Jonamic Contrast Ratic):FileLapidh Source:LEDDIMENBrightness:250 cd/m² (typ)PackagColor Space Support:8 bit (6 bit + FRC)PhysicaColor Space Support:16:9DIMENAspect Ratio:16:9PhysicaAspect Ratio:178° horizontal, 178° verticalPhysicaBacklight Life (Hours):30000 Hrs (Min)PackagCurvature:FlatPhysicaReferesh Rate (HZ):100PackagColor Gamut:YesPackagFlicker-Free:YesPackagColor Gamut:NTSC: 75% size (Typ) sRGB: 105% Goverage (Typ)PackagPixel Size:0.275 mm (H) x 0.275 mm (V)PackagSurface Treatment:Anti-Glare, Hard Coating (3H)PackagOMPATIBILITY1920x1080PackagPC Resolution (max):1920x1080PackagPC Coperating System:1920x1080PackagVGA:11DisplayPort:1Power in:DC Socket (Center Positive)UDIOInternal Speakers:22WConsumption (typical):18WConsumption (typical):18WConsumption (typical):22WConsumption (typical):22WConsumption (typical):22WConsumption (typical):22WConsumption (typical):22WConsumption (typical):22WConsumption (typical):22W </td <td>g): GIONS (IMPERIAL) (I ng (in.): Without Stand (in.): GIONS (METRIC) (W2 ng (mm): (mm): Without Stand (mm): AL ons: SE CONTENTS: /Disposal:</br></br></br></td> <td>3.7 XXHXD) 23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 XHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws. "Warranty offered may differ from</td>	g): GIONS (IMPERIAL) (I ng (in.): Without Stand (in.): GIONS (METRIC) (W2 ng (mm): (mm): Without Stand (mm): AL 	3.7 XXHXD) 23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 XHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws. "Warranty offered may differ from
Jeth Source:LEDDIMENLight Source:LEDPackagColors:16.7MPhysicaColor Space Support:8 bit (6 bit + FRC)PhysicaAspect Ratio:16.9PhysicaResponse Time (MPRT):1msPackagViewing Angles:178° horizontal, 178° verticalPhysicaBacklight Life (Hours):30000 Hrs (Min)PhysicaSacklight Life (Hours):30000 Hrs (Min)PhysicaCurvature:FlatPhysicaRefersh Rate (Hz):100PhysicaElchnology:YesPhysicaColor Gamut:YesPhysicaColor Gamut:NTSC: 75% size (Typ) sRGB: 105%PhysicaSurface Treatment:Anto Coating (3H)PhysicaSurface Treatment:Anto Coating (3H)PhysicaOMPATIBLITY1920x1080PhysicaPC Resolution (max):1920x1080PhysicaPC Resolution (max):1920x1080PhysicaPC Resolution (max):1920x1080PhysicaPC Resolution (max):1920x1080PhysicaPOWERIIDisplayPort:1Power in:DC Socket (Center Positive)UDIOIUE Solution (max):18WConsumption (typical):22WConsumption (typical):18WConsumption (typical):22WConsumption (typical):22WConsumption (typical):22WConsumption (typical):23WPower Supply:External Power	CIONS (IMPERIAL) (ing (in.): (in.): Without Stand (in.): CIONS (METRIC) (W) ing (mm): (mm): Without Stand (mm): AL Ons: SE CONTENTS: /Disposal:	AXHXD) 23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 XHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e-Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws. "Warranty offered may differ from
0 Sold max (typ) Packag Sclors: 16.7M Physica Colors Space Support: 8 bit (6 bit + FRC) Physica Aspect Ratio: 16.9 Physica Aspect Ratio: 178° horizontal, 178° vertical Physica Maxport Ratio: 178° horizontal, 178° vertical Physica Sacklight Life (Hours): 30000 Hrs (Min) Physica Curvature: Flat GENER Refresh Rate (Hz): 100 Regulat Yariable Refresh Rate FreeSync Regulat Sacklight Lifer: Yes Packag Color Gamut: NTSC: 75% size (Typ) sRGB: 105% Recycle Sack Care Readement: Anti-Glare, Hard Coating (3H) Packag OMPATIBILITY 1920x1080 Packag PC Care Solution (max): 1920x1080 Packag ONECTOR Intervertified; macOS Samm Audio Out: 1 DisplayPort: 1 Samm Audio Out: 1 DisplayPort: 1SW Samm Audio Out: Saw Consumption (t	ng (in.): (in.): Without Stand (in.): SIONS (METRIC) (W2 ng (mm): (mm): Without Stand (mm): NL oons: SE CONTENTS: (Disposal:	23.6 x 15.6 x 4.4 21.3 x 16 x 7.3 21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 (HXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UKrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x2 or 2 (by country) Please dispose of in accordance with local, state or federal laws. "Warranty offered may differ from
Program CorrProvide CorrColors:16.7MColors Since Support:8 bit (6 bit + FRC)Aspect Ratio:16:9Aspect Ratio:16:9Response Time (MPRT):1msPackagPhysicaSacklight Life (Hours):30000 Hrs (Min)Curvature:FlatBacklight Life (Hours):100Curvature:FlatRefresh Rate (Hz):100Variable Refresh Rate Technology:FreeSyncBlue Light Filter:YesColor Gamut:NTSC: 75% size (Typ) sRGB: 105% size / 99% coverage (Typ)Surface Treatment:Anti-Glare, Hard Coating (3H)OMPATIBILITY1920x1080PC Resolution (max):1920x1080PC Resolution (max):1920x1080PC Operating System:Windows 10/11 certified; macOS testedPC Resolution (max):1920x1080PC Operating System:10Color Socket (Center Positive)UDIOIUDIOUDIOIUDIOConsumption (typical):25WConsumption (typical):25W <trr>Consumption (typic</trr>	(in.): Without Stand (in.): SIONS (METRIC) (W2 ng (mm): (mm): Without Stand (mm): AL ons: SE CONTENTS: /Disposal:	21.3 x 16 x 7.3 21.3 x 12.7 x 1.4 KHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x2 or 2 (by country) Please dispose of in accordance with local, state or federal laws. "Warranty offered may differ from
Colors:16.7MPhysical PhysicalColors:16.7MPhysical PhysicalColor Space Support:8 bit (6 bit + FRC)Physical PhysicalAspect Ratio:16:9Physical PhysicalResponse Time (MPRT):1msPhysical PhysicalBacklight Life (Hours):30000 Hrs (Min)Physical PhysicalCurvature:FlatPhysical PhysicalCurvature:FlatPhysical PhysicalRefresh Rate (HZ):100Regulal PhysicalVariable Refresh Rate Technology:FreeSyncBilue Light Filter:YesColor Gamut:NTSC: 75% size (Typ) sRGB: 105% size / 99% coverage (Typ)Picker-Free:YesColor Gamut:0.275 mm (H) x 0.275 mm (V)Surface Treatment:Anti-Glare, Hard Coating (3H)OMPATIBILITY1920x1080PC Operating System:1920x1080PC Operating System:1920x1080PC Operating System:100Smm Audio Out:11100DisplayPort:11100DisplayPort:15WEco Mode (Conserve):15WEco Mode (Conserve):15WEco Mode (Conserve):15WEco Mode (Conserve):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1Kensington Lock Slot:1	Without Stand (in.): SIONS (METRIC) (W2 ing (mm): (mm): Without Stand (mm): AL oons: SE CONTENTS: /Disposal:	21.3 x 12.7 x 1.4 KHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x2 or 2 (by country) Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from
Color Space Support:8 bit (6 bit + FRC)PhysicaAspect Ratio:16:9DIMENResponse Time (MPRT):1msPackagViewing Angles:17% horizontal, 17% verticalPhysicaSacklight Life (Hours):30000 Hrs (Min)PhysicaBacklight Life (Hours):100PhysicaCurvature:FlatFreeSyncPhysicaViewing Angles:100PhysicaSurfersh Rate (Hz):100PhysicaVariable Refresh Rate (Hz):100PhysicaSurfersh Rate (Hz):100PhysicaSurface Treatment:YesPhysicaColor Gamut:NTSC: 75% size (Typ) sRGB: 105% size (Jyp)	SIONS (METRIC) (W) ng (mm): (mm): Without Stand (mm): AL ons: SE CONTENTS: (Disposal:	KHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from
Decide Outpool OutpoolDuff (0 bit in the (0)Aspect Ratio:16:9Aspect Ratio:16:9Response Time (MPRT):1ms178° horizontal, 178° verticalPhysicaBacklight Life (Hours):30000 Hrs (Min)Curvature:FlatRefresh Rate (Hz):100Variable Refresh RateFreeSyncBlue Light Filter:YesPacKaPacKaColor Gamut:NTSC: 75% size (Typ) sRGB: 105% size / 99% coverage (Typ)PacKaSurface Treatment:Anti-Glare, Hard Coating (3H)OMPATIBILITYPC Resolution (max):1920x1080PC Operating System:120x1080PC Resolution (min):1920x1080PC Operating System:100 Content filed; macOSPC Operating System:1100Soff Action (max):11001Power in:DC Socket (Center Positive)UDIOInternal Speakers:200 Mode (Conserve):15WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower supply:External Power AdaptorIDITIONAL HARDWARE1Kensington Lock Slot:1	SIONS (METRIC) (W) ng (mm): (mm): Without Stand (mm): AL ons: SE CONTENTS: (Disposal:	KHXD) 600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from
Response Time (MPRT):1msPackagResponse Time (MPRT):1msPhysicaJiwing Angles:178° horizontal, 178° verticalPhysicaBacklight Life (Hours):30000 Hrs (Min)GENERRefresh Rate (Hz):100RegularVariable Refresh RateFreeSyncRegularBlue Light Filter:YesPACKAFilcker-Free:YesRecycleColor Gamut:0.275 mm (H) x 0.275 mm (V)RecycleSurface Treatment:Anti-Glare, Hard Coating (3H)WarranOMPATIBILITY1920x1080Windows 10/11 certified; macOSPC Resolution (max):1920x1080YesONNECTORVimolws 11/11 certified; macOSYesVGA:11DisplayPort:1DC Socket (Center Positive)UDIOIsw22WConsumption (typical):Consumption (typical):22W22WConsumption (max):25W3WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWARE1Kensington Lock Slot:1	ng (mm): (mm): Without Stand (mm): AL ons: SE CONTENTS: (Disposal:	600 x 395 x 112 540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4, Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Response finite (WFR1).InitsViewing Angles:178° horizontal, 178° verticalPhysicaBacklight Life (Hours):30000 Hrs (Min)PhysicaCurvature:FlatRegulalRefresh Rate (Hz):100RegulalVariable Refresh RateFreeSyncRegulalBlue Light Filter:YesPACKAFilcker-Free:YesRecycleColor Gamut:0.275 mm (H) x 0.275 mm (V)RecycleSurface Treatment:Anti-Glare, Hard Coating (3H)WarranOMPATIBILITY1920x1080PCPC Resolution (max):1920x1080PCPC Resolution (max):1920x1080PCPC Resolution (max):1920x1080PCPC Resolution (max):1920x1080PCPC Resolution (max):100 Conserve)PCVGA:11DisplayPort:1Power in:DC Socket (Center Positive)UDIOIsw2WConsumption (typical):2WConsumption (typical):2SWVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1Kensington Lock Slot:1	(mm): Without Stand (mm): AL ons: SE CONTENTS: (Disposal:	540 x 406 x 185 540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x ² or 2 (by country) Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from
Normal ParisesThe inductional propertiesBacklight Life (Hours):30000 Hrs (Min)Backlight Life (Hours):100Curvature:FlatRefresh Rate (Hz):100Elechnology:FreeSyncBlue Light Filter:YesColor Gamut:YesColor Gamut:0.275 mm (H) x 0.275 mm (V)Surface Treatment:Anti-Glare, Hard Coating (3H)OMPATIBILITY1920x1080PC Operating System:1920x1080PC Operating System:1920x1080PC Operating System:100VGA:11100DisplayPort:1DisplayPort:1DisplayPort:15WConsumption (typical):22WConsumption (typical):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1Kensington Lock Slot:1	Without Stand (mm): AL ons: SE CONTENTS: /Disposal:	540 x 322 x 36 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance with local, state or federal laws.
Backagin Line (Hours). 30000 His (kill) General Curvature: Flat Regulal Refresh Rate (Hz): 100 Regulal Variable Refresh Rate Echonology: FreeSync Regulal Blue Light Filter: Yes PACKA Color Gamut: Yes Recycla Color Gamut: 0.275 mm (H) x 0.275 mm (V) Recycla Surface Treatment: Anti-Glare, Hard Coating (3H) Warran OMPATIBILITY 1920x1080 PackA PC Resolution (max): 1920x1080 PackA PC Resolution (min): 1920x1080 PackA PC Resolution (min): 1920x1080 PackA PC Resolution (min): 1920x1080 PackA PC Operating System: 1920x1080 PackA PC Operating System: 1920x1080 PackA PC Resolution (min): 1920x1080 PackA PC Resolution (min): 1920x1080 PackA PGA: 1 PackA PDID I.42: 1 PackA PDipayPort:	NL ons: SE CONTENTS: (Disposal:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x' or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Durvature: Flat Refresh Rate (Hz): 100 Variable Refresh Rate Technology: FreeSync Blue Light Filter: Yes PACKA Color Gamut: Yes Color Gamut: 0.275 mm (H) x 0.275 mm (V) Pixel Size: 0.275 mm (H) x 0.275 mm (V) Surface Treatment: Anti-Glare, Hard Coating (3H) OMPATIBILITY 1920x1080 PC Operating System: 1920x1080 PC Operating System: 1920x1080 ONNECTOR 1 VGA: 1 Addit Size 1 Softex Color Gamut: 120x1080 PC Operating System: 1920x1080 ONNECTOR 1 VGA: 1 Addito Out: 1 HDMI 1.4: 1 DisplayPort: 1 Power in: DC Socket (Center Positive) UDIO 1 Consumption (typical): 2W Consumption (typical): 2W Consumption (max): 2SW Voltage: AC 100-240V Stand-by: <td< td=""><td>ons: SE CONTENTS: /Disposal:</td><td>REACH, WEEE, EAC, UKRSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x' or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from</td></td<>	ons: SE CONTENTS: /Disposal:	REACH, WEEE, EAC, UKRSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x' or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Wariable Refresh Rate Technology: FreeSync Blue Light Filter: Yes Flicker-Free: Yes Color Gamut: NTSC: 75% size (Typ) sRGB: 105% size / 99% coverage (Typ) Pixel Size: 0.275 mm (H) x 0.275 mm (V) Surface Treatment: Anti-Glare, Hard Coating (3H) OMPATIBILITY 1920x1080 PC Operating System: 1920x1080 ONNECTOR 1 VGA: 1 3.5mm Audio Out: 1 PC wer in: DC Socket (Center Positive) UDIO I UDIO I Consumption (typical): 22W Consumption (typical): 25W Voltage: AC 100-240V Stand-by: 0.3W Power Supply: External Power Adaptor DIDTIONAL HARDWARE 1	SE CONTENTS: /Disposal:	REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4, Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Variable Refresh Rate Technology:FreeSyncBlue Light Filter:YesPACKAFilcker-Free:YesRecycleColor Gamut:NTSC: 75% size (Typ) sRGB: 105% size / 99% coverage (Typ)RecyclePixel Size:0.275 mm (H) x 0.275 mm (V)WarranPixel Size:0.275 mm (H) x 0.275 mm (V)WarranOMPATIBILITY1920x1080WarranPC Resolution (max):1920x1080YesPC Operating System:Windows 10/11 certified; macOS testedYesONNECTOR1YesVGA:11ODIsplayPort:1Power in:DC Socket (Center Positive)JUDIOIUse MacQ (Conserve):15WEco Mode (Conserve):15WEco Mode (conserve):15WConsumption (typical):22WConsumption (typical):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1Kensington Lock Sloi:1	SE CONTENTS: /Disposal:	UKCA, BSMI, RCM, GEMS, KC, e- Standby, BIS VA2432-MHD x1, HDMI Cable (v1.4, Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Technology: Preesync Blue Light Filter: Yes Blue Light Filter: Yes Color Gamut: Yes Color Gamut: 0.275 mm (H) x 0.275 mm (V) Pixel Size: 0.275 mm (H) x 0.275 mm (V) Surface Treatment: Anti-Glare, Hard Coating (3H) OMPATIBILITY 1920x1080 PC Resolution (max): 1920x1080 PC Operating System: Windows 10/11 certified; macOS PC Operating System: 1920x1080 PC Operating System: 1920x1080 PC Operating System: 1920x1080 PC Operating System: 1920x1080 ONNECTOR 1 VGA: 1 10011 1.4: 1 DisplayPort: 1 Power in: DC Socket (Center Positive) UDIO 1 Internal Speakers: 2Watts x2 OWER 1 Eco Mode (Conserve): 15W Eco Mode (contimized): 18W Consumption (typical): 2SW Voltage: AC 100-240V Stand-by: 0.3W Power	/Disposal:	VA2432-MHD x1, HDMI Cable (v1.4 Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Flicker-Free: Yes Color Gamut: NTSC: 75% size (Typ) sRGB: 105% size / 99% coverage (Typ) Pixel Size: 0.275 mm (H) x 0.275 mm (V) Pixel Size: 0.275 mm (H) x 0.275 mm (V) Surface Treatment: Anti-Glare, Hard Coating (3H) OMPATIBILITY 1920x1080 PC Operating System: 1920x1080 PC Operating System: 1920x1080 PC Operating System: 1920x1080 PC Operating System: 1920x1080 ONNECTOR 1920x1080 VGA: 1 NTSC: 1 PC Operating System: 1920x1080 ONNECTOR 1 VGA: 1 PC Operating System: 1 PC Operating System: 1 PC Operating System: 1 VGA: 1 PC Operating System: 1 POWer Internal Speakers: 2 POWer Supplice: 1 PON ECTOR 2 Voltage: AC 100-240V	/Disposal:	Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Flicker-Free: Yes Color Gamut: NTSC: 75% size (Typ) sRGB: 105% size / 99% coverage (Typ) Recycle Pixel Size: 0.275 mm (H) x 0.275 mm (V) Warran Surface Treatment: Anti-Glare, Hard Coating (3H) Warran OMPATIBILITY 1920x1080 Warran PC Resolution (max): 1920x1080 PC PC Operating System: Windows 10/11 certified; macOS tested Mac@ Resolution (min): 1920x1080 PC Operating System: 1920x1080 NonNECTOR NonNECTOR NonNECTOR VGA: 1 1 Nongamma	/Disposal:	Quick Start Guide x1, Power plug x1 or 2 (by country) Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Dolor Gamut:size / 99% coverage (Typ)RecyclePixel Size:0.275 mm (H) x 0.275 mm (V)WarranSurface Treatment:Anti-Glare, Hard Coating (3H)WarranOMPATIBILITY1920x1080PC Resolution (max):1920x1080PC Operating System:Windows 10/11 certified; macOS testedWardows 10/11 certified; macOS testedPC Operating System:1920x1080PC Operating System:1920x1080ONNECTOR1VGA:1Nome Consumption (min):1920x1080ONNECTOR1VGA:1Nome Consumption (min):1DisplayPort:1Do Socket (Center Positive)UDIOUDIOInternal Speakers:2Watts x2OWER1Eco Mode (Conserve):15WEco Mode (continized):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWARE1Kensington Lock Slot:1		Please dispose of in accordance wit local, state or federal laws. *Warranty offered may differ from
Dolor Gamut:size / 99% coverage (Typ)RecyclePixel Size:0.275 mm (H) x 0.275 mm (V)WarranSurface Treatment:Anti-Glare, Hard Coating (3H)WarranOMPATIBILITY1920x1080PC Resolution (max):1920x1080PC Operating System:Windows 10/11 certified; macOS testedWardows 10/11 certified; macOS testedPC Operating System:1920x1080PC Operating System:1920x1080ONNECTOR1VGA:1Nome Consumption (min):1920x1080ONNECTOR1VGA:1Nome Consumption (min):1DisplayPort:1Do Socket (Center Positive)UDIOUDIOInternal Speakers:2Watts x2OWER1Eco Mode (Conserve):15WEco Mode (continized):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWARE1Kensington Lock Slot:1		local, state or federal laws. *Warranty offered may differ from
WarranWarranOMPATIBILITYPC Resolution (max):1920x1080Wac@ Resolution (max):1920x1080PC Operating System:Windows 10/11 certified; macOS testedWac@ Resolution (min):1920x1080PC Operating System:Windows 10/11 certified; macOS testedWac@ Resolution (min):1920x1080ONNECTOR1VGA:1VGA:110piplayPort:1Power in:DC Socket (Center Positive)UDIOUDIOUDIO1Eco Mode (Conserve):15WEco Mode (Conserve):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDTITONAL HARDWARE1Kensington Lock Slot:1	y:	*Warranty offered may differ from
Surface Treatment:Anti-Glare, Hard Coating (3H)OMPATIBILITYPC Resolution (max):1920x1080Wac® Resolution (max):1920x1080PC Operating System:Windows 10/11 certified; macOS testedPC Operating System:1920x1080PC Operating System:1920x1080VGA:1ONNECTORVVGA:1Nom Audio Out:1DisplayPort:1DisplayPort:1Dower in:DC Socket (Center Positive)UDIOVInternal Speakers:2Watts x2OWER1Eco Mode (Conserve):15WEco Mode (coptimized):18WConsumption (typical):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1Kensington Lock Slot:1	y:	
PC Resolution (max):1920x1080Mac® Resolution (max):1920x1080PC Operating System:Windows 10/11 certified; macOS testedMac@ Resolution (min):1920x1080ONNECTOR1VGA:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:DC Socket (Center Positive)Addio Out:2Watts x2Addie Conserve):15WEco Mode (Conserve):15WEco Mode (Conserve):22WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDTITIONAL HARDWARE1Kensington Lock Slot:1		
PC Resolution (max):1920x1080Mac® Resolution (max):1920x1080PC Operating System:Windows 10/11 certified; macOS testedMac@ Resolution (min):1920x1080ONNECTOR1VGA:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:1Addio Out:DC Socket (Center Positive)Addio Out:2Watts x2Addie Conserve):15WEco Mode (Conserve):15WEco Mode (Conserve):22WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDTITIONAL HARDWARE1Kensington Lock Slot:1		
Mac@ Resolution (max):1920x1080PC Operating System:Windows 10/11 certified; macOS testedMac@ Resolution (min):1920x1080ONNECTOR1VGA:1As5mm Audio Out:1HDMI 1.4:1DisplayPort:1Dewer in:DC Socket (Center Positive)UDIOUUnternal Speakers:2Watts x2OWER1Eco Mode (Conserve):15WEco Mode (conserve):15WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDTITONAL HARDWARE1		
PC Operating System:Windows 10/11 certified; macOS testedMac@ Resolution (min):1920x1080ONNECTOR1VGA:1Alson Audio Out:1HDMI 1.4:1DisplayPort:1Power in:DC Socket (Center Positive)UDIOUEco Mode (Conserve):15WEco Mode (Conserve):18WConsumption (typical):22WConsumption (typical):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1Kensington Lock Slot:1		
Cooperating system:testedMac@ Resolution (min):1920x1080ONNECTOR1VGA:13.5mm Audio Out:1HDMI 1.4:1DisplayPort:1Power in:DC Socket (Center Positive)UDIOUDIOInternal Speakers:2Watts x2OWER18WEco Mode (Conserve):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWARE1		
ONNECTOR VGA: 1 3.5mm Audio Out: 1 B.Mm Audio Out: 1 DisplayPort: DC Socket (Center Positive) Obewer in: DC Socket (Center Positive) UDIO U UDIO U OWER 2Watts x2 Eco Mode (Conserve): 15W Eco Mode (Conserve): 18W Consumption (typical): 22W Consumption (max): 25W Voltage: AC 100-240V Stand-by: 0.3W Power Supply: External Power Adaptor DITIONAL HARDWARE Kensington Lock Slot:		
ONNECTOR VGA: 1 3.5mm Audio Out: 1 B.Mm Audio Out: 1 DisplayPort: DC Socket (Center Positive) Obewer in: DC Socket (Center Positive) UDIO U UDIO U OWER 2Watts x2 Eco Mode (Conserve): 15W Eco Mode (Conserve): 18W Consumption (typical): 22W Consumption (max): 25W Voltage: AC 100-240V Stand-by: 0.3W Power Supply: External Power Adaptor DITIONAL HARDWARE Kensington Lock Slot:		
VGA:13.5mm Audio Out:14.DMI 1.4:1DisplayPort:1Power in:DC Socket (Center Positive)UDIOUSAUTHOR2Watts x2OWER15WEco Mode (Conserve):15WEco Mode (Conserve):22WConsumption (typical):25WConsumption (max):25WVoltage:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1		
B.Smm Audio Out:1B.Smm Audio Out:1HDM 1.4:1DisplayPort:1DisplayPort:DC Socket (Center Positive)UDIO2Watts x2OWER2Watts x2Eco Mode (Conserve):15WEco Mode (conserve):18WConsumption (typical):22WConsumption (max):25WStand-by:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1		
HDMI 1.4:1DisplayPort:1Power in:DC Socket (Center Positive)UDIOUSAUTHARDARD2Watts x2OWER15WEco Mode (Conserve):15WEco Mode (Conserve):18WConsumption (typical):22WConsumption (max):25WStand-by:0.3WPower Supply:External Power AdaptorDDTITONAL HARDWARE1		
DisplayPort:1Power in:DC Socket (Center Positive)UDIOUlternal Speakers:2Watts x22Watts x2OWER15WEco Mode (Conserve):15WEco Mode (optimized):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDITIONAL HARDWARE1		
Power in:DC Socket (Center Positive)UDIOUnternal Speakers:2Watts x2OWEREco Mode (Conserve):15WEco Mode (conserve):2WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDTITONAL HARDWARE1		
UDIOInternal Speakers:2Watts x2OWER15WEco Mode (Conserve):15WEco Mode (optimized):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWARE1		
Additional Speakers:2Watts x2OWER15WEco Mode (Conserve):15WEco Mode (optimized):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWAREKensington Lock Slot:		
OWEREco Mode (Conserve):15WEco Mode (optimized):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWAREKensington Lock Slot:		
Eco Mode (Conserve):15WEco Mode (optimized):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWAREKensington Lock Slot:		
Eco Mode (optimized):18WConsumption (typical):22WConsumption (max):25WVoltage:AC 100-240VStand-by:0.3WPower Supply:External Power AdaptorDDITIONAL HARDWAREKensington Lock Slot:		
Consumption (typical): 22W Consumption (max): 25W voltage: AC 100-240V Stand-by: 0.3W Power Supply: External Power Adaptor DDITIONAL HARDWARE Kensington Lock Slot:		
Consumption (typical): 22W Consumption (max): 25W voltage: AC 100-240V Stand-by: 0.3W Power Supply: External Power Adaptor DDITIONAL HARDWARE Kensington Lock Slot:		
Consumption (max): 25W Voltage: AC 100-240V Stand-by: 0.3W Power Supply: External Power Adaptor DDITIONAL HARDWARE Kensington Lock Slot:		
Voltage: AC 100-240V Stand-by: 0.3W Power Supply: External Power Adaptor DDITIONAL HARDWARE Kensington Lock Slot:		
Stand-by: 0.3W Power Supply: External Power Adaptor DDITIONAL HARDWARE Kensington Lock Slot: 1		
Power Supply: External Power Adaptor DDITIONAL HARDWARE Kensington Lock Slot: 1		
ADDITIONAL HARDWARE Kensington Lock Slot: 1		
Kensington Lock Slot: 1		
5		
5		
· · · · ·		
Koy 1 (fourite) Koy 2 Koy 4		
Physical Controls: Key 7 (lavorite), Key 2, Key 3, Key 4, Key 5 (power)		
Input Select, Audio Adjust,		
On Screen Display: ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
PERATING CONDITIONS		
Temperature: 32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing): 20% to 90%		
VALL MOUNT		
VESA Compatible: 75 x 75 mm		
NPUT SIGNAL		
Frequency Horizontal: (v1.4): 30 ~ 115KHz, DisplayPort (v1.2): 30 ~ 115KHz		
Frequency Vertical: RGB Analog: 48 ~ 75Hz, HDMI (v1.4): 48 ~ 100Hz, DisplayPort (v1.2): 48 ~ 100Hz		
IDEO INPUT		
TMDS - HDMI (v1.4) PCI-E -		
Digital Sync: DisplayPort (v1.2)		
DisplayPort (v1.2)		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

