

SPECIFICAȚII TEHNICE (F4.1)

Nr.	ocds-b3wdp1-MD-1557734127548	4 iun 2019	Alternativa nr.-
Denumirea licitației:		Lot 1-23	Pagina 1 din 1
Serviciul de Informații și Securitate al RM			

LOT	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
Lot 1	Calculator staționar	Atol G5400	Moldova	Accent Electronic	Black, ATX/MicroATX, USB 3.0x1, USB 2.0x1, HD Audio x1, mic x1, 3x3.5 drive bays, 1x2.5 drive bays, 1x5.25 drive bays, buclăpentrulacățpeambeleprti. ATX 12 V, v2.31, 650W, 220-240V, 20+4 pin 1PCS/CPU 12V 4+4pin, 4 xSata, 4xPCI-E, 1x120 mm cooler/Active PFC, Intelligent fan speed control, PWM auto fan speed temp-controlled, 21 dBA. ATX, 1151, Suport windows 7/10 x32/x64, DDR4 2xSlots, 1xVGA, 1xDVI, 1xHDMI, 2xPCI-E X1, 1xPCI-E x16, PCI, 4xSATAIII 6.0 Gb/s, 2xUSB 3.1, 4xUSB2.0/GLAN RJ-45 with led/ Audio HD, all solid state capacitors. 2x3.3GHz, 3Mb, 1151, 8GT/s, HD Graphics, 14 nm, 54W, DDR4, DDR3L, support ECC, (Dual core)/Suport windows 7/10 x32/x64. 1151/ fan 120x25 mm/900-1600 rpm/55.5 cfm/125 W/ 17.8-26.1 dBA/ input 1,56 W. 4 GB DDR4 2400 MHz PC19200. HDD 500GB, SATA-III (6 Gb/s), 7200RPM, 32MB, 3.5".	Calculator Atol G5400 DEEPCOOL "SMARTER" Micro-ATX Case, without PSU, fully black painted interior, VGA Compatibility: 320mm, CPU Cooler Compatibility: 165mm, 1x 2.5" Drive Bays, 1xUSB3.0, 1xUSB2.0 /Audio, Black PSU XILENCE XP700R6, 700W, "Performance C" Series, ATX 2.3.1, Active PFC, 120mm fan,+12V (30A/30A), 20+4 Pin, 6x SATA, 2x PCI-E 6+2pin, 2x Peripheral, ErP2014 norm, Black GIGABYTE H310M S2H, Socket 1151, Intel® H310 (9th/8th Gen CPU), Dual 2xDDR4-2666, CPU Intel graphics, VGA, DVI, HDMI, 1xPCIe X16, 4xSATA3, 1xM.2, 2xPCIe X1, ALC887 HDA, GbE LAN, 4xUSB3.1, mATX Intel® Pentium® Gold G5400, S1151, 3.7GHz (2C/4T), 4MB Cache, Intel® UHD Graphics 610, 14nm 54W, tray DEEPCOOL Cooler "GAMMAXX 300R", Socket 775/1150/1151/2011 & AM4/FM2/AM3, up to 130W, 120x120x25mm, Semi-transparent fan with Red LED, 900~1600rpm, 17.8~21dBA, 55.5CFM, 4 pin, PWM, Hydro Bearing, 3 heatpipes direct contact 4GB DDR4-2400 GOODRAM, PC19200, CL17, 1.2V 3.5" HDD 500GB Toshiba DT01ACA050, Desktop™, 7200rpm, 32MB, SATAIII	
Lot 2	Calculator staționar asamblat la uzina producătorului	V530	China	Lenovo	Carcasași componente interne asamblate la uzina producătorului iDestkopBlack .tower, 5.25" ODD bays, 3.5" external bays, internal bays 3.5", 1x2.5", USB2.0, USB3.0, audio jack.300 W.1xPCI, 2x PCI Express x1, 1xPC Express x16, DVI, VGA, 4xUSB 2.0, 4x USB 3.1, Audio IN/OUT, Gigabit Ethernet, No WLAN , No ODD.CPU 2x3.5 Ghz, 3 MB, 1151, Cooler CPU. Memory 4GB (Up to 32 GB of Dual-channel) DDR4 2400 MHz. 1 TB 3.5-inch 7200 RPM.În set cu blocul de sistemaaasamblat de la uzina producătorului. 21,5" black 1920x1080 full HD, twisted nematic+film, LED, 200 cd/m2, mat, 5 ms, 100000000:1, unghiulobservăriipelaturile 100/70, 1xD-sub, 1xDVI, 1xHDMI, ajustareapozіțieiecranuluiînclinare, 22 W, 60 Hz, cablu VGA, DVI, cablu de alimentare, garanția 3 ani (VGA, DVI, HDMI). Mouse, keyboard incomplet cu blocul de sistemaaasamblat de la uzina producătorului. Microsoft Windows 10 pro x32/x64. En	Lenovo V530-15ICB ProcessorPentium Gold G5400 (2C / 4T, 3.7GHz, 4MB) GraphicsIntegrated Intel UHD Graphics 610 Memory4GB DIMM DDR4-2666 Storage1TB HDD 7200rpm 3.5" SATA6Gb/s Optane MemoryNone Optical9.0mm DVD±RW Media Reader7-in-1 EthernetIntegrated Keyboard / MouseUSB Black / USB Black Power Supply180W 85% Adapter Operating SystemWindows 10 Pro 64 ThinkVision S22e-19 21.5-inch LED Backlit LCD Monitor	
Lot 3	Laptop	-	-	-	-	-	
Lot 4	Monitor (cuboxeincluse)				Monitor BLACK 23,8", IPS-ADS LED, 250 cd/m2, 1000:1, 10M:1, 178/178 grade vizibilitatea, 5 ms, audio inclus 2x2 W, VGA, DVI, HDMI, Cablu VGA, Cablu DVI, Cablu HDMI, bloc de alimentareincorporat.	23.8" ACER IPS LED Nitro VG240Y ZeroFrame Black/Red (1ms, 100M:1, 250cd, 1920x1080, 178°/178°, VGA, HDMIx2 ,Speakers 2 x 2W, CrystalBrite, VESA) [UM.QV0EE.001]	
Lot 5	Tastieră	-	-	-	-	-	
Lot 6	Mouse	-	-	-	-	-	
Lot 7	UPS	Pro 1000	China	Sven	Line Interactive/600w/1000va/220-240V/ AVR/CPU controled, battery 12v/7A, 2puteri de ieșire/alarmăsonoră, protecție la suprasarcină, protecție la puls de înaltătensiune, protecțieîmpotrivascurtircuítelor.	SVEN Pro 1000 (USB), Line-interactive UPS with AVR, 1000VA /720W, 3x Schuko outlets, 2x7AH, AVR: 175-280V, USB, RJ-45, Cold start function, Black	
Lot 8	Surge	SF-05L	China	Sven	Surge Protector 5 Sockets, 5 m, BLACK, plăcibimetalice, protecție la suprasarcină, corpantiincendiar.	Surge Protector SVEN SF-05L, 5 Sockets, 5.0m, Black	
Lot 9	Surge	-	-	-	-	-	
Lot 10	Surge	-	-	-	-	-	

Lot 11	Imprimantă	-	-	-	-	-
Lot 12	Imprimantă	-	-	-	-	-
Lot 13	Scanner	-	-	-	-	-
Lot 14	Scanner				Scanner, USB 2.0, compatibil Windows 7/10 x32/x64, A4, 4800x4800, 19200x19200 dpi, 48 bit/24 bit, alimentare USB, Posibilitate de scanare a dosarelor de dimensiuni mari.	Scanner Canon Canoscan LiDE 400, CIS sensor, 3-colour (RGB) LED, 4800 x 4800dpi, 48-bit colour, 8-seconds - Color/A4/300dpi, USB 2.0, Upright scanning, PDF files creation function, Sent to Cloud, Scan thick documents Z-lid, D:250x367x42mm, W:1,7kg
Lot 15	Boxe	-	-	-	-	-
Lot 16	Switch	-	-	-	-	-
Lot 17	10 G SFP + 5m DAC	-	-	-	-	-
Lot 18	UPS				230V Rackmount, Line-interactive, Pre-Installed SmartSlot Card AP9630, Output Power Capacity 4000 Watts/5000VA, Max Configurable Power 4000 Watts/5000VA, Nominal Output Voltage 230V, Output Voltage Note Configurable for 220:230 or 240 nominal output voltage, Output Voltage Distortion Less than 5% at full load, Output Frequency(sync to mains) 47-53 Hz for 50 Hz nominal, Other Output Voltages 220,240V, Output Connections (2) IEC 320 C19 (Battery Backup), (4) IEC Jumpers(BatteryBackup), (8)IEC 320 C13, Nominal Input Voltage 230V, Input Frequency 50/60Hz +/- 3Hz(auto sensing), Input Connections Hard Wire 3-wire, Input voltage range for main operations 160-286V, Input voltage adjustable range for mains operation 151-302V, Battery Type VRLA, Typical recharge time 3 hour, Replacement Battery RBC55, RBC Quantity 2, Interface Port DB-9 RS-232, SmartSlot, Pre-Installed SmartSlotCards AP9630, Control panel LED status display with On Line: OnBattery: ReplaceBattery and Overload indicators, AudibleAlarm Audible and visible alarms:configurable delays, Surge energy rating 480 Joules, Filtering Full time multi-pole noise filtering:0,3% IEEE surge let-through: zero clamping response time:meets UL 1449, Maximum Height 222.0 mm, Maximum Width 483.0 mm, Maximum Depth 666.0 mm, Rack Height 5U, Net Weight 97.73 kg, Color Black	Output power capacity 4.0kWatts / 5.0kVA, Max Configurable Power (Watts) 4.0kWatts / 5.0kVA, Nominal Output Voltage 230V, Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage Efficiency at Full Load,96.0 %, Output Voltage Distortion Less than 5% at full load, Output Frequency (sync to mains)47 - 53 Hz for 50 Hz nominal Other Output Voltages, 220, 240, Topology Line Interactive, Waveform type Sine wave, Output Connections(4) IEC Jumpers (Battery Backup)(2) IEC 320 C19 (Battery Backup)(8) IEC 320 C13 (Battery Backup), Interface Port(s) DB-9 RS-232, SmartSlot, Pre-Installed SmartSlot™ Cards AP9630, Battery type VRLA, Typical recharge time 3hour(s), Replacement Battery RBC55
Lot 19	Dulap comunicațional	-	-	-	-	-
Lot 20	Sistem de operare				Microsoft Windows 10 pro x32/x64, En, licența nelimitată.	Windows 10 Professional 64-bit English 1pk DSP OEI DVD
Lot 21	Aplicație de prelucrare imagine	-	-	-	-	-
Lot 22	Aplicație de video redactare	-	-	-	-	-
Lot 23	Aplicație prelucrare text	-	-	-	-	-
Lot 24	Aplicație prelucrare text	-	-	-	-	-
	TOTAL					

Semnat: _____

Nume: Eugeniu Cobilas

În calitate de: Director general

Ofertantul: „Accent Electronic” SA

Adresa: or. Chișinău, str. Bulgară 33/1

Data: 4 iun 2019