

UH 300



AUTOCON® III 300,
power supply 220 – 240 VAC, 50/60 Hz, including mains cord

HF connecting sockets unipolar:

1x 3-pin US type

1x 5 mm connector KARL STORZ/Erbe VIO

HF connecting sockets bipolar:

1x 2-pin US type (28.58)

2x KARL STORZ/Erbe VIO

Connecting socket:

Neutral electrode 2-pol

Can be integrated into OR1™ with KARL STORZ OR1™ SCB control WU 300
System requirements: SCB R-UI Software Release 20090001-46 or higher

Image View – UH 300



Close

400 A



Image View – 400 A









Close



Two-Pedal HF Footswitch,
with button for switchover function, for use with HF generators



	UG 310	Isolation Transformer , 200 – 240 V, 2000 VA, with 3 special mains socket, automatic cutout, 3 grounding plugs, Dimensions in mm: 330 x 90 x 495 (w x h x d), for use with Equipment Carts UG xxx
	UG 300	Same , 100 – 120 V
	UG 410	Earth Leakage Monitor , 200 – 240 V, for mounting to equipment carts, Control panel dimensions: 44 x 80 x 29 mm (w x h x d), for use with Isolation Transformer UG 310
	UG 400	Earth Leakage Monitor , 100 – 120 V, for mounting to equipment carts, Control panel dimensions: 44 x 80 x 29 mm (w x h x d), for use with Isolation Transformer UG 300
	UG 700	Mains Cord , with angled plug, length 100 cm
	20 0102 70	Potential Equipotential Cable , length 500 cm
	20 0103 70	Potential Equipotential Cable , length 200 cm
	20 0105 70	Potential Equipotential Cable , length 150 cm
	20 0106 70	Potential Equipotential Cable , length 100 cm
	29005 PA-DR	Potential Equipotential Cable Set , for equipment carts, for 5 units, including Potential Equipotential Cable 5x 20 0106 70, 1x 20 0105 70, 1x 20 0102 70 for 5 units, for use with COR equipment carts and Equipment Cart 29005 DRB/DRS
	UG 605	Keyboard Tray , narrow, for mounting under narrow Shelf UG 603, load capacity max. 10 kg, Dimensions: 430 x 480 mm (w x d), for use with Equipment Carts UG xxx
	UG 606	Keyboard Tray , wide, for mounting under wide Shelf UG 604, load capacity max. 10 kg, Dimensions: 630 x 480 mm (w x d), for use with Equipment Carts UG xxx

Accessories

Bipolar High Frequency Cords,
for use with Bipolar Coagulation Forceps

Bipolar High Frequency Cords













KARL STORZ High Frequency
Instrument Surgical Unit

	847000 E	Bipolar High Frequency Cord , for AUTOCON® II 400 SCB systems (111, 113, 115, 122, 125), AUTOCON® II 200, AUTOCON® II 80, KARL STORZ Coagulator 26021 B/C/D, 860021 B/C/D, 27810 B/C/D, 28810 B/C/D, AUTOCON® systems (50, 200, 350), Erbe-Coagulator, T and ICC series, length 300 cm
	847000 A	Bipolar High Frequency Cord , with 2x 4 mm banana plug for KARL STORZ Coagulator 26020 XA/XB and Valleylab, length 300 cm
	847000 M	Bipolar High Frequency Cord , for Martin and Berchtold coagulators, length 300 cm
	847000 T	Bipolar High Frequency Cord , for Siemens coagulator from model Radiotom 804 upwards, for KARL STORZ bipolar coagulation forceps, length 300 cm
	847000 V	Bipolar High Frequency Cord , for KARL STORZ AUTOCON® II 400 SCB systems (112, 114, 116, 122, 125) and Valleylab coagulators, length 300 cm

High Frequency Surgical Units AUTOCON® see chapter 12, UNITS

Accessories for AUTOCON® III 400

	Art. No.	Description
	UF 901	One-Pedal Footswitch , with button for switchover function, for use with HF generators
	UF 902	Two-Pedal Footswitch , with button for switchover function, for use with HF generators
	UH 801	Bipolar High Frequency Cord , 400 cm with coding system, for use with KARL STORZ bipolar resectoscopes, and AUTOCON® III 400 units
	<u>27805</u>	Neutral Electrode , of conductive silicone with 2 rubber ties for fastening, contact surface A = 500 cm ² , for use with Connecting Cable 27806 UR
	<u>27806 UR</u>	Connecting Cable , for connecting Neutral Electrodes 27805 and 860021 E, length 300 cm
	27802	Neutral Electrode , for single use, contact surface divided into two, A = 169 cm ² , package of 50, Connecting Cable 27806 US required
	27806 US	Connecting Cable , for connecting single-use Neutral Electrode 27802, length 500 cm
	26 5200 43	Electrode Handle , with 2 buttons for activating the unipolar generator, yellow button: unipolar cutting, blue button: unipolar coagulation (High Frequency Cable 26 5200 45 required).
	26 5200 45	High Frequency Cable , for Electrode Handle 26 5200 43, length 500 cm
	26 5200 46	Electrode Handle , without buttons, with integrated connecting cable, length 300 cm; activation of the high frequency surgical unit via footswitch



Stand-alone devices

The COR mobile stand provides a good solution for the flexible positioning of stand-alone devices (e.g., HF generator, laser).



UG910
UG810
UG815
UG902

COR HF Mobile Stand

Top Cover, for COR mobile stand

Equipment Rail, for COR mobile stand

Footswitch Holder, for use with

Two-Pedal HF Footswitch UF902



UG916
UG810

COR Laser Mobile Stand

Top Cover, for COR mobile stand



UG912

COR Mobile Stand, high,
rides on 4 antistatic dual wheels, with locking brakes,
high beam module incl. cable manager and handle,
including:

UG804

Subrack, for COR mobile stand, high

UG811

Top Cover Monitor Holder, for COR mobile stand

UG854

Stainless Steel Tube, for COR mobile stand, length 400 mm

UG857

Monitor Module, for COR mobile stand

UG821

Shelf, wide, for COR mobile stand



UG913

COR Gastro Mobile Stand, high,
rides on 4 antistatic dual wheels, with locking brakes,
high beam module incl. cable manager and handle,
including:

UG804

Subrack, for COR mobile stand, high

UG811

Top Cover Monitor Holder, for COR mobile stand

UG854

Stainless Steel Tube, for COR mobile stand, length 400 mm

UG857

Monitor Module, for COR mobile stand

UG862

Drawer, wide, for COR mobile stand

UG816

Pump Holder, for COR mobile stand



UG914

COR Airway Mobile Stand, high,
rides on 4 antistatic dual wheels, with locking brakes,
high beam module incl. cable manager and handle,
including:

UG804

Subrack, for COR mobile stand, high

UG811

Top Cover Monitor Holder, for COR mobile stand

UG815

Equipment Rail, for COR mobile stand

UG854

Stainless Steel Tube, for COR mobile stand, length 400 mm

UG857

Monitor Module, for COR mobile stand

UG862

Drawer, wide, for COR mobile stand



UG915

COR C-MAC® Mobile Stand, high,
rides on 4 antistatic dual wheels, with locking brakes,
high beam module incl. cable manager and handle,
including:

UG804

Subrack, for COR mobile stand, high

UG811

Top Cover Monitor Holder, for COR mobile stand

UG815

Equipment Rail, for COR mobile stand

UG854

Stainless Steel Tube, for COR mobile stand, length 400 mm

UG862

Drawer, wide, for COR mobile stand

ET43-303127

Cross Tube Adaptor

ET43-302703

Stainless Steel Round Pipe, length 250 mm