



DATA SHEET

Lightspeed. Solid. Impressive.

NyTRO 3000 SAS SSD Series

The Seagate® NyTRO® 3000 SAS SSD Series includes the next generation of high-capacity, high-performance SAS SSDs designed with endurance offerings optimised for demanding enterprise applications and improved TCO.



Key Features and Benefits

- Dual-port 12 Gb/s SAS interface
- Industry-leading storage density range up to 15 TB
- Ultra-fast performance of up to 2,100 MB/s

Best-Fit Applications

- Server virtualisation
- OLTP databases
- Software-defined storage
- All flash arrays
- Caching and tiering



Enhanced Reliability, Data Protection, and Security

Seagate has decades of enterprise SAS expertise in mission-critical applications. The NyTRO 3000 SSD Series helps deliver exceptional data protection and reliability with full internal and external data path protection (T10 DIF), advanced ECC algorithms, media lifecycle management, and other techniques for extending flash memory life. Advanced power-loss data protection helps maintain data integrity in the event of unexpected power interruptions. Advanced security levels to prevent unauthorised access to a drive and safeguard stored data include Seagate Downloads & Diagnostics, TCG-compliant Self-Encrypting Drive and government-grade FIPS/Common Criteria tamper-resistant drive.¹

Industry-Leading Performance up to 2,100 MB/s

The NyTRO 3000 SSD Series delivers ultra-fast, consistent, and easily scalable performance that saturates dual 12 Gb/s SAS bandwidth, providing an effective 24 Gb/s interface with dual-port dynamic configurations. By removing the storage bottleneck, overall system and application responsiveness is significantly improved.

High-Capacity Solution With Multiple Endurance Offerings

Enterprise applications have different storage workload requirements. Databases or virtualisation with a typically mixed read/write workload require the highest random read/write IOPS, ultra-low latency, and high endurance. Content streaming applications demand high sequential read throughput and high storage density at the lowest cost per gigabyte. The NyTRO 3000 SSD Series offers an industry-leading range of capacities up to 15 TB in a 2.5-inch form factor to increase enterprise storage density in data centres. It also enables lower TCO by offering endurance categories to match cost and performance requirements of all enterprise workloads.

¹ Self-Encrypting Drives (SED) are not available in all models or countries. May require TCG-compliant host or controller support.



| Specifications | Nytro 3530 — Light Endurance | | | |
|--|------------------------------|--------------------|--------------------|--------------------|
| Capacity | 3.2TB | 1.6TB | 800GB | 400GB |
| Standard Model Number | XS3200LE10003 | XS1600LE10003 | XS800LE10003 | XS400LE10003 |
| Seagate Secure™ SED Model ¹ | XS3200LE10013 | XS1600LE10013 | XS800LE10013 | XS400LE10013 |
| Seagate Secure FIPS 140-2/Common Criteria Model ¹ | — | XS1600LE10023 | — | — |
| Features | | | | |
| Interface | Dual 12 Gb/s SAS | Dual 12 Gb/s SAS | Dual 12 Gb/s SAS | Dual 12 Gb/s SAS |
| NAND Flash Type | 3D eMLC | 3D eMLC | 3D eMLC | 3D eMLC |
| Form Factor | 2.5 in × 7 mm | 2.5 in × 7 mm | 2.5 in × 7 mm | 2.5 in × 7 mm |
| Performance — Single Port 12 Gb/s | | | | |
| Sequential Read (MB/s) Sustained, 128 KB ² | 1100 | 1100 | 1100 | 1100 |
| Sequential Write (MB/s) Sustained, 128 KB ² | 970 | 970 | 910 | 800 |
| Random Read (IOPS) Sustained, 4 KB ² | 200,000 | 200,000 | 200,000 | 135,000 |
| Random Write (IOPS) Sustained, 4 KB ² | 60,000 | 80,000 | 80,000 | 45,000 |
| Random 30% Write (IOPS) Sustained, 4 KB ² | 160,000 | 180,000 | 170,000 | 85,000 |
| Performance — Dual Port 12 Gb/s | | | | |
| Sequential Read (MB/s) Sustained, 128 KB ² | 2,100 | 2,100 | 2,100 | 2,000 |
| Sequential Write (MB/s) Sustained, 128 KB ² | 1,400 | 1,400 | 1,200 | 810 |
| Random Read (IOPS) Sustained, 4KB ² | 240,000 | 240,000 | 230,000 | 135,000 |
| Random Write (IOPS) Sustained, 4KB ² | 60,000 | 80,000 | 80,000 | 45,000 |
| Random 30% Write (IOPS) Sustained, 4KB ² | 160,000 | 180,000 | 170,000 | 85,000 |
| Endurance/Reliability | | | | |
| Lifetime Endurance (Drive Writes per Day) | 3 | 3 | 3 | 3 |
| Total Bytes Written (TB) | 17,500 | 8,700 | 4,300 | 2,100 |
| Non-recoverable Read Errors per Bits Read | 1 per 10E18 | 1 per 10E18 | 1 per 10E18 | 1 per 10E18 |
| Annualised Failure Rate (AFR) | 0.35% | 0.35% | 0.35% | 0.35% |
| Limited Warranty (years) | 5 | 5 | 5 | 5 |
| Power Management | | | | |
| +5/+12 V Max Start Current (A) | 0.80/0.21 | 0.80/0.21 | 0.80/0.21 | 0.80/0.21 |
| Average Idling Power (W) | 4.4 | 4.4 | 4.4 | 4.4 |
| Physical | | | | |
| Height (mm/in, max) ⁴ | 7 mm/0.276 in | 7 mm/0.276 in | 7 mm/0.276 in | 7 mm/0.276 in |
| Width (mm/in, max) ⁴ | 70.1 mm/2.76 in | 70.1 mm/2.76 in | 70.1 mm/2.76 in | 70.1 mm/2.76 in |
| Depth (mm/in, max) ⁴ | 100.45 mm/3.955 in | 100.45 mm/3.955 in | 100.45 mm/3.955 in | 100.45 mm/3.955 in |
| Weight (lb/g) | 85 g/0.187 lb | 85 g/0.187 lb | 85 g/0.187 lb | 80 g/0.176 lb |
| Carton Unit Quantity | 10 | 10 | 10 | 10 |
| Cartons per Pallet / Cartons per Layer | 90/9 | 90/9 | 90/9 | 90/9 |

¹ Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

² All performance measured at queue depth of 32 per PHY at beginning of life. System application performance may vary based on SAS host and prior system workload.

³ These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223 (SAS models).



| Specifications | Nytro 3330 — Scaled Endurance | | | | |
|--|-------------------------------|--------------------|--------------------|--------------------|--------------------|
| Capacity | 15.36TB | 7.68TB | 3.84TB | 1.92TB | 960GB |
| Standard Model Number | XS15360SE70103 | XS7680SE70103 | XS3840SE10103 | XS1920SE10103 | XS960SE10003 |
| Seagate Secure™ SED Model ¹ | XS15360SE70113 | XS7680SE70113 | XS3840SE10113 | XS1920SE10113 | XS960SE10013 |
| Seagate Secure FIPS 140-2/Common Criteria Model ¹ | XS15360SE70143 | — | — | XS1920SE10123 | — |
| Features | | | | | |
| Interface | Dual 12 Gb/s SAS | Dual 12 Gb/s SAS | Dual 12 Gb/s SAS | Dual 12 Gb/s SAS | Dual 12 Gb/s SAS |
| NAND Flash Type | 3D eTLC | 3D eTLC | 3D eTLC | 3D eTLC | 3D eTLC |
| Form Factor | 2.5 in x 15 mm | 2.5 in x 15 mm | 2.5 in x 7 mm | 2.5 in x 7 mm | 2.5 in x 7 mm |
| Performance — Single Port 12 Gb/s | | | | | |
| Sequential Read (MB/s) Sustained, 128 KB ² | 860 | 1,000 | 1100 | 1100 | 1100 |
| Sequential Write (MB/s) Sustained, 128 KB ² | 920 | 980 | 930 | 810 | 860 |
| Random Read (IOPS) Sustained, 4 KB ² | 102,000 | 180,000 | 180,000 | 180,000 | 150,000 |
| Random Write (IOPS) Sustained, 4 KB ² | 15,000 | 55,000 | 50,000 | 40,000 | 28,000 |
| Random 30% Write (IOPS) Sustained, 4 KB ² | 46,000 | 150,000 | 130,000 | 105,000 | 72,000 |
| Performance — Dual Port 12 Gb/s | | | | | |
| Sequential Read (MB/s) Sustained, 128 KB ² | 1,300 | 1,800 | 2,100 | 2,100 | 2,100 |
| Sequential Write (MB/s) Sustained, 128 KB ² | 1,000 | 1,100 | 1,100 | 900 | 870 |
| Random Read (IOPS) Sustained, 4KB ² | 102,000 | 240,000 | 240,000 | 240,000 | 150,000 |
| Random Write (IOPS) Sustained, 4KB ² | 15,000 | 55,000 | 50,000 | 40,000 | 28,000 |
| Random 30% Write (IOPS) Sustained, 4KB ² | 46,000 | 150,000 | 130,000 | 105,000 | 72,000 |
| Endurance/Reliability | | | | | |
| Lifetime Endurance (Drive Writes per Day) | 1 | 1 | 1 | 1 | 1 |
| Total Bytes Written (TB) | 27,000 | 13,600 | 6,800 | 3,400 | 1,700 |
| Non-recoverable Read Errors per Bits Read | 1 per 10E18 | 1 per 10E18 | 1 per 10E18 | 1 per 10E18 | 1 per 10E18 |
| Annualised Failure Rate (AFR) | 0.35% | 0.35% | 0.35% | 0.35% | 0.35% |
| Limited Warranty (years) | 5 | 5 | 5 | 5 | 5 |
| Power Management | | | | | |
| +5/+12 V Max Start Current (A) | 0.80/0.21 | 0.80/0.21 | 0.80/0.21 | 0.80/0.21 | 0.80/0.21 |
| Average Idling Power (W) | 4.4 | 4.4 | 4.4 | 4.4 | 4.4 |
| Physical | | | | | |
| Height (mm/in, max) ⁴ | 15 mm/0.591 in | 15 mm/0.591 in | 7 mm/0.276 in | 7 mm/0.276 in | 7 mm/0.276 in |
| Width (mm/in, max) ⁴ | 70.1 mm/2.76 in | 70.1 mm/2.76 in | 70.1 mm/2.76 in | 70.1 mm/2.76 in | 70.1 mm/2.76 in |
| Depth (mm/in, max) ⁴ | 100.45 mm/3.955 in | 100.45 mm/3.955 in | 100.45 mm/3.955 in | 100.45 mm/3.955 in | 100.45 mm/3.955 in |
| Weight (lb/g) | 165 g/0.364 lb | 165 g/0.364 lb | 85 g/0.187 lb | 80 g/0.176 lb | 80 g/0.176 lb |
| Carton Unit Quantity | 10 | 10 | 10 | 10 | 10 |
| Cartons per Pallet / Cartons per Layer | 90/9 | 90/9 | 90/9 | 90/9 | 90/9 |

¹ Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

² All performance measured at queue depth of 32 per PHY at beginning of life. System application performance may vary based on SAS host and prior system workload.

³ These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223 (SAS models).

seagate.com



| | |
|---------------------------------|---|
| AMERICAS | Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000 |
| ASIA/PACIFIC | Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888 |
| EUROPE, MIDDLE EAST, AND AFRICA | Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00 |

© 2018 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Nytro, the Nytro logo, Seagate Secure, and the Seagate Secure logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import, and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1950.6-1809GB September 2018