

METALOIDAS

JOINT STOCK COMPANY

Rėkyvos str. 21a, 78109 Šiauliai, Lithuania, VAT No. 453761113,
Tel.(+370-41)507680, fax.(+370-41)507681, GSM (+370-686) 81234
AB Bankas "Swedbank", account nr. LT 227300010077178292

TYRE RECYCLING PLANT

Pakruojo str. 44, 76126 Šiauliai, Lithuania, tel.(+370-41) 50-76-80, fax.(+370-41)50-76-81
E-mail: rita@metaloidas.lt; www.metaloidas.lt

2016.11.16

CERTIFICATE OF CONFORMITY

Producer:

JSC „Metaloidas“
Pakruojo str.. 44, Siauliai, Lithuania

Production address:

UAB „Metaloidas“
Pakruojo g. 44, Šiauliai, Lietuva

Institution of Certification:

MEEI Kft. Certification
Member of TUV Rheinland Group
Vaci ut 48/a-b Budapest, H-1132, Hungary

Product review:

Rubber tiles are weather resistant, decorative, optimum fall safety, slip resistant, good sound absorbing properties inside and outside. Easy to install - does not take much time and effort.

Composition:

Rubber granules combined together with polyurethane binder and colouring pigment.

Tested according to:

EN 1176-1:2008; EN 1177:2008 standards

Certificate No. :

MK 2792633 01; C-351513; C-357803-1; C-357803-2

Report No. :

28208942 001



Performance characteristic

Dimensions 500x500mm; 1000 x1000 mm;

Thickness: 40 mm; 90 mm; 30mm; 60mm; 50mm (characteristics could be different for other dimension and thickness of rubber tiles.)

Dimensional Stability	Better than ± 1 mm
Flexibility	52 MN/m ²
Residual Indentation	None
Heat Conductivity	0.14 W/MK
Shore A Hardness	48
Heat Resistance	To 300 °C
Freeze resistance	below -30 °C
Colour Fastness	Good UV resistance
Painting	PU paint for UV protection
Hygiene	Non-toxic
Sound Absorption	86.5 dB/100 Hz
Foot Comfort	Excellent
Shear Strength	5.4 N/mm ²
Critical Fall Height	In comply with BS 7188 standard
Weather Resistance	Unaffected by frost and snow
Cigarette Burns	Resistant

