

Laboratory Service PHYSICAL TEST REPORT



R-Tech
Rue de Mons 3 – B-4000 Liège – Belgium
Tel.: +32 4 224 71 40 – Fax: +32 4 224 25 90
Member of Schröder Group

Subject: I.S. SKIDO (hand mounted by HUS)

Sample n°: P-E13088

From: HUS

Test purpose: Mechanical impact resistance test following IEC/EN 62262 Standard

Remarks:

Test request n°: P-D13182

Folder n°: P-F13034


TEST CONDITIONS:

Operator: BOMBIL Patrick

I.S. Skido with PC protector
Info material not received

At pendulum hammer

5+3 impact points distributed on protector surface
One impact on each point



Test

IK05 : Impact energy: 0,7 joules
Hammer weight: 0,2 kg
Height of fall: 35 cm

IK06 : Impact energy: 1 joule
Hammer weight: 0,5 kg
Height of fall: 22 cm

IK07 : Impact energy: 2 joule
Hammer weight: 0,5 kg
Height of fall: 40 cm

IK08 : Impact energy: 5 joules
Hammer weight: 1,7 kg
Height of fall: 29,4 cm

Result

OK, nothing to indicate

OK, nothing to indicate

OK, nothing to indicate

OK for the protector, but a deformation of the alu sheet clamp allows the release of the fitting. See pictures here after.

CONCLUSIONS:

SKIDO satisfies the IK07 test in accordance with IEC/EN 62262 Standard.

Duplicate to: MM C. Horvath, C. Marville, Y. Borlez

LAB 19/04/2013

J.P. Harchies

P-13E182

I.S. SKIDO (hand made by HUS)

