

Portable Color Doppler System

EBit 50

Datasheet

V2.0



General information

Dimensions and Weight

- Dimensions of main unit (approx.): 358mm (Length) ×125mm (Width) ×399mm (Height)
- Net weight of main unit (approx.): 7.8kg (no probe included)

Electrical Power

- Power supply voltage: Auto adaptable for AC100-240V
- Power supply frequency: 50-60 Hz
- Power consumption: 150 VA

User interface

Operation Panel

- Control panel
- Alphanumeric keyboard
- 8 STC Slides
- Interactive backlit keys
- High resolution color LCD
 - Diagonal dimension: 15 inch
 - Resolution: 1024X768
 - Brightness adjustment
- Integrated speaker
 - Volume adjustable

System overview

Applications

- Abdominal
- Cardiac
- Small organ
- Peripheral Vascular
- Transvaginal
- Transrectal
- Musculo-skeletal
- Pediatric
- Fetal
- OB
- GYN
- Urology

Scanning Method

- Electronic convex
- Electronic linear
- Electronic micro convex
- Electronic phased array

Transducer Types

- Convex transducer: C3-E
- Linear transducer: L7-E, L12-E, L7W-E,
- Transvaginal transducer: V6-E, V7-E
- Phased array transducer: P3-E
- TransRectal transducer: L7R-E
- Micro-convex transducer: MC3-E, MC6-E, MC5-E

Image Modes

- B Mode
- B/M Mode
- M Mode
- 2B Mode
- 4B Mode
- 2D Steer (option)
- CFM Mode
- CPA Mode
- DPD Mode
- PW Mode
- B/BC Mode (option)
- Triplex Mode
- CW Mode (option)
- TDI (option)
- Color M Mode (option)
- Trapezoidal Mode
- ECG (option)
- Super Needle (option)
- Elastography Mode (option)
- Free Steering M mode (option)
- Quadplex Mode (option)
- Curved Panoramic (option)
- Stress Echo (option)

Display Mode

- Quad/dual display (Only for B)
- Duplex mode: B+CFM, B+CPA, B+DPD, B/M
- Triplex mode: B+CFM+PW, B+CPA+PW, B+DPD+PW,

Display Annotation

- Logo
- Hospital name
- Exam Date/Time

- Mechanical index
- Tissue thermal index
- Patient Name and Patient ID
- System status (real-time or frozen)
- Gray/Color bar
- Cine guide
- Measurement summary window
- Measurement results window
- Probe type
- Frequency
- Menu indication
- Trackball functions indication
- Imaging parameters

Standard Configuration

- High resolution 15 Inch LCD display
- 2 active probe ports
- Pulse Wave Doppler
- Color Doppler Flow Imaging
- Power Doppler Flow Imaging
- Directional Power Doppler Flow Imaging
- ≥500G integrated hard disk
- USB ports : 4
- Ethernet port :1
- S-video out port :1
- VGA port :1
- DVI port :1
- ECG port :1
- Foot switch :1
- Remote :1
- General measurement package
- Clinical measurement packages
- Multi-language screen display
- Review: images review system

- Archive: patient information management system
- Reporting system
- AIO (Automatic Image Optimization)
- Intelligent Zoom
- Speckle Reduction Algorithm (SRA)
- Q-Image software package

Software Options

- DICOM (storage, print, worklist)
- Super needle
- CW
- TDI
- Color M
- ECG
- B/BC mode
- 2D steer
- Quadplex Mode
- Curved Panoramic
- Stress Echo

Hardware Option

- Convex transducer: C3-E
- Linear transducer: L7-E, L12-E, L7W-E
- Transvaginal transducer: V6-E, V7-E
- Phased array transducer: P3-E TransRectal transducer: L7R-E
- Micro-convex transducer: MC3-E, MC6-E, MC5-E
- Footswitch
- Carrying case
- Trolley
- ECG cable
- Bag

Peripherals

- Video printer: SONY UP897MD, SONY UP-D711MD, SONY UP-X898MD
- PC printer :
 - HP Laser Jet 1020
 - HP Laser Jet 1102/1102W
 - HP Laser Jet P2055d
 - HP Laser Jet M251n/M252n/252dw
 - HP OfficeJet Pro 6230

Imaging processing and presentation

B Mode

- Gain
- STC
- Depth
- Freq.
- FHI
- AIO
- Invert
- X-CONTRAST
- UD Invert
- Zoom
- Full screen
- Focus number
- Compound
- SRA
- Density
- Dynamic
- Focus position
- Q-Image
- Persistence
- B Rejection
- Scan width
- Gamma

- Smooth
- Edge enhance
- Acoustic power
- L/R Flip
- Chroma
- 2D Map
- Zoom coef
- Trapezoidal imaging (only for linear transducer)
- 2D steer
- ECG
- Biospy
- Super Needle
- Needle Angle
- Center Line
- Elastography Mode (option)
- Curved Panoramic (option)
- Stress Echo (option)

M Mode

- Gain
- STC
- Depth
- Invert
- FHI
- AIO
- Full Screen
- Speed
- M Chroma
- Layout
- M 2D map
- Free M

Color Mode

- Gain

- Depth
- FHI
- AIO
- Full Screen
- Freq.
- Wall filter
- Q-flow
- Color Invert
- Q-beam
- Steer (only for linear transducer)
- Color Map
- PRF
- Persistence
- Baseline
- Color mode: Velocity, Variance
- Wall Thre.
- Blood Efection
- Density
- B/BC

CPA/DPD Mode

- Gain
- Depth
- FHI
- AIO
- Color Invert
- Full Screen
- Freq.
- Wall filter
- Q-flow
- Q-beam
- Steer (only for linear transducer)
- PRF
- Color Map

- Persistence
- CF Mode: Velocity, Variance
- Wall Thre.
- Blood Efection
- Density
- B/BC

PW Mode

- Gain
- FHI
- AIO
- Full Screen
- Freq.
- Wall Filter
- Triplex mode
- Quadplex Mode
- Steer
- Invert
- PW chroma
- Audio
- PRF
- Speed
- Baseline
- Angle
- D 2D map
- Spectrum Enhance
- Dynamic Range

TDI mode

- Gain
- Depth
- FHI
- AIO
- Full Screen

- Freq.
- Steer
- Wall filter
- Color Invert
- Density
- Color Map
- PRF
- Q-beam
- Q-flow
- Persistence
- Baseline
- Wall Thre.
- Blood Effection
- B/BC

CW mode

- Gain
- Angle
- Invert
- FHI
- AIO
- Full Screen
- Steer
- Freq.
- Wall Filter
- CWD chroma
- Audio
- Triplex Mode
- PRF
- Speed
- Base line
- CW 2D map
- Spectrum enhance
- Dynamic Range

Cineloop

- Support 2D, M, PW, CFM, CPA, DPD
- Simultaneous and independent review in Triplex mode
- Cineloop auto/manual
- Variable cine playback speed
- User-define start and end frame of cine storage
- User-define start and end frame of cine review
- storage in hard disk and display in real-time modes
- Slide show: slide show function

Storage

- ≥500GB integrated hard drive
- USB driver
- Still images storage format: BMP
- Still images export format: BMP, JPG
- Cine loops storage format: CINE
- Cine loops export format: AVI

Review

- Image review Layout: 1×1, 2×2, 4×4
- Image management

Archive

- Patient info
- Review report
- Backup exam
- Restore exam
- Send exam
- Delete exam
- Patient view
- Study view
- Expand all
- Collapse all

- Select all
- New Exam
- Continue Exam
- Edit Exam
- Review

Measurement & calculation

General Measurement Package

- Software packages for various specific clinical use
- Comprehensive analysis methods
- Clinical analysis reports

General measurement package

- General B mode measurement
 - Distance
 - Perimeter/area
 - Volume (1Distance)
 - Volume (1Distance)
 - Volume (1Ellipse)
 - Volume (2Distance)
 - Volume (3Distance)
 - Volume (1Distance1Ellipse)
 - Ratio (distance/ area)
 - Angle
 - Histogram (rectangular/ellipse/trace)
 - profile
- PW mode measurement
 - Distance
 - Peak
 - Velocity
 - Trace
 - StD%
 - StA%
 - ICA/CCA

- Flow Volume
- Heart__Rate
- General M mode measurement
- Velocity
- Distance
- Time
- HR

Clinical Analysis Packages

- Abdomen
- Obstetric
- Gynecology
- Cardiology
- Vascular
- Urology
- Small parts
- ORTH
- Pediatrics

System setup

By using system Setup, users could

- Customize hospital information
- Customize language
- Customize screen type
- Customize screen controller
- Customize measurement package
- Customize comment/bodymarks
- Customize exam mode
- Customize hotkey functions
- DICOM setting
- Net setting
- System information
 - function setting
 - Upgrade
 - hardware function
 - Video&VGA setting

User Define Functions

By user-define function, users could customize user-define preset, including

- Applications name, Presets name, User defined name
- Applications exam type
- Imaging parameters

Multi-language Display Interface

- English
- Chinese
- Other languages

Note: other languages for detailed, please contact CHISON.

Inputs & outputs

System power in: 1

- Ethernet: 1
- S-video: 1
- Footswitch port: 1
- USB port: 4
- Video out: 1
- Remote control: 1
- VGA: 1
- DVI: 1
- ECG port: 1

Operating conditions

- Ambient temperature: 10°C to 40°C
- Relative humidity: 30% to 75%
- Atmospheric pressure: 700 hPa to 1060 hPa

Storage and transport conditions

- Ambient temperature: -5°C to 40°C
- Relative humidity: ≤ 80%
- Atmospheric pressure: 700 hPa to 1060 hPa

Not all features or specifications described in this document may be available in all probes and/or modes.

CHISON Medical Technologies Co., Ltd. reserves the right to make changes in specifications and features shown here in, or discontinues the product at any time without notice or obligation. For the most current information, Contact CHISON Representative.