

LLC «JV YUKOIL»

48A Ivana Pulyuya str., Bila Tserkva, Kyiv region, Ukraine, 09100

Hot-line: +38 (0) 800 60 5555

Tel: +38 (061) 222 80 25 (laboratory)

State register No. 31852954



Testing laboratory of JV "YUKOIL" LLC is certified for carrying out tests of quality parameters of petroleum products, technical fluids and lubricants. Certificate of technical competence recognition № AB 83-21 dated 16.11.2021 is issued by the State-owned enterprise "ZAPORIZHYASTANDARTMETROLOGIA", valid till 16.11.2024

Quality Certificate No 17007.01.01.1

Transmission oil YUKO TAp-15V (GL-3, SAE 90)

Manufacturer JV YUKOIL LLC

Packed by JV YUKOIL LLC

Viscosity grade: **SAE 90**

Quality Index: **API GL-3**

Production date: April 2023

Package: canister 20L PE

Batch No: 17007.24.04.23.01.



№	Test	Norm	Result	Test method
1	Density at 20°C, kg/m ³ , not more than	960	888	ASTM D1298
2	Kinematic viscosity at 100°C, mm ² /s	14,0-16,0	14,0	ASTM D445
4	Open cup flash point, °C, not less than	185	215	ASTM D92
5	Pour point, °C, not high than	minus 15	minus 17	ASTM D97
8	Mass fraction of mechanical impurities, %, not more than	0,03	0,020	GOST 6370
9	Water content, %, not more than	traces	traces	ASTM D95
11	Tribological characteristics on 4 balls machine at (20±5)°C			ASTM D2783
	- welding load, N, not less than	2764	2 764	ASTM D2783
	- scuff index, N, not less than	470	470	ASTM D2783
12	Corrosive effect on metals	pass	pass	GOST 2917 or ASTM D130

Result: the product quality meets the standard of TU U 19.2-31852954-002:2021

seal

Head of Quality Assurance Department

WEB: www.yuko.eu

Hot-line: +38 (0) 800 60 5555

E-mail: support@yukoil.com

Tel.: +38 (061) 222 80 32

Member of:





YUKO TAP-15V (GL-3, SAE-90)

MINERAL TRANSMISSION OIL FOR TRUCK AND AGRICULTURAL MACHINERY.

SPECIFICATIONS:

SAE 90

API GL-3

DESCRIPTION:

It is used in truck transmissions, agricultural machinery, as well as for lubrication of spur, spiral-bevel and worm gears, where contact loads reach 2000 MPa.

It is produced from mineral base oils with additives.

BENEFITS:

- Provides effective lubrication of transmission elements, including while working with increased loads;
- Increases the service life of gearbox parts;
- Contains detergent, antioxidant and anti-wear additives.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14.8
Flash point in an open crucible, °C	210
Pour point, °C	-15

Packing	Vendor code	Barcode
Barrel metal 20l	001796	482007024020
Canister plastic 20l	007746	482007024019
Canister plastic 5l	004279	482007024100