

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1734705330136 din 20.12.2024

Obiectul achiziției: Privind achiziționarea: Echipament de iluminat și proiectoare

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
1.1. Compact Lighting Console	MagicQ MQ70	UK	Chamsys	<p>Control your stage, studio, or live entertainment lighting system with the Compact Console. This compact lighting control console can control up to 24 DMX universes and features 12 faders, 8 attribute encoders, and 2 master faders, with support up to 12,288 fixtures. It features a built-in 10.1" multitouch display and Wi-Fi to control the console remotely. Compatible with the existing light console MagicQ</p> <p><i>General</i> Software Specifications - Max Number of Universes: 24 Max Number of DMX Channels: 12,288 Max Number of Fixtures Supported: 12,288 Max Number of Cues: 5000 Max Number of Cue Stacks: 2000 Max Number of Groups: 5000 Max Number of Palettes: 4096 Number of Media Server Layers Supported: 50 (Each Different Content) Numbers of Shows: Virtually Unlimited USB I/O - 5 x USB-A Female Input/Output Video I/O - 1x HDMI Output Audio I/O - 1x 1/8" / 3.5 mm Input 1x 1/8" / 3.5 mm Output</p>	<p>Control your stage, studio, or live entertainment lighting system with the Compact Console. This compact lighting control console can control up to 24 DMX universes and features 12 faders, 8 attribute encoders, and 2 master faders, with support up to 12,288 fixtures. It features a built-in 10.1" multitouch display and Wi-Fi to control the console remotely. Compatible with the existing light console MagicQ</p> <p><i>General</i> Software Specifications - Max Number of Universes: 24 Max Number of DMX Channels: 12,288 Max Number of Fixtures Supported: 12,288 Max Number of Cues: 5000 Max Number of Cue Stacks: 2000 Max Number of Groups: 5000 Max Number of Palettes: 4096 Number of Media Server Layers Supported: 50 (Each Different Content) Numbers of Shows: Virtually Unlimited USB I/O - 5 x USB-A Female Input/Output Video I/O - 1x HDMI Output Audio I/O - 1x 1/8" / 3.5 mm Input</p>	

				<p>Other I/O - 4 x 5-Pin DMX 3 x RJ45 Ethernet 1 x MIDI Input 1 x MIDI Output 1 x LTC Input 1 x Remote Input</p> <p>Buttons and Controls - Playbacks: 10; Grand Master Fader: 1 Crossfade Master Fader: 1; Attribute Encoders: 8; Wireless - Wi-Fi</p> <p>Power Source - Plug-In Power (Included) AC Input Power - 110 to 240 VAC, 50 / 60 Hz Power Input - 1 x Neutrik powerCON TRUE1 UPS - 12 V Lead-Acid Battery</p>	<p>1x 1/8" / 3.5 mm Output Other I/O - 4 x 5-Pin DMX 3 x RJ45 Ethernet 1 x MIDI Input 1 x MIDI Output 1 x LTC Input 1 x Remote Input</p> <p>Buttons and Controls - Playbacks: 10; Grand Master Fader: 1 Crossfade Master Fader: 1; Attribute Encoders: 8; Wireless - Wi-Fi</p> <p>Power Source - Plug-In Power (Included) AC Input Power - 110 to 240 VAC, 50 / 60 Hz Power Input - 1 x Neutrik powerCON TRUE1 UPS - 12 V Lead-Acid Battery</p>	
1.2. LED Light	LED STP-14 Sunbar	China	Eurolite	<p>3-in-1 LED-Sunbar With warm white beam effects, stroboscope and ambient light 14 Warm white 3W LEDs with 6.5° beam angle for narrow beams 120 Bright RGB LEDs for mood lighting and colour animations 180 Cold white LEDs for fast, dynamic strobe effects Auto, Music, Master/Slave and DMX modes (2, 6, 34 or 37 DMX channels selectable) Music control via built-in microphone with adjustable microphone sensitivity Power-twist mains connection with loop-through output for power supply of up to 8 devices Fanless convection cooling via cooling fins Power supply: 100-240 V AC, 50/60 Hz Total connected load: 95 W Dimensions (L x H x D): 100 x 8.5 x 9 cm Weight: 3.92 kg</p>	<p>3-in-1 LED-Sunbar With warm white beam effects, stroboscope and ambient light 14 Warm white 3W LEDs with 6.5° beam angle for narrow beams 120 Bright RGB LEDs for mood lighting and colour animations 180 Cold white LEDs for fast, dynamic strobe effects Auto, Music, Master/Slave and DMX modes (2, 6, 34 or 37 DMX channels selectable) Music control via built-in microphone with adjustable microphone sensitivity Power-twist mains connection with loop-through output for power supply of up to 8 devices Fanless convection cooling via cooling fins Power supply: 100-240 V AC, 50/60 Hz Total connected load: 95 W Dimensions (L x H x D): 100 x 8.5 x 9 cm Weight: 3.92 kg</p>	
1.3. LED Strobe	LED Super Strobe ABL	China	Eurolite	<p>3 Effects in one unit: strobe, blinder and ambient light 216 cool white LEDs (SMD 5730) for fast, dynamic strobe and blinder effects</p>	<p>3 Effects in one unit: strobe, blinder and ambient light 216 cool white LEDs (SMD 5730) for fast, dynamic strobe and blinder effects</p>	

				<p>144 additional RGB LEDs (SMD 5050) provide pleasant mood lighting RGB LEDs and cool white LEDs can be controlled separately RGB LEDs controllable in 1 or 48 segments, depending on choice of DMX mode Auto, music, master/slave and DMX modes 17 Integrated chaser programmes in auto and music mode Flash rate: 20 Hz Stepless RGB colour mixing Dimmer Addressing and settings via control unit with 4-digit LED display Music control via built-in microphone with adjustable microphone sensitivity 7, 13, 22 or 148 DMX channels selectable Flat metal housing with integrated wall bracket Adjustable mounting bracket Power Twist connections for easy series connection of up to 8 units Projection: flicker-free Power supply: 100-240 V AC, 50/60 Hz Power consumption: 130 W DMX input: 3-pin XLR male DMX output: 3-pin XLR female Dimensions (W x H x D): 45.5 x 25.5 x 8 cm Weight: 3.94 kg</p>	<p>144 additional RGB LEDs (SMD 5050) provide pleasant mood lighting RGB LEDs and cool white LEDs can be controlled separately RGB LEDs controllable in 1 or 48 segments, depending on choice of DMX mode Auto, music, master/slave and DMX modes 17 Integrated chaser programmes in auto and music mode Flash rate: 20 Hz Stepless RGB colour mixing Dimmer Addressing and settings via control unit with 4-digit LED display Music control via built-in microphone with adjustable microphone sensitivity 7, 13, 22 or 148 DMX channels selectable Flat metal housing with integrated wall bracket Adjustable mounting bracket Power Twist connections for easy series connection of up to 8 units Projection: flicker-free Power supply: 100-240 V AC, 50/60 Hz Power consumption: 130 W DMX input: 3-pin XLR male DMX output: 3-pin XLR female Dimensions (W x H x D): 45.5 x 25.5 x 8 cm Weight: 3.94 kg</p>	
1.4. Moving-Head Beam	TMH XB-280 Moving Head Beam	China	Eurolite	<p>Bright, narrow beam with OSD 10 280W discharge lamp, colour wheel, gobos and prisms Beam angle: 2° Positioning: 540° PAN and 270° TILT (16-bit resolution) Rotating 8- and 24-facet prism, combinable for multi-facet effects, in both directions and at different speeds Frost filter Multi-colour filter Strobe effect with variable speed and random generator</p>	<p>Bright, narrow beam with OSD 10 280W discharge lamp, colour wheel, gobos and prisms Beam angle: 2° Positioning: 540° PAN and 270° TILT (16-bit resolution) Rotating 8- and 24-facet prism, combinable for multi-facet effects, in both directions and at different speeds Frost filter Multi-colour filter Strobe effect with variable speed and random generator</p>	

				<p>Dimmer Motorised focus kCompatible with QuickDMX Phantom-powered USB socket for optional QuickDMX, CRMX and WDMX receivers (available as accessories, not included) Control board with graphic LCD for setting DMX start address, PAN/TILT reverse, reset, lamp switching, hour meter Power Twist mains connection Colour wheel 14 dichroic colours and open Rainbow effect with variable speed in both directions Gobo wheel with static 13 gobos and open, plus shake effect 19 CH DMX mode operable Unit is cooled by fan Controllable via DMX, stand-alone, master/slave function Music control via microphone Noise classification: Class 4 (loud noises) Power supply: 100-240 V AC, 50/60 Hz Power consumption: 385 W DMX connection: 3-pin XLR In / Out Dimensions WxDxH: 30 x 21 x 51 cm Weight: 14.80 kg</p>	<p>Dimmer Motorised focus kCompatible with QuickDMX Phantom-powered USB socket for optional QuickDMX, CRMX and WDMX receivers (available as accessories, not included) Control board with graphic LCD for setting DMX start address, PAN/TILT reverse, reset, lamp switching, hour meter Power Twist mains connection Colour wheel 14 dichroic colours and open Rainbow effect with variable speed in both directions Gobo wheel with static 13 gobos and open, plus shake effect 19 CH DMX mode operable Unit is cooled by fan Controllable via DMX, stand-alone, master/slave function Music control via microphone Noise classification: Class 4 (loud noises) Power supply: 100-240 V AC, 50/60 Hz Power consumption: 385 W DMX connection: 3-pin XLR In / Out Dimensions WxDxH: 30 x 21 x 51 cm Weight: 14.80 kg</p>	
1.5. DMX Cable	OT206	Germania	Klotz	Cable DMX	Cable DMX	
1.6. Clamp	812	China	Global Truss	Compatible with tubing Ø 48 - 51 mm Machine screw M10 with butterfly nut, split lock washer and washer Shutter: M8 with butterfly nut	Compatible with tubing Ø 48 - 51 mm Machine screw M10 with butterfly nut, split lock washer and washer Shutter: M8 with butterfly nut	
1.7. Connector	NC3MXX	Liechtenstein	Neutrik	3-pol XLR Male Connector	3-pol XLR Male Connector	
1.8. Connector	NC3FXX	Liechtenstein	Neutrik	3-pol XLR Female Connector	3-pol XLR Female Connector	
1.9. Connector	NC5MXX	Liechtenstein	Neutrik	5-pol XLR Male Connector	5-pol XLR Male Connector	

Semnat: Semnat electronic, Numele, Prenumele: Carabut Vladislav, În calitate de: Director

Ofertantul: SC "Muzic-Prod" S.R.L.

Adresa: Moldova, Chisinau, Durlesti, str-la II Vovinteni 15