Eaton 5SC1500IR

Catalog Number: 5SC1500IR

Eaton 5SC UPS, 1500 VA, 1050 W, Input: C14, Outputs: (8) C13, Rack, 2U

General specifications

Product Name

Eaton 5SC UPS

UPC

18.

743172088338

Product Height

86.2 mm

Product Weight

17.78 kg

Certifications

UL 1778

IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC

cTUVus

Catalog Number

5SC1500IR

Product Length/Depth

440 mm

Product Width

405 mm

Compliances

CE Marked

TUV



FAT-N



Battery

Battery type

Lead-acid maintenance-free (replaceable)

Runtime graph

\$row.attributeValue.cdata

Battery replacement

User replaceable

Battery quantity

3

Battery management

ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection

Battery rating

12 V / 9 Ah

Extended battery capability

No

Electrical output

Receptacle

(8) C13

Voltage

230V

Wattage

1050 W

Output power factor

0.7

Output voltage range

230 V (+6%/-10%)

Output waveform

Sine wave

Output nominal voltage

230V default (220/230/240V)

Feed type

1

Topology

Line-interactive

VA rating

1500 VA

Electrical input

Input connection

C14

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50-60 Hz

Input voltage range

184-276 V

Input frequency range

45-55 Hz (50 Hz system), 55-65 Hz (60 Hz system)

Communications

Includes network card

No

Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for

remote On/Off and Remote

Power Off

Dry contacts (2 outputs,

optocoupler, RJ)

Ethernet interface

No

User interface

LCD Display

Potential free switch contact

Yes

Expansion slots

One slot for optional communication card

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power

Protector

Type of interface

Other

Additional specifications

Construction type

482.6 mm (19 inch) device

Enclosure

Black

Package contents

Rack-mounting kit

Cable locking system

USB cable

Serial cable

(2) IEC-IEC cables

Quickstart guide

Safety instructions

Phase (output)

1

Auto shutdown function

Yes

Color

Black

Efficiency

97

Rack mounting kit

Yes

Phase (input)

1

Environmental

Altitude

3000 m

Noise level

<40 dB at 1 meter

Temperature range

0-90% non-condensing

Relative humidity

0-90% non-condensing

Resources

Brochures

Eaton 5SC UPS - 500/3000VA - Datasheet

Eaton UPS and battery services - EN

Eaton UPS Services Quick Guide - EN

Compliance information

EU DoC Eaton 5SC

Manuals and user guides

Eaton 5SC Rack-RT UPS - 1000i Rack2U/1500i Rack2U/2200i

RT2U/3000i RT2U - Installation and user manual



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia