

Horizontal Cylindrical Pressure Autoclave



Features:

- \* Drying function.
  - \* Automatic sterilization process.
  - \* Safety valve for over pressure protection.
  - \* Over-temperature, over-pressure protection device.
- \* Interlock function.
  - \* 304 stainless steel material chamber.
  - \* Automatically in case of low water level.
  - \* Water level sensor. The power will be cut-off .
  - \* Double door optional.

Technical Parameters:

| Model                    | BKQ-H150                                                                                         | BKQ-H200      | BKQ-H300                                                                                   | BKQ-H400       | BKQ-H500       |
|--------------------------|--------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------------------------------------------------|----------------|----------------|
| Capacity                 | 150L                                                                                             | 200L          | 280L                                                                                       | 400L           | 500L           |
| Chamber Size(mm)         | φ440*1000                                                                                        | φ515*1000     | φ600*1000                                                                                  | φ700*1100      | φ700*1300      |
| Working Pressure         | 0.22MPa                                                                                          |               |                                                                                            |                |                |
| Working Temp.            | 134℃                                                                                             |               |                                                                                            |                |                |
| Temperature Range        | 105~134℃                                                                                         |               |                                                                                            |                |                |
| Sterilization Time       | 0~60 min                                                                                         |               |                                                                                            |                |                |
| Drying Time              | 0~60 min                                                                                         |               |                                                                                            |                |                |
| Temp. Display Accuracy   | ≤±2℃                                                                                             |               |                                                                                            |                |                |
| Consumption              | 9KW                                                                                              |               | 12KW                                                                                       | 18KW           |                |
| Power Supply             | Standard: 380V, 50Hz(3-phase);<br>Optional: 220V, 50/60Hz(1-phase).<br>Wiring Method: Air switch |               | Standard: 380V, 50Hz(3-phase);<br>Optional: 220V, 60Hz(3-phase). Wiring Method: Air switch |                |                |
| External Size (W*D*H) mm | 1400*600*1300                                                                                    | 1400*670*1650 | 1400*770*1780                                                                              | 1430*880*1830  | 1800*900*1820  |
| Package Size (W*D*H) mm  | 1550*750*1850                                                                                    | 1560*820*1850 | 1680*920*2100                                                                              | 1600*1050*2100 | 1850*1050*2100 |
| Gross Weight(kg)         | 320                                                                                              | 350           | 465                                                                                        | 530            | 580            |

Hot Air Sterilizer



Application:

Hot air sterilizer is used to sterilize small surgical instrument, glass, petri dishes etc.  
This device is suitable for medical and veterinary clinics, hospitals, pharmacies, health care centers, and laboratories.

Features:

- \* Inner door without glass, outer door with observation window, back inlet and outlet.
- \* Intelligent microcomputer P.I.D temperature controller, accurate temperature control.
- \* Stainless steel tube circular heater.
- \* The inner box adopts circular arc structure design, and the movable partition can be pulled.

Technical Parameters:

| Model                   | HAS-T50I                                   | HAS-T70I    | HAS-T105I   | HAS-T200I    |
|-------------------------|--------------------------------------------|-------------|-------------|--------------|
| Capacity                | 48L                                        | 80L         | 105L        | 180L         |
| Temp. Range             | RT+10~250℃                                 |             |             |              |
| Temp. Precision         | 0.1℃                                       |             |             |              |
| Temp. Fluctuation       | ±1℃                                        |             |             |              |
| Ambient Temp.           | 5~40℃                                      |             |             |              |
| Timing Range            | 0~9999min                                  |             |             |              |
| Shelves No.             | 2 pcs                                      |             |             |              |
| Consumption             | 1000W                                      | 1500W       | 1600W       | 2450W        |
| Power Supply            | AC220V 50Hz(Standard); 110V 60Hz(Optional) |             |             |              |
| Internal Size(W*D*H) mm | 419*332*348                                | 450*397*450 | 550*348*550 | 602*498*602  |
| External Size(W*D*H) mm | 728*595*532                                | 750*680*635 | 850*620*735 | 900*775*785  |
| Package Size(W*D*H) mm  | 780*640*655                                | 855*735*755 | 925*665*860 | 1000*835*935 |
| Gross Weight(kg)        | 60                                         | 80          | 115         | 145          |