

SPECIFICAȚII TEHNICE 4.1

Nr. Procedurii de achiziție: 21005572						Data: 28.03.19		Alternativa Nr.:	
Denumirea procedurii de achiziție: "Achiziționarea articolelor angiografice conform IMSP Institutul de Cardiologie (repetat) pentru anul 2019"						Lot.: 8,9		Pagina: 1 din 1	
Codul CPV	Nr. d/o	Denumirea bunurilor	Modelul articolului	Tara de origine	Producătorul	Specificatia tehnica solicitata	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință	
1		2	3	4	5	6	7	8	
33100000-1	8	STENT GRAFT CORONARIAN	CELOSIA	SUA	InSitu Tech	Stentul este din otel inoxidabil. Graftul este din PTFE, premontat. Vizibilitate redicta ce permit o fixare exacta datorita celor 2 markeri.Shift flexibil care permite patrunderea cu usurinta n vase torturase, forta radiala mare. Diametru: 3-5 mm, lungime 9-26 mm.	Vezi catalogul/prospectul atasat, Celosia™ Covered Stent Stent Design: Direct-Stent® U.S. Patented Hybrid Cell Design. Stent Material: Cobalt Chromium, Stent Covering Polymer: Eptfe, Wall Thickness: 0.076mm / 0.003", Variable Strut Width: 0.046mm - 0.127mm / 0.0018 - 0.005", Delivery System: Rapid Exchange (RX), Balloon Material: Semi-Compliant, Nylon Blend, Optimal Deployment Pressure: 6 ATM, Rated Burst Pressure, 16 ATM, Shaft Size (Proximal -Distal): 1.9 - 2.7F, Premounted Profiles: 0.94 - 1.4mm, Tip Entry Profile: 0.017", Recommended Guidewire: 0.014", Minimum Guiding Catheter: 5 - 6F, Working Length: 142cm, Stent Diameter: 2.0 - 7.0mm. Stent Length: 5 - 40mm	FDA/ISO	
33100000-1	9	STENT GRAFT pentru periferie	SILENE	SUA	InSitu Tech	Stentul este din otel inoxidabil. Graftul este din PTFE, premontat. Vizibilitate redicta ce permit o fixare exacta datorita celor 2 markeri. Shift flexibil care permite patrunderea cu surinta in vase torturase, forta radiala mare. Diametru: până la 9 mm, lungime până la 30 mm.	Vezi catalogul/prospectul atasat, Silene™ Covered Stent Stent Design: Direct-Stent® U.S. Patented Hybrid Cell Design. Stent Material: Cobalt Chromium, Stent Covering Polymer: ePTFE, Wall Thickness: 0.076mm / 0.003", Variable Strut Width: 0.046mm - 0.127mm / 0.0018 - 0.005", Delivery System: Over The Wire (OTW), Balloon Material: Low-Compliant, Nylon Blend, Optimal Deployment Pressure: 8 ATM, Rated Burst Pressure: 10 - 12 ATM, Shaft Size (Proximal - Distal): 5 - 7F, Tip Entry Profile: 0.039", Recommended Guidewire: 0.035", Minimum Sheath Introducer: 6 - 8F, Working Length: 130cm, Stent Diameter: 6.0 - 10.0mm, Stent Length: 15 -	FDA/ISO	



Semnăt: 

Numele, prenumele: Captari Alexandru În calitate de: Administrator

Ofertantul: "CAVATEH M" SRL

Adresa: MD-2028 CHIȘINĂU, str. Academiei 3, of. 110B