

Magnetic Stirrer

○Magnetic mixing equipment with heating.

Characteristics:

- Heating power and stirring speed is stepless adjustable.
- With adjustable thermometer rack, stainless steel rods and the stir bar.
- SH-(C) series: Ceramic Plate
- SH-3D: Display
- SH-3D(C): Ceramic plate&Display controller



Main Technical Parameters:

Patent No. : ZL 2018 3 0095053.5

Model		SH-2A	SH-2B	SH-2	SH-3A	SH-3B	SH-3D	SH-3
		SH-2A (C)	SH-2B (C)	SH-2 (C)	SH-3A (C)	SH-3B (C)	SH-3D (C)	SH-3 (C)
Function	Max. Volume (ml)	—	2000	2000	—	5000	5000	5000
	Speed (r.p.m)	—	100~2000		—	100~2000		
	Working Time	Continuous						
	Minimum Revolution (r.p.m)	—	100	100	—	100	100	100
	Max.Temp. (°C)	380	—	380	380	—	380	380
Structure	Exterior	Cast aluminium, Surface spraying / Ceramic Coated						
	Plate Size(mm)	120 × 120			170 × 170			
	Driving Mode	—	Motor		—	Motor		
	Motor Power (W)	—	10		—	20		
	Heating Power(kW)	0.18	—	0.18	0.5	—	0.5	0.5
	Stir Bar	—	PTFE		—	PTFE		
Controller	Continuous Operation	Yes						
	Setting Mode	Scale						
	Speed Display Mode	—	Scale		—	Scale		
	Timer	No						
	Operation Function	No						
	Temp. Sensor	No						
Specification	Exterior Size (W*L*H)(mm)	200 × 120 × 90			265 × 185 × 190			
	Packing Size (W*L*H)(mm)	250 × 180 × 120			280 × 210 × 220			
	Plate Size (mm)	120 × 120			170 × 170			
	Plate Load	3KG			10KG			
	Power Supply (50/60Hz)	110V or 220V						
	Current Rating							
	NW/GW (kg)	1.9/3	1.9/3	1.9/3	2.2/3.4	2.2/3.4	2.2/3.4	2.2/3.4