

VIVI 400 HIGH POWER LED

LARGE SIZE

Modern luminaries made in shockproof resin material, UV rays stabilized, rust and corrosion-free. Suitable for post top, wall and hanging installation. Provided with reflective ceiling designed to host the lighting source and equipped with TÜV approved, long-life and efficient **E27 high power LED lamp included**. Insulation class II, Protection rating IP65.

Diffusore moderno realizzato in resina antiurto, stabilizzato ai raggi UV, inattaccabile da ruggine e corrosione. Idoneo per il montaggio a palo, a sospensione o a parete. Provvisto di soffitto riflettente progettato per accogliere la sorgente luminosa e fornito completo di lampada a LED E27 ad ALTA POTENZA, approvata TÜV di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP65.

V50.000.H1L

E27 HIGH POWER LED

INDOOR & OUTDOOR USE

+80°C
-30°

90%
HUMIDITY

VOLTAGE SURGE
RESISTANT



DRIVER
SILICONE
PROTECTION



VIVI 400 HIGH POWER LED - COMPONENTS

IP65



ROOF made of shockproof resin material, UV-rays stabilized, rust and corrosion-free.

TETTO realizzato in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.

High temperature resistant reflective **CEILING** made of shockproof resin material. Provided with E27 lampholder and equipped with **HIGH POWER LED lamp**. Designed to host and protect the lighting source, granting its safe and quick installation.

SOFFITTO riflettente realizzato in resina antiurto ad alta resistenza al calore. Fornito completo di portalamпада E27 e provvisto di **lampada a LED ad ALTA POTENZA**. Progettato per accogliere e proteggere la sorgente luminosa e per garantirne una veloce e sicura installazione.

DIFFUSER made of UV-rays stabilized polymethylmethacrylate (PMMA), one piece only, available in clear or opal colour.

DIFFUSORE realizzato in polimetilmetacrilato (PMMA) stabilizzato ai raggi UV, un pezzo unico, disponibile in colore trasparente o opale.

Decorative connection **RING** to be fixed on the luminaires diffuser.

ANELLO decorativo di connessione da fissare sul diffusore dell'apparecchio.

VIVI 400 HIGH POWER LED

V50.000 *



Dimensions and weight

Height: 420 mm
Diameter: 480 mm
Weight: 4,2 Kg
Junction to support: Ø 60 mm
Area expose to wind pressure:
CxS = m² 0,1449

Moulded colours:

Black White Grey

Diffuser PMMA:

Clear Opal

HIGH POWER LED



- **COST SAVING:** long-life and efficient LED light source.
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** E27 standard lamp holder.
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments.
- **SUITABLE FOR OUTDOOR USE:** built-in driver fully protected against heat and humidity by silicone paste.

*ADD. SUFFIX

Luminaires equipped with TÜV approved, long-life and efficient **E27 high power LED lamp**, granting the same luminous flux of traditional SON/HQI lighting sources. The lamp can be quickly and easily replaced, making the luminaires maintenance very simple.

	30 W	3300 Lm	4000 K	.Q1L
			3000 K	.Q1R
	50 W	5000 Lm	4000 K	.H1L
			3000 K	.H1R



LED LAMPS



More technical details about TÜV approved Fumagalli LED Lamps on page 512.

* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

PHOTOMETRIC DATA SAMPLE - VIVI 400 HIGH POWER LED



SAVE -40%

HIGH POWER LED 50W
(power consumption)

Area: 10x10mt
Height: 3,5mt
28 lux

VIVI 400 E27

HQI 70W 84W
(power consumption)

Area: 10x10mt
Height: 3,5mt
28 lux

VIVI 400

LARGE SIZE





MIDIPILAR/VIVI400
V50.254

Pcs 1
Kg 5,5
mc 0,092

NEW LOT/VIVI400
V50.115

Pcs 1
Kg 5,2
mc 0,071

VIVI 400
V50.000

Pcs 1
Kg 4,9
mc 0,09

MARIO/VIVI400
V50.129

Pcs 1
Kg 5,2
mc 0,07

EKTOR 3000 MIDIPILAR/VIVI400 1L V50.364.A10	AKILLE 3000 MIDIPILAR/VIVI400 1L V50.414.A10
Pcs 1 Kg 34 mc 0,262	

EKTOR 4000 MIDIPILAR/VIVI400 1L V50.371.A10	AKILLE 4000 MIDIPILAR/VIVI400 1L V50.421.A10
Pcs 1 Kg 41 mc 0,314	

EKTOR 2500 MIDIPILAR/VIVI400 1L
V50.361.A10

Pcs 1
Kg 30,6
mc 0,235

VIVI 400

LARGE SIZE



