

Touch Screen Constant-Temperature Incubator

Features:

- * Large LCD touch screen.
- * D type: with inner glass door.
- * G type: with viewing window.
- * Microprocessor controller.
- * Stainless steel chamber.



Double-layer Door (D type)



Glass Viewing Window Door (G type)

Safety Functions:

- * Over temperature alarm.
- * Independent limit temperature alarm system.
- * Leakage current and over-voltage protector.

Standard Accessories:



Test port



Base stand



Universal casters



UV lamp

Optional Accessories:

Technical Parameters:

Model	BJPX-H548K(D/G)	BJPX-H888K(D/G)	BJPX-H1608K(D/G)
Capacity	54L	88L	160L
Temperature Control Method	PT100		
Temperature Range	RT+5~85°C		
Temperature Stability	±0.5°C (at 37°C)		
Temperature Uniformity	±1°C (at 37°C)		
Ambient Temperature	5~30°C, recommend 25°C±2°C		
Timing Range	0~999h		
Shelves	2pcs/adjustable		
Power Consumption	345W		495W
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110±10%, 60Hz(Optional)		
Internal Size(W*D*H)mm	395*346*395	500*364*500	558*518*600
External Size(W*D*H)mm	D type: 536*588*681 G type: 522*626*587	D type: 650*573*793 G type: 627*621*892	D type: 716*732*890 G type: 685*779*790
Package Size(W*D*H)mm	D type: 606*648*818 G type: 592*676*724	D type: 720*630*930 G type: 697*671*820	D type: 788*792*1027 G type: 755*829*927
Gross Weight(kg)	D type: 51 G type: 44	D type: 85 G type: 51	D type: 89 G type: 69