



E-77/0

- Connector: RJ11 modular plug 4P4C
- Flow diverter to be ordered separately
- Measuring range: 0-100% O₂
- Output signal: 7.5–13.0 mV
- Response time: < 12 seconds
- Warranty: 16 months
- Storage: up to 6 months



E-77/0S

- Connector: RJ11 modular jack
- Flow diverter to be ordered separately
- Measuring range: 0-100% O₂
- Output signal: 9-13 mV
- Response time: < 15 seconds
- Warranty: 16 months
- Storage: up to 6 months



E-15/2

- Connector: 3 contact rings
- Measuring range: 0-100% O₂
- Output signal: 14.–20 mV
- Response time: < 12 seconds
- Warranty: 15 months
- Storage: up to 6 months



E-75/6 and E-75/8

- Connector: E-75/KE6: SM2SH 2pol
- Connector: E-75/KE8: IP40 3pol
- Measuring range: 0-100% O₂
- Output signal: 10-14 mV
- Response time: < 13 seconds
- Warranty and Storage as E-75/4



E-15/5M

- specification as E-15/5 however different housing to fit for Mindray WATO



E-16/0

- Connector: 3-pin Molex
- Measuring range: 0-100% O₂
- Output signal: 9.5-16 mV
- Response time: < 12 seconds
- Warranty: 16 months
- Storage: up to 6 months



E-17/M

- Connector: 3-pin Molex
- Measuring range: 0-100% O₂
- Output signal: 12.5-16.5 mV
- Response time: < 12 seconds
- Warranty: 16 months
- Storage: up to 6 months