

Environmentally Friendly & High-efficiency

Environmentally-friendly Freon-free refrigerant and high-efficiency compressor supplied by an international famous brand ensure energy saving and high efficiency.

Refrigeration System

Two compressors and separate control of the upper refrigeration chamber and the lower freezing chamber.

☐ High-precision Computerized Temperature Control

The digital temperature display can indicate operating status clearly, and users may set the high temperature/low temperature alarm points based on their needs.

Thermal Insulation System

The CFC-free polyurethane foam technology and the thicker insulating layer can improve the effect of thermal insulation.



TemperatureControl System

·digital temperature display, clear opera-ion status.

temperature points can be set according to High and low temperature alarm user requirements,

- · High precision microcomputer temperature control system, 2 ~ 8 °C refrigerated, Frozen - 10 ~ - 26 °C adjustable;
- Display both refrigerating temperature and freezing temperature, refrigerating room, The refrigerating chamber can be closed separately.



Refrigeration System

- · Environmentally-friendly Freon-free refrigerant and high-efficiency compressor supplied by an international famous brand ensure energy saving and high efficiency.
- Two compressors and separate control of the upper refrigeration chamber and the lower freezing chamber.
- ·The CFC-free polyurethane foam technology and the thicker insulating layer can improve the effect of thermal insulation.





Security System

- · The well-developed audible & visual alarm system makes it safer for storage;
- The turn-on delay and stopping interval protection function can ensure reliability in running;
- The door is equipped with a lock, improving security of sample storage.



Lighting System inside the Cabinet

The LED lighting system provides great visibility.




Human-oriented

- Three steel wire shelf are standard in the refrigerator room, and three ABS drawers are standard in the freezer room;
- Casters at the bottom with locking device for easy movement.


Scope of Application

Suitable for freezing of ice bars and storage of various things needing refrigerated storage such as blood plasma, reagent, etc. Suitable for use in hospitals, clinics, health and disease prevention systems, blood banks, laboratories in colleges & universities, the frozen food industry, and catering industry, etc.

Performance Data / Cooling Curve




External Dimensions













2~8°C/-10~-26°C Combined Refrig	erator and Freezer
Model	YCD-EL300
Cabinet Type	Upright
Capacity(L)	300, R:197, F:103
Internal Size(W*D*H)mm	R:600*510*657, F:500*460*535
External Size(W*D*H)mm	700*640*1876
Package Size(W*D*H)mm	760*720*1935
NW/GW(Kgs)	95/106
Performance	
Temperature Range	R:2~8, F:-10~-26
Ambient Temperature	16-32
Cooling Performance	R:5, F:-26
Climate Class	N
Controller	Microprocessor
Display	Digital display
Refrigeration	
Compressor	2pcs
Cooling Method	R: Forced air cooling , F:Direct cooling
Defrost Mode	R:Automatic,F:Manual
Refrigerant	R600a
Insulation Thickness(mm)	R:50, F:100
Construction	
External Material	DCM
	PCM
Inner Material	Aluminum plate with spraying
Inner Material Shelves	
	Aluminum plate with spraying
Shelves	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS)
Shelves Door Lock with Key	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes
Shelves Door Lock with Key Lighting	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED
Shelves Door Lock with Key Lighting Access Port	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm
Shelves Door Lock with Key Lighting Access Port Casters	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm
Shelves Door Lock with Key Lighting Access Port Casters Alarm	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake)
Shelves Door Lock with Key Lighting Access Port Casters Alarm Temperature	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake) High/Low temperature, High ambient temperature
Shelves Door Lock with Key Lighting Access Port Casters Alarm Temperature Electrical	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake) High/Low temperature, High ambient temperature Power failure,Low battery
Shelves Door Lock with Key Lighting Access Port Casters Alarm Temperature Electrical System	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake) High/Low temperature, High ambient temperature Power failure,Low battery
Shelves Door Lock with Key Lighting Access Port Casters Alarm Temperature Electrical System Electrical	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake) High/Low temperature, High ambient temperature Power failure,Low battery Sensor failure,Door ajar,Built-in USB datalogger failure,Communication failure
Shelves Door Lock with Key Lighting Access Port Casters Alarm Temperature Electrical System Electrical Power Supply(V/HZ)	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake) High/Low temperature, High ambient temperature Power failure,Low battery Sensor failure,Door ajar,Built-in USB datalogger failure,Communication failure 220-240~/50
Shelves Door Lock with Key Lighting Access Port Casters Alarm Temperature Electrical System Electrical Power Supply(V/HZ) Power(W)	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake) High/Low temperature, High ambient temperature Power failure,Low battery Sensor failure,Door ajar,Built-in USB datalogger failure,Communication failure 220-240~/50 250
Shelves Door Lock with Key Lighting Access Port Casters Alarm Temperature Electrical System Electrical Power Supply(V/HZ) Power(W) Power Consumption(KWh/24h)	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake) High/Low temperature, High ambient temperature Power failure,Low battery Sensor failure,Door ajar,Built-in USB datalogger failure,Communication failure 220-240~/50 250 1.54
Shelves Door Lock with Key Lighting Access Port Casters Alarm Temperature Electrical System Electrical Power Supply(V/HZ) Power(W) Power Consumption(KWh/24h) Rated Current(A)	Aluminum plate with spraying R:3(coated steel wired shelf),F:3(ABS) Yes LED 2pcs. Ø 25 mm 4 (2 casters with brake) High/Low temperature, High ambient temperature Power failure,Low battery Sensor failure,Door ajar,Built-in USB datalogger failure,Communication failure 220-240~/50 250 1.54

 $^{^{\}star} \text{The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading.} \\$



There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.