

SPECIFICAȚII TEHNICE (F4.1)

						Alternativa nr.	
Numărul licitației:		ocds-b3wdp1-MD-1549877300				Data:	21.02.2019
Denumirea licitației:		Server					
Cod CPV	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
48800000-6	Server	ThinkSystem SR650	UE	Lenovo	Type Server rack mountable	Server rack mountable 2U	
					Processor	min. 2 Processors, min. 10 physical cores per each processor, min. 2.2 GHz base frequency, min. 3.0 GHz turbo frequency, cache min. 13 Mb, CPU Virtualization hypervisor support (vPro, VTx), TDP max. 85W per Processor	2x Intel Xeon Silver 4114 (10 Cores/20 Threads, 2.2GHz Base frequency, 3GHz Turbo frequency, 13.75MB Cache, Intel Hyper-Threading Technology, Intel Virtualization Technology (VT-x), Intel vPro Platform Eligibility, TDP max 85W
					Memory	min. 128 GB (4x 32 GB) DDR4 ECC RDIMM min. 2666 MHz, (up to 3.0 TB maximum memory)	128GB (4x 32GB TruDDR4 2666 MHz (2Rx4 1.2V) RDIMM), up to 3TB with 24x 128GB
					Network	min. 4 x Gigabit LAN ports, optional upgrades available	4x Gigabit LAN ports, optional upgrades available
					HDD bays included	24x 2.5" SAS/SATA/SSD included drives capacity	24x 2.5" SAS/SATA/SSD included drives capacity
					HDDs array	14x 300GB 15K 12G SAS 2.5" Enterprise Hot Plug HDD	14x 300GB 15K 12G SAS 2.5" Enterprise Hot Plug HDD
					Controllers	Hardware RAID controller, support for RAID 0,1,10,5,6,50,60, min. 2GB flash cache	ThinkSystem RAID 930-24i 4GB Flash PCIe 12Gb Adapter (dedicated PCIe slot 7), support for RAID 0,1,10,5,50,6,60
					Ports	min.: 1x Video port, 4x RJ45, 3x USB (min. 2x USB 3.0), 1x Micro SD slot	VGA, 3x USB 3.0, 4x RJ-45, XClarity Controller network connector
					Management	Health monitoring, advanced predictive fail warning, power and thermal control, full remote administration, dedicated RJ45 and Service ports, bluescreen capture, mapping of remote media drives, Perpetual license.	XClarity Controller Enterprise perpetual license: Health monitoring, advanced predictive fail warning, power and thermal control, full remote administration, dedicated RJ45 port and service USB2.0 port, bluescreen capture, mapping of remote media drives

