



# BULGARKONTROLA

**BULGARKONTROLA SA -Sofia**

*Conformity Assessment Body for Construction Products*

*With identification number 14 and Permit № ПССП-14 on 15.09.2016*

*Issued by Ministry of Regional Development and Public Works*

## CERTIFICATE OF CONFORMITY

**14 – НУРВСУСРВ – 3739**

Issued pursuant to Art. 14, par.1 and par.2 of the Regulation № ПД-02-20-1 on 05.02.2015 on the terms and conditions for use of construction products in the construction of the Republic of Bulgaria on Ministry of Regional Development and Public Works for the **construction product**

### **System made of One-component acrylic paint "Deko Professional"**

**With reflective glass beads GV150x850MBT produced of "Interminglass"- Potters**

For horizontal road marking with product range, colours and evaluated characteristics in accordance with national requirements as per Supplement № 1 to this Certificate.

placed on the market by

**ORGACHIM AD**

**21 Treti Mart Blvd., 7000 Rousse, Bulgaria**

**ID 117001047**

manufactured by

**ORGACHIM AD**

**21 Treti Mart Blvd., 7000 Rousse, Bulgaria**

This certificate certifies that the product has been evaluated and meets national requirements set out in

**BDS EN 1436:2018**

*and item 4.4. of Annex 3 to item 2 of Order № 02-14-1329 from 03.12.2015,  
the Minister of Regional Development and Public Works*

*Amendment and addition by Order № RD-02-14-257 from 13.03.2019 г.*


The certificate was issued on **15/12/2022** cancel the Certificate № 14-НУРВСУСРВ-3300 on **23/12/2019** and remains valid for three years until **14/12/2025**, provided that the manufacturer ensures consistency of product characteristics and the conditions of production or production control have not been changed significantly.

**Place: Sofia**

**Date: 15/12/2022**

**Director of "Conformity Assessment" Dept.**

*[Signature]*  
**/T. Lyubenova/**







**Product range, colour and and evaluated characteristics  
in accordance with national requirements**

Characteristics	Requirement to declare / border level
<b>1. Deko Professional road marking paint type “Normal”</b>	
<b>1.1. White</b>	
1.1.1. Classes of Qd for dry road markings, $med.m^{-2} .lx^{-1}$	<b>class Q, <math>Q&gt;160</math></b> According to table 1, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day. for roads III class roads and municipal roads and streets IV class
1.1.2. Classes of RL for dry road markings, $med.m^{-2} .lx^{-1}$	<b>class R4, <math>RL\geq 200</math></b> According to table 3, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day. for roads III class roads and municipal roads and streets IV class
1.1.3. Classes of RL for road markings during wetness, $med.m^{-2} .lx^{-1}$	<b>class RW2, <math>RL\geq 35</math></b> According to table 4, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day. for roads III class roads and municipal roads and streets IV class
1.1.4. Luminance factor $\beta$	<b>class B3. <math>\beta\geq 40</math></b> According to table 2, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day. for roads III class roads and municipal roads and streets IV class
1.1.5. Corner points of chromaticity regions for white road markings - Coordinates x - Coordinates y	According to table 6, BDS EN 1436:2018 - 0.285-0.355 - 0.305-0.375
1.1.6. Classes of skid resistance, S SRT value	<b>class S2, <math>SRT\geq 50</math></b> According to table 8, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day. for roads III class roads and municipal roads and streets IV class
<b>1.2. Yellow</b>	
1.2.1 Classes of Qd for dry road markings, $med/lxm^{-2} .lx^{-1}$	<b>class Q4, <math>Q&gt;160</math></b> According to table 1, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day. for roads III class roads and municipal roads and streets IV class
1.2.2. Classes of RL for dry road markings, $med/lxm^{-2} .lx^{-1}$	<b>class R4, <math>RL\geq 200</math></b> According to table 3, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day. for roads III class roads and municipal roads and streets IV class

Place: Sofia  
Date: 15/12/2022

Director of "Conformity Assessment" Dept.   
/T. Lyubenova/






**Supplement № 1**  
**to Certificate of Conformity № 14– HYPBCПCРБ-3739**

1	2
1.2.3. Classes of RL for road markings during wetness, $med/lxm^{-2} \cdot lx^{-1}$	<b>class RW, <math>RL \geq 35</math></b> According tabl. 4, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day, for roads III class roads and municipal roads and streets IV class
1.2.4. Luminance factor $\beta$	<b>class B3, <math>\beta \geq 40</math></b> According tabl. 5, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day, for roads III class roads and municipal roads and streets IV class
1.2.5. Corner points of chromaticity regions for yellow road markings - Coordinates x - Coordinates y	According tabl. 6, BDS EN 1436:2018 - 0.389-0.545 - 0.399-0.535
1.2.6. Classes of skid resistance, S SRT value	<b>class S2, <math>S \geq 50</math>,</b> According tabl. 7, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day, for roads III class roads and municipal roads and streets IV class
<b>2. Deko Professional road marking paint type "City"</b>	
<b>2.1. White</b>	
2.1.1. Classes of Qd for dry road markings, $med/lxm^{-2} \cdot lx^{-1}$	<b>class Q4, <math>Q &gt; 160</math></b> According tabl. 1, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day, for roads III class roads and municipal roads and streets IV class
2.1.2. Classes of RL for dry road markings, $med/lxm^{-2} \cdot lx^{-1}$	<b>class R4, <math>RL \geq 200</math></b> According tabl. 3, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day, for roads III class roads and municipal roads and streets IV class
2.1.3. Classes of RL for road markings during wetness, $med/lxm^{-2} \cdot lx^{-1}$	<b>class RW2, <math>RL \geq 35</math></b> According tabl. 4, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day, for roads III class roads and municipal roads and streets IV class
2.1.4. Luminance factor $\beta$	<b>class B3, <math>\beta \geq 40</math></b> According tabl. 2, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day, for roads III class roads and municipal roads and streets IV class
2.1.5. Corner points of chromaticity regions for white road markings - Coordinates x - Coordinates y	According tabl. 6, BDS EN 1436:2018 - 0.285-0.355 - 0.305-0.375
2.1.6. Classes of skid resistance, S SRT value	<b>class S2, <math>SRT \geq 50</math>,</b> According tabl. 7, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year. per day, for roads III class roads and municipal roads and streets IV class

**Place: Sofia**  
**Date: 15/12/2022**

**Director of "Conformity Assessment" Dept.**   
**/T. Lyubanova/**





**Supplement № 1**  
**to Certificate of Conformity № 14– НУРВСИРСРБ-3739**

1	2
<b>2.2. Yellow</b>	
2.2.1. Classes of Qd for dry road markings, $\text{mcd/lxm}^{-2} \cdot \text{lx}^{-1}$	<b>class Q4, <math>Q &gt; 160</math></b> According tabl. 1, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year, per day, for roads III class roads and municipal roads and streets IV class
2.2.2. Classes of RL for dry road markings, $\text{mcd/lxm}^{-2} \cdot \text{lx}^{-1}$	<b>class R4, <math>RL \geq 200</math></b> According tabl. 3, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year, per day, for roads III class roads and municipal roads and streets IV class
2.2.3. Classes of RL for road markings during wetness, $\text{mcd/lxm}^{-2} \cdot \text{lx}^{-1}$	<b>class RW2, <math>RL \geq 35</math></b> According tabl. 4, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year, per day, for roads III class roads and municipal roads and streets IV class
2.2.4. Luminance factor $\beta$	<b>class B3, <math>\beta \geq 40</math></b> According tabl. 5, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year, per day, for roads III class roads and municipal roads and streets IV class
2.2.5. Corner points of chromaticity regions for yellow road markings - Coordinates x - Coordinates y	According tabl. 6, BDS EN 1436:2018 - 0,389-0,545 - 0,399-0,535
2.2.6. Classes of skid resistance, S SRT value	<b>class S2, <math>SRT \geq 50</math>,</b> According tabl. 7, BDS EN 1436:2018 for class II roads with an annual average daily intensity of less than 4000 units / year, per day, for roads III class roads and municipal roads and streets IV class

**Place: Sofia**  
**Date: 15/12/2022**

**Director of "Conformity Assessment" Dept.**

*(Signature)*  
**/T. Lyubanova/**

