SUPERVEGA SUCTION ASPIRATOR ON TROLLEY



• 28191 SUPERVEGA on trolley - suction 2x2 l jar

• 28192 SUPERVEGA on trolley - suction 2x2 I jar with footswitch

Continuously adjustable vacuum, with indicator. Silicone connection tube 8x14 mm. 2 jars 2 l, made of sterilizable polycarbonate (autoclavable at 121°C). Approved for NON-STOP operation without overheating. Suction power: 40 air litres/min. Steel painted frame, fitted with 5 star base.

TECHNICAL SPECIFICATIONS

Size: 38x36xh 92 cm Weight 6.2 kg Operating voltage: 220-230 V - 50/60 Hz; other on request Power consumption: 110 VA

Maximum suction: -0.80 bar (600 mm Hg) Flow: 40 air litres/minute

Operating cycle: continuous Noise level: 61.5 dBA

Norms EN 60601-1-1, EN 60601-1-2 - € 93/42 EEC - Class II - Type B

Supervega on trolley also fits Flovac® jars 28272 for disposable liners 28273. See below





• 28193 SUPERVEGA BATTERY on trolley - suction 2x2 l jar

• 28197 SUPERVEGA BATTERY on trolley - suction 2x2 l jar with footswitch Professional portable suction unit for the aspiration of body liquids, oral, nasal and tracheal aspiration in adults or children. Suction power of 36 l/min. Double collection jars on a stand with five castors for easy transport. Two different working options: AC/DC adapter or rechargeable battery make it a versatile suction unit approved for NON-STOP operation without overheating. Visual and acoustic alarm indicating low battery level, vacuum-meter (bar & kPa) and vacuum regulator.

MADE IN ITALY

TECHNICAL SPECIFICATIONS

Operating voltage: 100-240 V - 50/60 Hz Internal rechargeable Pb battery: 12V - 4A Battery autonomy: 60 min Recharging: 240 min Operating cycle: continuous with AC/DC Flow: 36 air litres/minute Noise level: 65.5 dBA Size - Weight: 32x30xh 99 cm - 7.9 kg Five antistatic wheels with brake

User manual:

GB, FR, DE, IT, ES

ACCESSORIES AND SPARES FOR CLINIC PLUS, HOSPI PLUS, SUPERVEGA ON TROLLEY



AUTOCLAVABLE JARS WITH OVERFLOW VALVE SYSTEM

Equipped with screw cover with handle for easy grip, autoclavable silicone o-ring for tight seal, overflow valve system integrated in the cover, clear graduated scale in ml with 100 or 200 ml intervals. Suitable for central vacuum systems and Gima suction units. Available in two types of polycarbonate. Makrolon® and Apec®

polycarbonate, Makrolon [®] and Apec [®] .					
GIMA code	AUTOCLAVABLE JARS	Compatible with			
	JARS IN MAKROLON® AUTOCLAVABLE UP TO 121°C				
28236	Jar 2 I with cover - Makrolon®	2 l aspirators			
28227	Cover for jar 2 l	28236			
28228	Jar 4 l with cover - Makrolon®	4 or 5 l aspirators			
	Cover for jar 4 l	28228			
28221	Jar 5 l with cover - Makrolon®	4 or 5 l aspirators			
28225	Cover for jar 5 l	28221			
JARS IN APEC® AUTOCLAVABLE UP TO 143°C					
28186	Jar 2 I with cover - Apec®	2 l aspirators			
28184	Cover for jar 2 l	28186			
28187	Jar 5 l with cover - Apec®	4 or 5 l aspirators			
28188	Cover for jar 5 l	28187			
ANTIBACTERIAL, HYDROPHOBIC FILTERS					
28237		D, E			
28239	Hydrophobic, antibacterial filter	A, B, C			

FLOVAC® DISPOSABLE LINERS

Equipped with polyethylene disposable liner, hydrophobic filter, overflow system, reusable container with clear graduated scale in ml with 50 ml intervals.

GIMA code	FLOVAC® JARS AND DISPOSABLE LINERS	Compatible with	
28273 28274	Reusable jar for disposable liner 2 l Disposable liner 2 l cover+bag Reusable jar for disposable liner 3 l Disposable liner 3 l cover+bag	B, C, D, E (only 2 l)* 28272 B, C, D, E (only 2 l)* 28274	
GIMA code	SPARES	Compatible with	
	Silicone tube 8x14 - roll of 30 m	A, B, C, D, E	
28253	Adapter to connect catheter to silicone tube	25482	
	Suction catheter see at page 51	28253	
28276	Vacuum indicator Ø 50 mm - spare	A, B	
28277	Vacuum indicator Ø 60 mm - spare	C, D, E	
28265	Bottom base	C, E	
28266	Bottom base	В	
	Bottom base	D	
28217	2 Pin British Plug - optional	All	
*Suitable also for MPR line using optional 2 Lring			

*Suitable also for MPR line using optional 2 I ring

LEGEND: A: SuperVega on trolley, B: Clinic, C: Clinic Plus, D: Hospital, E: Hospi Plus