

HEPALAM-78-ARM

Laminar Flow Absolute Filters



HL11ARM2PG-0610-0610-078

FILTER CODE STRUCTURE

Type	HL	HEPALAM-78
Class EN 1822	11	E11
Frame	A	A: Aluminum
Media	R	R: Micro Glass Fibre Y: High Heat (Max. 120 °C)
Pleat Depth	M	K: 48 mm M: 58 mm
Surface Grid	2	0: Without Grid 1: Face Grid Air Outlet 2: Both Side with Grid
Gasket Type	P	X: Without Gasket P: Polyurethane R: Rubber E: EPDM Y: High Heat
Gasket Direction	G	X: No C: Air Outlet G: Air Inlet W: Both Side
Size		0610-0610-078

APPLICATIONS

- To be used for absolute air filtration in controlled contamination environments clean rooms, LAF benches and operating rooms

TECHNICAL SPECIFICATIONS

Class EN 1822	E10	E11	E12
Av. Efficiency EN 1822	≥85 %	≥95 %	≥99,5%
Max. Temperature	80°C (Optional 120 °C)		
Relative Humidity	100 %		
Rec. Final Pres. Drop	600 Pa.		
Filter Stage	III - IV		

HEPALAM-78-ARM Series Technical Data

Code	Size W x L x D	Filter Class EN 1822	Depth mm	Area m ²	Air Flow m ³ /h	In.Pressure Drop (pa)	Weight kg
HL10ARM2PG	0305-0305-078	E10	78	2,80	150	60	1,85
HL10ARM2PG	0305-0610-078	E10	78	5,50	300	60	3,50
HL10ARM2PG	0457-0457-078	E10	78	6,00	350	60	4,25
HL10ARM2PG	0457-0610-078	E10	78	8,00	450	60	6,50
HL10ARM2PG	0610-0610-078	E10	78	10,50	600	60	6,80
HL10ARM2PG	0610-0762-078	E10	78	13,00	750	60	8,50
HL10ARM2PG	0610-0915-078	E10	78	15,50	900	60	10,00
HL10ARM2PG	0610-1220-078	E10	78	21,00	1200	60	12,50

Code	Size W x L x D	Filter Class EN 1822	Depth mm	Area m ²	Air Flow m ³ /h	In.Pressure Drop (pa)	Weight kg
HL11ARM2PG	0305-0305-078	E11	78	2,80	150	70	1,85
HL11ARM2PG	0305-0610-078	E11	78	5,50	300	70	3,50
HL11ARM2PG	0457-0457-078	E11	78	6,00	350	70	4,25
HL11ARM2PG	0457-0610-078	E11	78	8,00	450	70	6,50
HL11ARM2PG	0610-0610-078	E11	78	10,50	600	70	6,80
HL11ARM2PG	0610-0762-078	E11	78	13,00	750	70	8,50
HL11ARM2PG	0610-0915-078	E11	78	15,50	900	70	10,00
HL11ARM2PG	0610-1220-078	E11	78	21,00	1200	70	12,50

Code	Size W x L x D	Filter Class EN 1822	Depth mm	Area m ²	Air Flow m ³ /h	In.Pressure Drop (pa)	Weight kg
HL12ARM2PG	0305-0305-078	E12	78	2,80	150	100	1,85
HL12ARM2PG	0305-0610-078	E12	78	5,50	300	100	3,50
HL12ARM2PG	0457-0457-078	E12	78	6,00	350	100	4,25
HL12ARM2PG	0457-0610-078	E12	78	8,00	450	100	6,50
HL12ARM2PG	0610-0610-078	E12	78	10,50	600	100	6,80
HL12ARM2PG	0610-0762-078	E12	78	13,00	750	100	8,50
HL12ARM2PG	0610-0915-078	E12	78	15,50	900	100	10,00
HL12ARM2PG	0610-1220-078	E12	78	21,00	1200	100	12,50

HEPALAM-78-ARM

Laminar Flow Absolute Filters



HL13ARM2PG-0610-0610-078

FILTER CODE STRUCTURE

Type	HL	HEPALAM-78
Class EN1822	13	H13
Frame	A	A: Aluminum
Media	R	R: Micro Glass Fibre Y: High Heat (Max. 120 °C)
Pleat Depth	M	K: 48 mm M: 58 mm
Surface Grid	2	0: Without Grid 1: Face Grid Air Outlet 2: Both Side with Grid
Gasket Type	P	X: Without Gasket P: Polyurethane R: Rubber E: EPDM Y: High Heat
Gasket Direction	G	X: No C: Air Outlet G: Air Inlet W: Both Side
Size	0610-0610-078	

APPLICATIONS

- To be used for absolute air filtration in controlled contamination environments clean rooms, LAF benches and operating rooms

TECHNICAL SPECIFICATIONS

Class EN1822	H13	H14	U15
Av. Efficiency EN1822	≥99.95 %	≥99.995 %	≥99.9995 %
Max. Temperature	80°C (Optional 120 °C)		
Relative Humidity	100 %		
Rec. Final Pres. Drop	600 Pa.		
Filter Stage	III - IV		

HEPALAM-78-ARM Series Technical Data

Code	Size W x L x D	Filter Class EN 1822	Depth mm	Area m ²	Air Flow m ³ /h	In.Pressure Drop (pa)	Weight kg
HL13ARM2PG	0305-0305-078	H13	78	2,80	150	110	1,85
HL13ARM2PG	0305-0610-078	H13	78	5,50	300	110	3,50
HL13ARM2PG	0457-0457-078	H13	78	6,00	350	110	4,25
HL13ARM2PG	0457-0610-078	H13	78	8,00	450	110	6,50
HL13ARM2PG	0610-0610-078	H13	78	10,50	600	110	6,80
HL13ARM2PG	0610-0762-078	H13	78	13,00	750	110	8,50
HL13ARM2PG	0610-0915-078	H13	78	15,50	900	110	10,00
HL13ARM2PG	0610-1220-078	H13	78	21,00	1200	110	12,50

Code	Size W x L x D	Filter Class EN 1822	Depth mm	Area m ²	Air Flow m ³ /h	In.Pressure Drop (pa)	Weight kg
HL14ARM2PG	0305-0305-078	H14	78	2,80	150	125	1,85
HL14ARM2PG	0305-0610-078	H14	78	5,50	300	125	3,50
HL14ARM2PG	0457-0457-078	H14	78	6,00	350	125	4,25
HL14ARM2PG	0457-0610-078	H14	78	8,00	450	125	6,50
HL14ARM2PG	0610-0610-078	H14	78	10,50	600	125	6,80
HL14ARM2PG	0610-0762-078	H14	78	13,00	750	125	8,50
HL14ARM2PG	0610-0915-078	H14	78	15,50	900	125	10,00
HL14ARM2PG	0610-1220-078	H14	78	21,00	1200	125	12,50

Code	Size W x L x D	Filter Class EN 1822	Depth mm	Area m ²	Air Flow m ³ /h	In.Pressure Drop (pa)	Weight kg
HL15ARM2PG	0305-0305-078	U15	78	2,80	150	140	1,85
HL15ARM2PG	0305-0610-078	U15	78	5,50	300	140	3,50
HL15ARM2PG	0457-0457-078	U15	78	6,00	350	140	4,25
HL15ARM2PG	0457-0610-078	U15	78	8,00	450	140	6,50
HL15ARM2PG	0610-0610-078	U15	78	10,50	600	140	6,80
HL15ARM2PG	0610-0762-078	U15	78	13,00	750	140	8,50
HL15ARM2PG	0610-0915-078	U15	78	15,50	900	140	10,00
HL15ARM2PG	0610-1220-078	U15	78	21,00	1200	140	12,50