

Histo-Tek® VP1™

Vacuum Infiltration Processor

Specifications



General

Name and description	Histo-Tek® VP1™ Vacuum Infiltration Processor
Itemcode	1700
Dimensions (WxDxH)	55.2 x 60.4 x 132.8 cm
Height to retort	103.3 cm
Weight	130 kg

Electrical

Rated power supply	100/115/220-240VAC, 50/60Hz
Power consumption	1,200 VA

Environmental

Operational temperature range	+10 °C to +40 °C
Operational relative humidity	30 to 85%, non-condensing
Storage temperature	-10 °C to +60 °C
Storage relative humidity	30 to 90%, non-condensing

Operating

Capacity	Up to 300 standard cassettes
Processing reagent	Reagent bottles: 10 Reagent volume required (150 cassettes): 2.0 - 3.5L Reagent volume required (300 cassettes): 3.2 - 3.5L
Cleaning reagent	Reagent bottles: 2 Reagent volume required: 4.5 - 4.8L
Paraffin container	Containers: 4 Paraffin volume required (150 cassettes): 2.0 - 3.5L Paraffin volume required (300 cassettes): 3.2 - 3.5L
Mixing method	Pump-in and pump-out
Fume control	Activated carbon filter and condenser

User interface

Display	10.4-inch colour LCD, touch screen
Data interface	USB data port

Certifications

Regulatory status	(EU) 2017/746 CE IVD, Class A device
Conformity	2011/65/EU (EU) 2015/863 EN IEC 63000:2018

Visit us at sakura.com

Sakura Finetek Europe B.V., Flemingweg 10A, 2408 AV Alphen aan den Rijn
P.O. Box 362, 2400 AJ Alphen aan den Rijn, The Netherlands

