

YUKO MGE-46V (HM 46)

HYDRAULIC OIL.

SPECIFICATIONS:

ISO 46

DESCRIPTION:

It is used for hydraulic systems (hydrostatic drive) of agricultural and other machinery operating at a pressure of up to 35 MPa with a short-term increase to 42 MPa.

Produced from high-quality base oils with a combined additive.

BENEFITS:

- It has anti-wear, anti-foam and anti-corrosion properties;
- Excellent fluidity characteristics at low temperatures;
- Non-aggressive in relation to materials of seals of hydraulic drives;
- Ehe main type of oil used in hydraulic systems of mobile machinery.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 40 °C, mm ² /s	46.1
Density at 20°C, kg/m ³	875
Viscosity index, min	95
Acid number, mg KOH/g	0.8
Flash point in open crucible, °C	210
Pour point, °C	-32

Packing	Vendor code	Barcode
Canister plastic 20l	001785	482007024036
Oilbox carton polyethylene 20l	010751	482007024326
Canister plastic 5l	004281	482007024198
Barrel metal 200l	001783	482007024038

Выпускается по ТУ У 23.2-31852954-003-2003. Данная информация является справочной и может быть изменена без уведомления. Данная публикация от 01.09.2014 г. заменяет все ранее опубликованные описания данного продукта.

0 800 60 5555
Telephone hotline