

Vertical Laminar Flow Cabinet



BBS-DDC/BBS-SDC



BBS-V680



BBS-V800

TECHNICAL PARAMETERS

Model	BBS-V680	BBS-V800	BBS-DDC	BBS-SDC
External Size (W*D*H)	680*410*1160mm	802*650*1550mm	1060*620*1850mm	1460*620*1850mm
Internal Size (W*D*H)	630*375*615mm	800*530*540mm	935*530*650mm	1335*530*650mm
Work Surface Height	/	660mm	750mm	750mm
Display	LED Display		LCD Display	
Airflow Velocity	Average of 0.3~0.5m/s, air speed adjustable		Average of 0.3~0.45m/s, air speed adjustable	
Material	Main Body: Cold-rolled steel with anti-bacteria power coating Work Table: 304 stainless steel(except model BBS-V680)			
Pre-Filter	Polyester fiber, washable			
HEPA Filter	99.999% efficiency at 0.3 μm			
Noise	<85dB			
Front Window	/	Manual, 5mm toughened glass, anti-UV		
Max Opening	/	490mm	400mm	400mm
Illuminating Lamp	Fluorescent lamp 8W*1	LED lamp 8W*1	LED lamp 12W*1	LED lamp 16W*1
UV Lamp	15W*1	18W*1	20W*1	40W*1
	Emission of 253.7 nanometers			
Consumption	160W	350W	150W	250W
Standard Accessory	Fluorescent lamp UV lamp*2 Water & gas tap	LED lamp UV lamp*2 Base stand	LED lamp UV lamp*2 Base stand	LED lamp UV lamp*2 Base stand
Optional Accessory	/	Electric height adjustable base stand		
Caster	/	Universal wheel with leveling feet		
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz			
Gross Weight	50kg	116kg	185kg	231kg
Package Size (W*D*H)	840*560*1380mm	960*800*1800mm	1240*900*1350mm	1640*900*1350mm