



Shedding New Light On MICROSCOPY


Focus in comfort. Comfort in focus.

Nikon has designed the ECLIPSE Si to meet the rigorous demands of professionals who spend hours using the microscope. The ECLIPSE Si is ergonomically designed to enhance operational efficiency. This powerful instrument helps you to stay focused for longer by reducing the strain on your body. The ECLIPSE Si is the new standard in microscopes, expanding the possibilities of exploring the micro world.



Pursuing efficient workflow

The ECLIPSE Si has been developed with the primary goal of reducing fatigue during microscope usage. The ECLIPSE Si eliminates unnecessary adjustments and enables efficient and comfortable operation. The ergonomic design also enables natural posture, even when carrying out repetitive tasks.



aintains comfortable brightness when switching magnifications

Objective lenses with different magnifications transmit light to varying degrees. Therefore, light intensity must be adjusted every time the user changes the objective. In addition, when switching from high to low magnification objectives, the sudden increase in brightness often causes eye strain. The ECLIPSE Si features the intelligent Light Intensity Management (LIM) which automatically remembers and sets the light intensity level for each objective. The LIM feature reduces up to 40% of the time spent on adjusting light intensities*. With the ECLIPSE Si, users can increase comfort and save time even when the routine requires frequent magnification changes...

*Compared to a previous LED model as regards time required to change three objectives and adjust light intensities (test carried out by Nikon)




Push the brightness control knob briefly to activate the LIM feature.


LIM feature OFF

With low-power objective

Since brightness varies depending on the objective, switching magnifications can induce eye strain.

LIM feature ON





The optimal light intensity level is automatically recalled and applied to each objective, therefore eliminating unexpected changes in light intensity when changing magnifications and streamlining workflow.

ow stage for effortless slide replacement



The height of ECLIPSE Si stage is 135 mm, which is about 50 mm lower than our conventional microscopes. The lower stage design reduces the range of notion required to exchange specimen slides, and in turn this can reduce arm and shoulder fatigue. Since the position of the stage movement knob s also lower, different areas on the specimen slide can be easily explored while resting your hands on the table. The lever for opening and closing the pecimen holder has also been designed to be ergonomic with an easy-toperate size and shape. Furthermore, the ECLIPSE Si features a 30% smalle



Easy-to-operate specimen holder

ables natural posture to be maintained throughout the entire microscope workflow

The inclination angle of the eveniece tube is 45 degrees, which enables observation through the eyepieces while maintaining a natural posture. The low stage design also allows you to seamlessly switch from looking through the eyepieces to checking the slide placement on the stage without having to adjust your posture. An optional eye-level riser is also available to further tailor the height of the eyepieces.



Check on the stage while maintaining the observation posture

Orry free focusing thanks to vertical stop

The ECLIPSE Si is equipped with a stoppe that can be used to set the upper limit of the stage height. The stage stops at the set height even when the focus knob is turned thereby eliminating the risk of over-focusing and breaking the slides or damaging the bjectives.

Specimen exchange and focusing can be performed with confidence, without worrying about the stage height.



The stage does not rise above the set height.



Easy operation just by turning the screw at the height you

Pursuing stress-free ease of use

We wanted to design a microscope that would eliminate fatigue incurred by frequent specimen exchanges and provide a more comfortable user experience. The ECLIPSE Si combines innovative features and intelligent design to minimize unnecessary body movements, saving time and reducing strain on the user even when examining a large number of slides.

Adjusting focus and moving the stage with one hand

The coarse and fine focus knobs are located on both sides of the microscope, making it possible to focus with either hand. In addition, the stage handle is positioned close to the focus knob, allowing users to easily adjust both the stage position and focus with the same hand. With the stage movement and focus controlled by the same hand, the other hand can be dedicated to rotating the nosepiece or replacing the slides. These features provide an efficient workflow even when examining a large number of specimen slides.



Coarse focus knob Fine focus knob

Coarse/fine focus and stage movement can be operated with one hand

e illumination brightness is shown ir a bar graph on the LCD. You can check the magnification at a glance while maintaining your observation posture











Knob rotation direction display

The direction of rotation of the focus and brightness control knobs can be intuitively grasped.



No hesitation in choosing a knob to operate

The icon of the stage movement knob to be operated is illustrated on the travel scale of the specimen in the forward-backward and right-left directions.



Changing magnifications comfortably

The reversed-type nosepiece provides easy access and visibility to the objective lens in use. The position of the nosepiece is low to reduce strain on the arm when frequent magnification changes are required. The nosepiece features an easy grip for smooth rotation, and accommodates up to five objective lenses to provide a wide range of magnifications.



Fasy-to-rotate quintuple nosepiece

Blocks blue component in LED light

Since LED light contains a large amount of blue or short wavelength light, there is concern that prolonged observation may put a strain on the eyes. The ECLIPSE Si offers an optional blue light blocking filter that can be placed on the field lens to remove the blue component of the LED light.



tomatically powers off after a period

The ECLIPSE Si is equipped with an ECO mode which automatical turns off the illumination after a certain period of inactivity. The length of the inactivity period is adjustable. With ECO mode, the ECLIPSE Si helps you save power without any effort.



Press and hold the brightness control knob to turn on the ECO mode

Easily share images on-site and remotely

Capture specimen images for documentation or for real-time sharing with others by configuring the ECLIPSE Si (trinocular version) with a digital camera.



When the ECLIPSE Si is configured with the Digital Sight 1000 microscope camera (optional), images of specimens can be easily displayed on the monitor for simultaneous observation by multiple people, and recorded without the use of a PC. Furthermore, by connecting the camera to a tablet PC*, images can be shared in real time with remote or off-site PCs and smart devices via a network.

The DS-Fi3* high-definition microscope camera, which faithfully captures the true colors of specimens, is also available.

* NIS-Elements L imaging software is required.



Digital Sight 1000 microscope camera



Simultaneous observation and display of specimens on a



Share images in real-time with PCs in another room or building

Superior Optics for High Quality Images

Nikon's advanced optical technologies, culminating from a long tradition as a microscope manufacturer, play a vital role in the ECLIPSE Si. The ability to fulfill the need for accurate observation of specimens is a source of pride for us.



Excellent image flatness and chromatic aberration correction

The ECLIPSE Si employs CFI E Plan series objectives, which feature flat, sharp images up to the periphery of the field of view. These objectives are part of the CFI60 infinity-corrected optical system,

which achieves both high resolution and long working distances.
A wide variety of Nikon CFI60 objectives are




CFI E Plan series objectives

Observation with FOV of 22mm

The ECLIPSE Si can enhance the efficiency of clinical observations when equipped with FOV22 tubes* and lenses that enable a large 22mm field of view.


*C-TB, C-TF, C-TT and C-TE2 tubes






Long-life LED with constant color temperature

The high-intensity, white LED light source, features a long life of up to 60,000 hours. Since the color temperature remains constant even when the brightness is changed, the color of the image does not change when changing magnifications.






Uniform brightness up to the periphery of the field of view

The illumination system features an integrated fly-eye lens which provides uniform brightness over the entire field of view.





Blocking light from outside the field of view

The ECLIPSE Si is equipped with a field diaphragm that can be used to limit the illumination range for optimal observation and image acquisition. Adjusting the field diaphragm suppresses the occurrence of flare and ghosting, enabling high contrast image observation. During fluorescence observation, the range of photobleaching of specimens can also be limited.




Turn the field diaphragm dial until the illumination range is circumscribed to the field of view.

Compatible with a Wide Variety of Observation Methods

Using optional accessories, the ECLIPSE Si allows for a wide variety of observation methods in addition to bright-field.

Bright-field observation

High-quality images can be acquired with bright, uniform illumination over the entire field of view, using objectives with superior image flatness and excellent chromatic aberration correction.



Phase contrast observation

Combining of a phase condenser and phase contrast objectives enables observation of colorless and transparent specimens with high contrast, without staining or labeling the specimens with dyes. A standard Abbe condenser, with a PH slider inserted, also allows phase contrast observation.










Dark-field observation

By inserting a slider for dark-field microscopy into the condenser slot and using oblique illumination, light scattered by specimens can be visualized. This method is effective for observation of unstained specimens such as live bacteria and examination of colloidal particles.





Simple polarizing observation

By attaching a polarizer to the field lens and an analyzer to the eyepiece tube mount, simple polarizing observation can be performed. The polarization state can be adjusted by turning the polarizer.





olarizer and analyzer for simple polarizing




Diascopic fluorescence observation

Nikon has developed a unique diascopic fluorescence illumination method that enables easy fluorescence observation without attaching dedicated episcopic illuminator and fluorescence observation equipment. By simply inserting an EX filter slider into the condenser slot and a BA filter slider into the nosepiece slot, fluorescence observation of specimens expressing GFF or stained with fluorescent dyes such as FITC and Alexa 488 can be performed.





Diascopic fluorescence set



Online Guide accessible with a **Smartphone**

You can access a web-based operation manual for the ECLIPSE Si on your smartphone by simply scanning the QR code sticker attached to the microscope. The Online Guide provides visual instructions including movies that enable you to guickly check how to setup and use the microscope. *QR code is a registered trademark of DENSO WAVE INCORPORATED.





Optional accessories

Digital Sight 1000 microscope camera

Equipped with a 2-megapixel CMOS image sensor, the Digital Sight 1000 can acquire color images and movies of up to 1920 x 1080 pixels. Just connect a monitor* and a mouse, and you can easily capture images without using a PC.





DS-Fi3 microscope camera

Equipped with a 5.9-megapixel CMOS image sensor. The DS-Fi3 can acquire high-resolution color images of up to 2880 x 2048 pixels*. Its excellent color reproducibility enables the acquisition of images with colors faithful to those of the images observed under the microscope. Its high sensitivity also makes the DS-Fi3 ideal for acquiring fluorescence images.

* NIS-Elements L imaging software is required for controlling the camera.



NIS-Elements L imaging software

By connecting the Digital Sight 1000 or DS-Fi3 to a tablet PC with NIS-Elements L installed, images of specimens under observation can be shared with other PCs via a network. The software also contains a variety of measurement and annotation functions.



Teaching Head

Enables simultaneous observation by two people using the same microscope. Available in two types: face-to-face type and side-by-side. Areas of interest can be indicated with the built-in LED pointer.



Eye-level Riser


By mounting the eye-level riser under the eyepiece tube, the eyepoint can be raised by 25 mm. The height of the eyepiece can be adjusted to fit the observer, which allows observation in a comfortable posture.





Up to two pieces (50 mm) can be mounted.

System diagram C-mount Camera Centering CFI E 15X CFI E 10X C-DA C-0.7X C-0.55X C-mount Adapter DXM Relay Lens DS Relay Lens Y-TV55 TV Tube 0.55X C-mount Camera C-TEP3 DSC Port for EC-T-TB2 Ф Trinocular Tube F E2EP Eveniece pointer C-OA 15r Teaching Unit Face to Face Dia-FL set GFP-B CEIGO Objectives Y-THPL LED Pointer Unit for Teaching Unit 4-AC AC Adapter F2-F-RF Blue Light Blocking Filter EZ-SPRT 10-40X PH Slider E2-SPHZ 100X PH Slider Dark-field Slider Y-THSP Support for Side by Side * C-TEP2 DSC Port for Ergonomic Binocular Tube with built-in 0.7X relay lens is also available ** Replaced with supplied Abbe condenses



Specifications

Model name	Main body: ECLIPSE Si
Optical system	CFI60 infinity optical system
Illumination	High luminescent white LED illuminator (Eco-illumination) • Built-in fly-eye lens • Up to two 45 mm diameter filters can be installed* • Light Intensity Management (LIM) feature included
Focusing	Coaxial coarse/fine focusing (located on both sides), cross roller guide, Focusing stroke: Up 2 mm/Down 13 mm, coarse: 37.7 mm per rotation, fine: 0.2 mm per rotation, minimum reading: 2 µm With coarse focus knob torque adjustment ring and stage vertical movement stopper
Eyepieces (F.O.V., mm)	With diopter adjustment ■ E2-CFI 10X (20)*², E2-CFI 15X (12)*² ■ CFI 10X (22)*³
Tubes	Inclination angle 45°, pupillary distance: 50-75 mm, eyepoint height: adjustable to 2 positions • EC-T-TB2 Binocular Tube 2 • EC-T-TF2 Trinocular Tube F2 (Eyepiece: Port: 50:50, built-in 0.55X relay lens in camera port, with C-mount) Inclination angle 25°, pupillary distance: 50-75 mm • C-TB Binocular Tube • C-TF Trinocular Tube F (Eyepiece: Port = 100:0, 0:100)
Nosepiece	• C-TT Trinocular Tube T (Eyepiece: Port = 100:0, 20:80, 0:100) Inclination angle 10°-30°, extension: up to 40 mm • C-TE2 Ergonomic Binocular Tube (Eyepiece: Port = 100:0, 50:50 via optional C-TEP3 DSC Port C-0.55X) Reversed-type quintuple nosepiece (within main body)
	Rectangular mechanical stage (within main body), with specimen holder 2L and vernier calibrations, cross travel: 76 (X) x 52 (Y) mm
Objectives (NA/W.D.)	CFI E Plan Achromat 4X (0.1/30mm)*4 CFI E Plan Achromat 4XX (0.25/7mm) CFI E Plan Achromat 4XX (0.50/6.65mm) CFI E Plan Achromat 40X (0.65/0.65mm) CFI E Plan Achromat 100X Oil (1.25/0.23mm)*4 Other CFI60 objectives can also be used. Objectives for phase contrast observation: CFI Achromat DL 10X (0.25/7.0mm) CFI Achromat DL 10X (0.40/3.90mm) CFI Achromat DL 40X (0.65/0.65mm) CFI Achromat DL 100X Oil (1.25/0.23mm)
Condenser	Abbe Condenser, NA 1.25, vertically movable and centerable
Observation methods*5	Brightfield, phase contrast, diascopic fluorescence, dark-field, simple polarizing
Fungus-proof treatment	Antifungal paint is applied around optical system
Optional accessories	E2-SPH1 10X-40X PH slider/E2-SPH2 100X PH slider (used with an Abbe condenser and phase contrast objectives) SI-PH phase condenser (used with phase contrast objectives) E2-F-FL Dia-FL set GFP-B E2-SDF dark-field slider E2-DP simple polarizer, E2-PSA simple analyzer E2-SPF dark-field slider E2-DP simple polarizer, E2-PSA simple analyzer E2-SPF dark-field slider E2-DP simple polarizer, E2-PSA simple analyzer
Power supply	Uses the included AC adapter (input: 100-240 VAC, 0.48A Max., 50-60 Hz, output: 5.0 VDC, 3.0A Max.)
Power consumption (max.)	Nominal value: 5 W
Weight	Approx. 6.0kg (when equipped with binocular tube), approx. 6.4kg (when equipped with trinocular tube)
	n a simple polarizer is attached, only one filter can be installed *2 Used in combination with EC-T-TB2 Binocular Tube 2 or EC-T-TF2 Trinocular Tube F2

- 1 If the thickness is 2.5 mm or less. When a simple polarizer is attached, only one filter can be installed *2 Used in combination with EC-T-TB2 Binocular Tube 2 or EC-T-TF2 Trinocular Tube F2
- *3 Used in combination with C-TB Binocular Tube, C-TF/C-TT Trinocular Tubes or C-TE2 Ergonomic Binocular Tube
 *4 Cannot be used for dark-field observation
 *5 Observations other than brightfield require optional accessories.
 *6 Not for medical purposes
 *7 A C-OA 15mm adapter is required

Cooperation between pathological specimens and imaging guidance: Dr. Yasushi Nakamura, Pathologist, Osaka Cytopathological Laboratory

Digital Sight 1000 and DS-Fi3 microscope cameras, and NIS-Elements L imaging software are not for medical purposes. Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. July 2024 ©2024 NIKON CORPORATION



WARNING

TO ENSURE CORRECT USAGE, READ THE CORRESPONDING MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT.

Monitor images are simulated.

Company names and product names appearing in this brochure are their registered trademarks or trademarks.

N.B. Export of the products* in this brochure is controlled under the Japanese Foreign Exchange and Foreign Trade Law.

Appropriate export procedure shall be required in case of export from Japan. *Products: Hardware and its technical information (including software)







Nikon Healthcare Rusiness Unit website



NIKON CORPORATION

Head office

1-5-20, Nishioi, Shinagawa-ku, Tokyo 140-8601, Japan https://www.healthcare.nikon.com/en/

Manufacturer

471, Nagaodai-cho, Sakae-ku, Yokohama, Kanagawa 244-8533, Japan

Nikon Instruments Inc.

1300 Walt Whitman Road, Melville, N.Y. 11747-3064, U.S.A. phone: +1-631-547-8500; +1-800-52-NIKON (within the U.S.A. only) fax: +1-631-547-0299

https://www.microscope.healthcare.nikon.com/

Nikon Europe B.V.

Stroombaan 14, 1181 VX Amstelveen, The Netherlands phone: +31-20-7099-000

https://www.microscope.healthcare.nikon.com/en_EU/

Nikon Precision (Shanghai) Co., Ltd.

CHINA phone: +86-21-6841-2050 fax: +86-21-6841-2060 (Beijing branch) phone: +86-10-5831-2028 fax: +86-10-5831-2026 (Guangzhou branch) phone: +86-20-3882-0550 fax: +86-20-3882-0580 https://www.nikon-precision.com.cn/

Nikon Canada Inc.

CANADA phone: +1-905-625-9910 fax: +1-905-602-9953

Nikon France, Succursale de Nikon Europe B.V. FRANCE phone: +33-1-4516-4516

Nikon Deutschland, Zweigniederlassung der Nikon Europe B.V.

GERMANY phone: +49-211-9414-888

Nikon Italy, Branch of Nikon Europe B.V.

ITALY phone: +39-055-300-9601

Nikon Europe B.V., Amstelveen, Zweigniederlassung Schweiz (Egg/ZH)

SWITZERLAND phone: +41-43-277-2867

Nikon UK, Branch of Nikon Europe B.V. UNITED KINGDOM phone: +44-208-247-1717

Nikon Österreich, Zweigniederlassung der Nikon Europe B.V. AUSTRIA phone: +43-1-972-6111

Nikon Singapore Pte. Ltd.

SINGAPORE phone: +65-6559-3651 fax: +65-6559-3668

Nikon Australia Pty Ltd AUSTRALIA phone: +61-2-8767-6900

Nikon Instruments Korea Co., Ltd.

KOREA phone: +82-2-6288-1900 fax: +82-2-555-4415


NIKON INDIA PVT. LTD. INDIA phone: +91-124-4688-500





Microscope Camera Solutions

For Nikon Healthcare



INNOVATED FOR TOP BRAND MICROSCOPES

Create a Stunning Microscope Imaging System for You

For Trinocular Upright Microscopes









Solution ③

WiFi Camera

Function Comparison

● Standard ○ Optional - N/A

	Solution ₁	Solution2	Solution3
Built-in Android OS	•	•	_
Pre-installed Office suits	•	•	-
15.6"high color gamut monitor	•	_	_
Image output methods			
5G WiFi	•	•	•
USB	_	_	•
HDMI or DP	● DP	● DP	●HDMI
Network	_	_	•

Solution HDMI output method is unavailable for 20.0MP cameras.



Features & Benefits

5G WiFi and DP are simultaneous outputs



5G WiFi output

Compatible with various devices and operating systems, including Windows, iOS, and Android. Mobile devices can access the system by scanning a QR code. connects to PC via WiFi.





DP output

With DP output for display on monitors, Tvs and projectors.










Connecting to the Internet

The camera supports wireless Internet connection (only supports 5G WiFi router signal), by entering the password of any 5G WiFi network, you can directly open the browser to access the Internet. This will allow you to take advantage of online features and functionalities directly from your camera.





- Built-in operating system Android processor RK3399, MS office suit(Word, Excel, Powerpoint) are preinstalled, no need computer.
- 15.6" high-definition ISP display.
- Comes with an imaging app that displays live images upon startup.
- Includes a high-power 0.43X reduction lens for a wide field of view.
- 32GB built-in RAM with support for external U-disk storage for pictures and videos.
- USB interface allows for easy connection of keyboards and mouse.





1	Power switch	Switch on/off.
2	Headphone and microphone ports	Connect with headset cable for audio output.
3	Power input	DC 12V 3A
4	USB 3.0 interface	Can be connected to a mouse, keyboard, USB flash drive (for copying videos
(5)	USB 2.0 interface	and images).Or you can use the manufacturer's optional USB to DC5V power cord to power the Ei and Si.
6	DP output interface	Transmission via DP cable, connected to a display device.
7	USB 2.0 interface	Can be connected to a mouse, keyboard, USB flash drive (for copying videos and images).Or you can use the manufacturer's optional USB to DC5V power cord to power the Ei and Si.
8	5G WiFi antenna	The omnidirectional antenna provides a broad signal coverage, ensuring connectivity across a wide area. Its design supports up to 7 simultaneous connections, accommodating a variety of mobile devices including smart-phones, tablets, and laptops.
9	Easy focus with allen key (Only for 0.43X reduction lens camera)	Simple and precise focus adjustment for synchronization between eyepiece and monitor.

Specifications

15.6" high color gamut display

Number of pixels	1920(horizontal) x 1080 (vertical)
Pixels arrangement	RGB vertical stripe
Colour gamut	100% (sRGB)
Display number of colors	16.7M(8Bit)
Surface treatment	Anti-glare
Surface hardness	3H
Viewing angel range	170 horizontal, 170 vertical
Contrast	800
Brightness	500cd/m² (average of 5 points)

Applicable to	Nikon	Nikon				
Models	JX200	JX200				
C-mount category	D-C-12	D-C-20				
With 0.43X reduction lens category	D-N-12	D-N-20				
Physical resolution	12.0MP	20.0MP				
Image sensor	SONY IMX412 CMOS	SONY IMX147 CMOS				
Exposure mode	Rolling Shutter	Rolling Shutter				
Maximum resolution	4000×3000 (12,000,000Pixels)	5184×3888 (20,155,392 Pixels)				
ISO sensitivity	Equivalent to 100-12800	Equivalent to 100-12800				
Sensor size	1/2.3''	1/2.3"				
Pixel size	1.55μm×1.55μm	1.2μm×1.2μm				
Spectral response	380-650nm	380-650nm				
Exposure capability	Real-time auto and manual adjustment	Real-time auto and manual adjustment				
Exposure time	10μs-333ms	10μs-333ms				
White balance	Real-time auto and manual RB adjustment	Real-time auto and manual RB adjustment				
Preview resolution	4000×3000@30fps,3840×2160@30fps	5184×3888@10fps,3840×2160@15fps				
Power supply	DC 12V 3A	DC 12V 3A				
Wireless protocol	5G WiFi IEEE802.11ac	5G WiFi IEEE802.11ac				
A/D convertsion bit depth	12bit 12bit					
Software and App	Windows Software:KoPa Capture Pro,Embedded software:KoPa WiFi Lab AO,App:KoPa WiFi Lab					

Accessories

Power adapter and power cord (Optional Chinese, American, European, Australian, Korean, British standard etc.)






USB mouse and keyboard



Dimensions(Unit:mm)

Net weight ≈2kg

Camera with 0.43X adapter Camera with C-mount







Features & Benefits

5G WiFi and DP are simultaneous outputs



5G WiFi output

Compatible with various devices and operating systems, including Windows, iOS, and Android. Mobile devices can access the system by scanning a QR code. connects to PC via WiFi.





DP output

With DP output for display on monitors, Tvs and projectors.









Connecting to the Internet

The camera supports wireless Internet connection (only supports 5G WiFi router signal), by entering the password of any 5G WiFi network, you can directly open the browser to access the Internet. This will allow you to take advantage of online features and functionalities directly from your camera.





- Built-in operating system Android processor RK3399, MS office suit(Word,Excel, Powerpoint) are preinstalled, no need computer.
- Comes with an imaging app that displays live images upon startup.
- Includes a high-power 0.43X reduction lens for a wide field of view.
- 32GB built-in RAM with support for external U-disk storage for pictures and videos.
- USB interface allows for easy connection of keyboards and mouse.





1	5G WiFi antenna	The omnidirectional antenna provides a broad signal coverage, ensuring connectivity across a wide area. Its design supports up to 7 simultaneous connections, accommodating a variety of mobile devices including smartphones, tablets, and laptops.
2	USB 3.0 interface	
		Can be connected to a mouse, keyboard, USB flash drive (for copying videos
3	USB 2.0 interface	and images).Or you can use the manufacturer's optional USB to DC5V power cord to power the Ei and Si.
4	DP output interface	Transmission via DP cable, connected to a display device.
(5)	Easy focus with allen key (Only for 0.43X reduction lens camera)	Simple and precise focus adjustment for synchronization between eyepiece and monitor.
6	Power input	DC 12V 3A
7	Headphone and microphone ports	Connect with headset cable for audio output.
8	Power switch	Switch on/off.

Specifications

Applicable to	Nikon	Nikon				
Models	TE2000	TE2000				
C-mount category	C-C-12	C-C-20				
With 0.43X reduction lens category	C-N-12	C-N-20				
Physical resolution	12.0MP	20.0MP				
Image sensor	SONY IMX412 CMOS	SONY IMX147 CMOS				
Exposure mode	Rolling Shutter	Rolling Shutter				
Maximum resolution	4000×3000 (12,000,000Pixels)	5184×3888 (20,155,392 Pixels)				
ISO sensitivity	Equivalent to 100-12800	Equivalent to 100-12800				
Sensor size	1/2.3"	1/2.3''				
Pixel size	1.55μm×1.55μm	1.2μm×1.2μm				
Spectral response	380-650nm	380-650nm				
Exposure capability	Real-time auto and manual adjustment	Real-time auto and manual adjustment				
Exposure time	10μs-333ms	10μs-333ms				
White balance	Real-time auto and manual RB adjustment	Real-time auto and manual RB adjustment				
Preview resolution	4000×3000@30fps,3840×2160@30fps	5184×3888@10fps,3840×2160@15fps				
Power supply	DC 12V 3A	DC 12V 3A				
Wireless protocol	5G WiFi IEEE802.11ac	5G WiFi IEEE802.11ac				
A/D convertsion bit depth	12bit 12bit					
Software and App	Windows Software:KoPa Capture Pro,Embedded software:KoPa WiFi Lab AO,App:KoPa WiFi Lab					

Accessories

Power adapter and power cord (Optional Chinese, American, European, Australian, Korean, British standard etc.)





DP cable




USB mouse and keyboard







Net weight ≈1.3kg




Camera with 0.43X adapter



Camera with C-mount





Features & Benefits



5G WiFi output

Compatible with various devices and operating systems, including Windows, iOS, and Android. Mobile devices can access the system by scanning a QR code. Allows to connect to PC via.WiFi





USB output

Supports connection to a computer via USB 2.0. You can utilize the KoPa Capture Pro software or any standard UVC 2.0 protocol software to access the camera's real-time images without the need for driver installation.





HDMI output

With HDMI output for display on monitors, Tvs and projectors.




No software, only live images are available, at which point the camera image properties can be controlled via WiFi or USB.



Network output

Connect the camera to the router or switch through the network cable, up to 13 units computers, mobile phones and tablets in the LAN can access and control the images as long as they have installed the software and APP.









1	HDMI output interface (only 12.0MP camera)	The display device is connected and the image can be displayed, but the image cannot be controlled.
2	Network output interface	When WiFi is in gear: connect to a router or switch to access a LAN so that Windows computers, smartphones, and tablets on the LAN can share the microscopic screen; or connect to the Internet directly.
3	USB output/ power supply	Two in one: data transmission and power supply.
4	5G WiFi antenna	The omnidirectional antenna provides a broad signal coverage, ensuring connectivity across a wide area. Its design supports up to 7 simultaneous connections, accommodating a variety of mobile devices including smartphones, tablets, and laptops.
(5)	Easy focus with allen key (Only for 0.43X reduction lens camera)	Simple and precise focus adjustment for synchronization between eyepiece and monitor.
6	USB/OFF/Network working mode switching	Two working modes switching

Specifications

Applicable to	Nikon	Nikon					
Models	CF48	CF48					
C-mount category	B-C-12	B-C-20					
With 0.43X reduction lens category	B-N-12	B-N-20					
Physical resolution	12.0MP	20.0MP					
Image sensor	SONY IMX412 CMOS	SONY IMX147 CMOS					
Exposure mode	Rolling Shutter	Rolling Shutter					
Maximum resolution	4000×3000 (12,000,000Pixels)	5184×3888 (20,155,392 Pixels)					
ISO sensitivity	Equivalent to 100-12800	Equivalent to 100-12800					
Sensor size	1/2.3"	1/2.3''					
Pixel size	1.55μm×1.55μm	1.2μm×1.2μm					
Spectral response	380-650nm	380-650nm					
Exposure capability	Real-time auto and manual adjustment	Real-time auto and manual adjustment					
Exposure time	10µs-333ms	10μs-333ms					
White balance	Real-time auto and manual RB adjustment	Real-time auto and manual RB adjustment					
Preview resolution	4000×3000@30fps,3840×2160@30fps	5184×3888@10fps,3840×2160@15fps					
Power supply	DC 5V 3A	DC 5V 3A					
Wireless protocol	5G WiFi IEEE802.11ac	5G WiFi IEEE802.11ac					
A/D convertsion bit depth	12bit	12bit					
Software and App	Windows Software:KoPa Capture Pro, App:KoPa WiFi Lab						

Accessories

HDMI cable(optional, 2m only for 12.0MP camera)




Gigabit ethernet cable (optional, 2m)




Dimensions(Unit:mm)


Net weight ≈1kg;



Camera with 0.43X adapter



Camera with C-mount









Microscope objectives

Our objectives help you

Nikon's first microscope, released in 1925

focus on yours

Nikon is a leader in the development and manufacture of optical and digital imaging technology for advanced science and clinical research. With over a 100-year history of optical excellence, Nikon is committed to accelerating innovation in science and clinical imaging to improve healthcare and provide a better quality of life.

The switch from traditional film photography to digital imaging was a major milestone in the field of microscopy, opening up new possibilities in both application and technology. Introduction of digital imaging spurred significant technological changes including the development of objectives with enhanced optical quality and functionality to meet the new demands. Objective lenses are arguably the most important element in the microscope and Nikon continues to invest heavily in the development of objectives to meet the changing demands of science. Explore some of Nikon's newest developments in high-performance objectives in this brochure.






It Starts with the Glass

Nikon has been developing optical glass since its inception in 1917, and to this day, wholly owns and formulates all of its glass.

Optical glass starts as an ingot (shown on right) which is formed by blending rare earth elements and repeated melting, shaping and slow cooling to achieve a target refractive index. The glass ingots are precision-cut, polished and coated to produce lens elements for the objective.





Mastering Excellence

The front lens of high-performance objectives is hand-polished by Nikon's most highly skilled experts (shown on left), a technique requiring more than a decade to master.

By controlling the entire manufacturing process from glass formulation to assembly and alignment of lens elements, Nikon ensures the highest quality and performance of its objectives.


Objectives Inspired by Your Science

Produced to exacting standards, Nikon's objectives provide exceptional detail and clarity. The highest level of image quality can be achieved whether it be for routine tasks or cutting-edge research.

Anti-Reflective Nano Crystal Coat

Nano Crystal Coat is ultra-low refractive index thin film technology that applies a nanoparticle film used for the projection lens of Nikon's semiconductor manufacturing equipment. An extremely high antireflection effect is achieved by forming a low-density film with particles of a few nanometers to a dozen nanometers. It also lowers the reflection of vertically incident light compared to conventional antireflection film, achieves extremely high transmittance in a wide wavelength range, has an unprecedented effect with respect to ghosting and flares caused by obliquely incident light.







Cleared Tissue Imaging




CFI90 20XC Glyc

Designed for deep imaging of cleared tissues

The unique CFI90 design results in an incredibly high N.A. while maintaining a large field of view and ultra-long working distance. Incorporates a correction collar for compensating for different refractive indices of clearing agents.

- NA: 1.00, WD: 8.20 mm
- Chromatic aberration correction from the visible to IR range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction



Cleared Tissue Imaging



CFI Plan Apochromat 10XC Glyc

Compatible with a wide range of immersion media and clearing agents

In addition to water and immersion oil, this objective lens is compatible with a variety of tissue clearing agents. The lens also features chromatic aberration correction over a broad spectral range and is compatible with the Ti2 inverted microscope.

- NA: 0.50, WD: 5.50 mm (upright) / 2.00 mm (inverted)
- Chromatic aberration correction from the visible to IR range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction



Multiphoton Imaging




CFI75 Apochromat 25XC W 1300

Developed for deep brain applications

Best in class objective for multiphoton and electrophysiology applications. Offers ultra-long working distance and incredibly high N.A. for exceptional results every time.

- NA: 1.10, WD: 2.00 mm
- Chromatic aberration correction from the visible to near IR range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction



Zebrafish larva

Multiphoton Imaging




CFI75 Apochromat LWD 20XC W

Objective for large FOV multiphoton imaging

This objective can acquire bright multiphoton confocal images up to the edge of a large field of view of 22 mm. With a long working distance of 2.8 mm and a high numerical aperture of 1.00, it enables clear observation to deep within *in vivo* samples.

- NA: 1.00, WD: 2.8 mm
- Chromatic aberration correction from the visible to near IR range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction



Confocal Imaging



CFI Apochromat LWD Lambda S 20XC WI

A versatile objective for a wide range of applications

Combines high N.A., long working distance and large field of view for imaging thick, live samples. Chromatic aberration correction from visible to IR for multiphoton imaging as well.

- NA: 0.95, WD: 0.95 mm
- Chromatic aberration correction from the visible to IR range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction



Image courtesy of: Dr. L. Dubreil, Dr. J. Pichon and Pr MA Colle, CENN at PAnTher UMR703 INRAE/Oniris, Nantes France

Partner UMR/03 INRAE/Oniris, Nantes France

Confocal Imaging





CFI Plan Apochromat Lambda S 25XC/40XC Sil

High-resolution objectives for observing thick specimens

Silicone oil closely matches the refractive index of live cells, thereby minimizing spherical aberration and providing brighter, higher-resolution images. Unlike water, silicone oil demonstrates minimal evaporation at 37°C, thereby enabling extended, long-term time-lapse imaging experiments.

- NA: 1.05 (25XC)/1.25 (40XC), WD: 0.55 mm (25XC)/0.30 mm (40XC)
- Chromatic aberration correction in the visible range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction

100 µm Normal mouse embryos HeLa cell

Confocal Imaging



CFI Plan Apochromat IR 60XC WI

Incredible resolution and field flatness

This objective provides an NA of 1.27, the highest among 60X water immersion objectives, and achieves incredible field flatness. Corrects for chromatic aberration over a wide wavelength range up to IR, and supports various applications including multicolor live-cell confocal imaging, multiphoton imaging and laser tweezer applications.

- NA: 1.27, WD: 0.17 mm
- Chromatic aberration correction from the visible to IR range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction




Image of mouse embryo courtesy of: Dr. Yoshiteru Kai, Shonan Yume Clinic, Yamashita

Super-Resolution Imaging




CFI SR HP Plan Apochromat Lambda S 100XC Sil

High-resolution silicone oil immersion objective for imaging live samples

Silicone oil more closely matches the refractive index of live cells compared to water or oil, thereby minimizing spherical aberration issues common to live cell imaging. In addition, the 100XC Sil lens achieves exceptional resolving power even at greater depths, making it well-suited for superresolution imaging of thicker specimen.

- NA: 1.35, WD: 0.30 mm
- Chromatic aberration correction in the visible range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction



Super-Resolution Imaging




Auto Correction Collar

Quick and accurate spherical aberration correction

Achieving the highest quality point spread function is critical for super-resolution imaging. The ACC quickly moves lens elements in the objective to an optimal position based on the acquired point spread function to minimize spherical aberration.





Dendrites

High-Content Imaging




CFI S Plan Fluor LWD ADM 20XC

High NA and long WD objective designed for HC applications

This objective is compatible with thick plastic-bottom dishes and well-plates, and enables high-resolution phase-contrast and fluorescence observations. Its large FOV improves throughput of high-content applications.

- NA: 0.70, WD: 2.30-1.30 mm
- Chromatic aberration correction in the visible range
- Correction collar for spherical aberration correction



Pathological Examination



CFI Plan Apochromat Lambda D 40XC

Large field-of-view imaging with uniform brightness

This objective achieves uniform brightness up to the edge of the field of view, chromatic aberration correction from 405 nm upward, and improved resolution. The 25 mm field of view allows you to capture images of a large area of the sample, improving throughput.

- NA: 0.95, WD: 0.21 mm
- Chromatic aberration correction from the visible to near IR range
- High-transmittance Nano Crystal Coat
- Correction collar for spherical aberration correction




Image courtesy of: Nichirei Biosciences Inc.

A tool for finding the right objective

Nikon's online Objective Selector tool enables you to quickly and easily find the right objective for your application. Refine your search based on application, technique, objective class, immersion type, etc. Specifications for multiple objectives can be displayed in a single window for easy comparison.

https://www.microscope.healthcare.nikon.com/selectors/objectives



OBJECTIVE SELECTOR

For OEM and DIY


With over 100 years of experience in developing optical technology, Nikon offers a wide range of components that can fulfill almost any optical requirement.

Nikon develops products to the highest standards, from design to manufacture, to ensure we meet the needs of a wide variety of customers.

For detailed specifications including dimensions and transmission information, please refer to the following website.

https://www.microscope.healthcare.nikon.com/products/oem





As individual as you

Nikon offers a broad portfolio of objectives to meet your individual application needs. Explore some of the different objective series in the following pages.



CFI Plan Apochromat Lambda D series

Outstanding image flatness and high resolution provide uniform image quality up to the edge of a large field of view of 25 mm, improving efficiency in image tiling and high content screening. Chromatic aberration has been corrected over a wide wavelength range from 405 nm to 850 nm, enabling highly accurate multicolor



CFI Plan Apochromat Lambda D 2X, 4X, 10X, 20X, 40XC, 60X Oil and 100X Oil

Silicone immersion objectives

Silicone oil closely matches the refractive index (RI) of living cells and tissues, allowing deep observations with minimal optical aberrations. Silicone immersion objectives enable clear observation with a high signal-to-noise ratio deep into living tissue, and facilitate ease of observation with their large fields of view, high resolution, and evaporation-resistant oil.



CFI Plan Apochromat Lambda S 25XC Sil, CFI Plan Apochromat Lambda S 40XC Sil, CFI Plan Apochromat Lambda S 60XC Sil

Use	Madal	NIA	W.D. (mm)	0	Consideration of the second	Delekteda	Darkfield	DIC	Dhara andward	Delevisione		Fluorescence		T:0 F DE0
Use	Model	NA	W.D. (mm)	Cover glass thickness	Spring loaded	Brightfield	Darkileid	DIC	Phase contrast	Polarizing	UV	Visible light	NIR	Ti2-E PFS
	Lambda D 2X	0.10	8.50	0/0.17		0					O CF	0	0	
	Lambda D 4X	0.20	20.00	0/0.17		0					0	0	0	•
	Lambda D 10X	0.45	4.00	0.17		0	\triangle	0		•	0	0	0	•
	Lambda D 20X	0.80	0.80	0.17	1	0	•	0		•	0	0	0	•
	Lambda D 40XC	0.95	0.21	0.11-0.23	1	0	•	0		•	© CF	0	0	•
	Lambda D 60X Oil	1.42	0.15	0.17	1	0		0	EXT PH3-60x	•	0	0	0	•
Brightfield (CFI Plan Apo)	Lambda D 100X Oil	1.45	0.13	0.17	1	0		0	EXT PH4-100x*	•	0	0	0	•
	Lambda S 25XC Sil	1.05	0.55	0.11-0.23		0	•	0			•	0		•
	Lambda S 40XC Sil	1.25	0.30	0.13-0.21 (23°C) 0.15-0.23 (37°C)		0	•	0			•	0		•
	Lambda S 60XC Sil	1.30	0.30	0.15-0.19		0		0			•	0	0	•
	IR 60XC WI	1.27	0.18-0.16	0.15-0.19	✓	0		0	EXT PH3-60x	0	•	0	0	•
	NCG 100X Oil	1.40	0.16	0	✓	0		0		0	•	0		

^{*} An optical path length difference correction block is required.

Glossary C: with correction collar Oil: oil immersion WI: water immersion

W: water dipping Mi: multi immersion Glyc: glycerin immersion Sil: silicone oil immersion Cover glass thickness - : can be used without cover glass

0: use without cover glass

Possible with the following ∴ : universal condenser (dry) and darkfield ring

: above and darkfield condenser (dry) : darkfield condenser (oil)

Phase rings
PHL, PH1, PH2, PH3: condenser cassette modules.
EXT PH3, EXT PH4: external phase contrast modules for Ti2-E.

Fluorescence (UV)

: possible with visible light that has a longer wavelength than the excitation light used for DAPI

: recommended for best results

340: high transmittance with an ultraviolet wavelength range of

CF: confocal imaging is possible at 488 nm and above

Brightfield/DIC/Polarizing/Fluorescence (visible light)

■ : possible but not recommended

: recommended for best results

: compatible with PFS

CFI Plan Apochromat VC

With its high degree of chromatic aberration correction and exceptional resolving power, the CFI Plan Apochromat VC 60XC WI is the perfect choice for multi-color fluorescence imaging as well as brightfield and DIC applications. In particular, axial chromatic aberration has been corrected in the short wavelength range, making this objective highly effective for confocal applications.



CFI Plan Apochromat VC 60XC WI

CFI SR series/CFI HP series/CFI SR HP series

Strict adjustment and inspection minimize the SR objective's asymmetric aberration, optimizing it for super-resolution microscopy. The HP objective has improved axial chromatic aberration correction and is compatible with the high-power lasers required for the fast blinks of fluorophores under super-resolution microscopy. The SR HP objective offers both excellent optical performance and high durability against high power laser excitation. AC objectives support the Auto Correction function of the Ti2-E inverted microscope.



CFI SR Plan Apochromat IR 60XC WI, CFI HP Plan Apochromat VC 100X Oil, CFI SR HP Apochromat TIRF 100XC Oil and CFI SR HP Plan Apochromat Lambda S 100XC Sil

Use	Model	NA	W.D. (mm)	Cover glass thickness	Spring loaded	Brightfield	Darkfield	DIC	Phase contrast	Polarizing	Fluorescence			Ti2-E PFS
	Model	INA	W.D. (IIIII)	Cover glass trickness	Spring loaded	Brightheid		DIC		Polarizing	UV	Visible light	NR	112-E PF3
Brightfield (CFI Plan Apo)	VC 60XC WI	1.20	0.31-0.28	0.15-0.18	1	0		0	EXT PH3-60X	0	0	0		•
Super-resolution (CFI SR Plan Apo)	IR 60XC WI	1.27	0.18-0.16	0.15-0.19		0		0	EXT PH3-60X	0	0	0	0	•
	IR 60XAC WI	1.27	0.18-0.16	0.15-0.19		0		0	EXT PH3-60X	0	0	0	0	•
Super-resolution (CFI HP Plan Apo)	VC 100X Oil	1.40	0.13	0.17	✓	0		0	EXT PH3-100X	0	•	0		•
Super-resolution (CFI SR HP Plan Apo)	Lambda S 100XC Sil	1.35	0.31-0.29 (23°C) 0.30-0.28 (37°C)	0.15-0.19		0		0		0	0	0		•
Super-resolution (CFI SR HP Apo)	TIRF 100XC Oil	1.49	0.16-0.10 (23°C) 0.15-0.09 (37°C)	0.13-0.19 (23°C) 0.14-0.20 (37°C)		0		0	EXT PH4-100X	0	•	0		•
	TIRF 100XAC Oil	1.49	0.16-0.10 (23°C) 0.15-0.09 (37°C)	0.13-0.19 (23°C) 0.14-0.20 (37°C)		0		0	EXT PH4-100X	0	•	0		•

CFI Apochromat Lambda S series

These high-numerical-aperture (NA) objectives provide chromatic aberration correction over wavelengths ranging from violet to near-infrared and are ideal for multicolor confocal imaging. The LWD Lambda S 20XC WI lens has a chromatic aberration correction range up to infrared. The transmittance of these lenses is enhanced over a wide wavelength range by utilizing Nano Crystal Coat technology.



CFI Apochromat Lambda S 40XC WI and CFI Apochromat LWD Lambda S 20XC WI/40XC WI

CFI Apochromat TIRF series

These objectives boast an unprecedented NA of 1.49 (using a standard coverslip and immersion oil), the highest resolution among Nikon objectives. Correction collars enable optimization of point spread functions for varying imaging temperatures, correcting spherical aberration when imaging at 23 and 37 degrees Celsius.



CFI Apochromat TIRF 60XC Oil and 100XC Oil

Multiphoton confocal objectives

These objectives are optimized for deep tissue imaging using a multiphoton confocal microscope, thanks to their ability to correct chromatic aberration up to near-IR range.

They provide both long WD and high NA, as well as high transmittance. The Glyc models have a correction collar for the refraction index of immersion liquids, and are compatible with various tissue clearing reagents that are used in neuroscience research.



CFI Plan Apochromat 10XC Glyc, CFI90 20XC Glyc, CFI75 Apochromat LWD 20XC W and 25XC W 1300

Use	Model	NA	W.D. (mm)	Cover glass thickness	Spring loaded	Brightfield	Darkfield	DIC	Phase contrast	Polarizing	Fluorescence			Ti2-E PFS
USE	iviouei	INA	VV.D. (IIIII)		Opring loaded	Drigitaliola	Darkileiu	DIC	Filase Contrast	Fularizing	UV	Visible light	NIR	112-2113
Confocal (CFI Apo)	LWD Lambda S 20XC WI	0.95	0.99-0.90	0.11-0.23		0	•	0		0		0	0	•
	LWD Lambda S 40XC WI	1.15	0.61-0.59	0.15-0.19		0	•	0	EXT PH3-40X	0	0	0		•
	Lambda S 40XC WI	1.25	0.20-0.16	0.15-0.19	✓	0		0	EXT PH3-40X	0	0	0		•
	TIRF 60XC Oil	1.49	0.16-0.10 (23°C) 0.13-0.07 (37°C)	0.13-0.19 (23°C) 0.15-0.21 (37°C)		0		0	EXT PH4-60X	0	•	0		•
Evanescent (CFI Apo)	TIRF 100XC Oil	1.49	0.16-0.10 (23°C) 0.15-0.09 (37°C)	0.13-0.19 (23°C) 0.14-0.20 (37°C)		0		0	EXT PH4-100X	0	•	0		•
Multiphoton confocal (CFI Plan Apo)	10XC Glyc	0.50	Upright: 5.50 Inverted: 2.00	0-0.17		0	0					0	0	
Multiphoton confocal (CFI90)	20XC Glyc*	1.00	8.20	0		• ***							0	
	LWD 20XC W**	1.00	2.8	0-0.17		0					•	0	0	
Multiphoton confocal (CFI75 Apo)	25XC W*	1.10	2.00	0		0	•	0 ****		0	0	0	0	
	25XC W 1300*	1.10	2.00	0		0	•	0 ****		0	0	0	0	

^{*} Dedicated for FN1 and Ni-E focusing nosepiece type

^{**} Dedicated for AX R MP multiphoton confocal system
*** Can only be used as a finder (chromatic aberration is corrected above 588 nm)

^{****} Also compatible with near-infrared DIC

CFI Plan Fluor series

Featuring a high transmission rate, especially in the ultraviolet wavelength, and flatness of field, this series is designed for fluorescence observation and imaging. These objectives can function as multipurpose objectives for brightfield, fluorescence, simple polarizing, and DIC observations.







CFI Plan Fluor DLL 10X, 20X, 40X and 100X Oil

CFI Super Fluor series

This CFI Super Fluor series ensures an extra-high transmission rate of ultraviolet wavelengths down to 340nm for fluorochromes like indo-1 and fura-2. Also, these objectives have improved S/N ratios for short wavelengths and have high NA, making the fluorescence images they produce significantly sharper and brighter.



CFI Super Fluor 10X, 20X, 40XC and 40X Oil

Use	Model	NA	W.D. (mm)	Cover glass thickness	Spring loaded	Brightfield	Darkfield	DIC	Phase contrast	Polarizing		orescence	Ti2-E PF
930	Wiodei	1.0	W.D. (IIIII)	Cover glass thorness	Opining loaded		Barkileia	510	i nasc contrast	1 Oldrizing	UV	Visible light	
	4X	0.13	17.20	-		0				•	0	0	
	10X	0.30	16.00	0.17		0	\triangle	0		0	0	0	•
	20X	0.50	2.10	0.17		0	0	0		0	0	0	
	20XC MI	0.75	0.51-0.35 (oil) 0.51-0.34 (glycerin) 0.49-0.33 (water)	0-0.17	✓	0	0	0		0	0	0	
ightfield (CFI Plan Fluor)	40X	0.75	0.66	0.17	✓	0	$\circ \bullet$	0		0	0	0	•
	40X Oil	1.30	0.24	0.17	✓	0		0	EXT PH3-40X	0	0	0	•
	60XC	0.85	0.40-0.31	0.11-0.23	/	0	•	0		0	0	0	
	60XS Oil	0.50-1.25	0.22	0.17	✓	0	0	0	EXT PH3-60X	0	0	0	
	100X Oil	1.30	0.16	0.17	✓	0		0		0	0	0	•
	100XS Oil	0.50-1.30	0.16	0.17	1	0	0	0		0	0	0	
	DL 4XF	0.13	16.50	1.20		0			O PHL		0	0	
	DLL 10X	0.30	16.00	0.17		0	\triangle		© PH1		0	0	•
	DL 10XF	0.30	15.20	1.20		0	\triangle		© PH1		0	0	•
(25) 5)	DLL 20X	0.50	2.10	0.17		0	0		© PH1		0	0	•
nase contrast (CFI Plan Fluor)	DLL 40X	0.75	0.66	0.17	✓	0	\circ		© PH2		0	0	•
	DLL 100X Oil	1.30	0.16	0.17	1	0			© PH3		0	0	•
	DM 40X	0.75	0.66	0.17	✓	0	\circ		© PH2		0	0	
	BM 40X	0.75	0.66	0.17	✓	0	$\circ \bullet$		© PH2		0	0	
podized phase contrast (CFI Plan Fluor)	ADH 100X Oil	1.30	0.16	0.17	✓	0			© PH3		0	0	•
	4X	0.20	15.50	_		0				•	◎ 340	0	•
	10X	0.50	1.10	0.17	1	0	0	0		•	◎ 340	0	•
	20X	0.75	1.00	0.17	1	0	0	0		•	◎ 340	0	•
ghtfield (CFI Super Fluor)	40XC	0.90	0.34-0.26	0.11-0.23	/	0	•	0		•	◎ 340	0	
	40X Oil	1.30	0.19	0.17	/	0		0		•	◎ 340	0	•
	100XS Oil	0.50-1.30	0.20	0.17	1	0	0			•	© 340	0	

CFI S Plan Fluor series

The broadband multilayer coating realizes high transmittance from ultraviolet to near-infrared wavelengths, with superior chromatic correction. The correction collar allows these objectives to be used with a diverse range of culture vessels and specimen thicknesses. High-quality images with no aberrations can be obtained under a broad range of illumination techniques.



CFI S Plan Fluor LWD 20XC and LWD ADM 20XC



CFI S Plan Fluor ELWD 20XC, 40XC and 60XC



CFI S Plan Fluor ELWD ADM 20XC, 40XC and ADL 60XC

Nikon Advanced Modulation Contrast (NAMC) series

Nikon has developed dedicated objectives for advanced modulation contrast. Colorless and transparent samples can be observed in high relief with a plastic dish, which is not possible in DIC observation. The direction of contrast can be matched to S Plan Fluor ELWD NAMC objectives, thereby allowing optimal contrast selection for techniques like microinjection and ICSI.





Use	Model	NA	W.D. (mm)	Cover glass thickness	Spring loaded	Brightfield	Darkfield	DIC	Phase	Polarizing	Fluorescence		Ti2-E PFS
Use	Model	INA	VV.D. (IIIIII)	Cover glass trickness	Spring loaded	brightheid		DIC	contrast	Polarizing	UV	Visible light	112-E PF3
	LWD 20XC	0.70	2.30-1.30	0-1.80		0	0	0		0	0	0	•
British (OFLO Blass Floor)	ELWD 20XC	0.45	8.20-6.90	0-2.00		0	0	0		0	0	0	•
Brightfield (CFI S Plan Fluor)	ELWD 40XC	0.60	3.60-2.80	0-2.00		0	$\bigcirc lacktriangle$	0		0	0	0	•
	ELWD 60XC	0.70	2.60-1.80	0.10-1.30		0	0	0		0	0	0	
	LWD ADM 20XC	0.70	2.30-1.30	0-1.80		0	0		© PH2		0	0	•
Apodized phase contrast	ELWD ADM 20XC	0.45	8.20-6.90	0-2.00		0	0		© PH1		0	0	•
(CFI S Plan Fluor)	ELWD ADM 40XC	0.60	3.60-2.80	0-2.00		0	$\bigcirc lacktriangle$		© PH2		0	0	•
	ELWD ADL 60XC	0.70	2.60-1.80	0.10-1.30		0	$\bigcirc lacktriangle$		© PH2		0	0	
Advanced modulation contrast	ELWD NAMC 20XC	0.45	8.20-6.90	0-2.00		0					0	0	
(CFI S Plan Fluor)	ELWD NAMC 40XC	0.60	3.60-2.80	0-2.00		0					0	0	
Advanced modulation contrast (CFI)	NAMC 10XF	0.25	6.20	1.20		0						•	
	LWD NAMC 20XF	0.40	3.10	1.20		0						•	
	LWD NAMC 40XC	0.55	2.70-1.70	0-2.00		0						•	

CFI Plan Achromat series

CFI Plan Achromat series provides incredible image flatness, with chromatic aberration corrected throughout the entire visible spectrum. These objectives are suitable not only for observation but also for capturing images.



CFI Plan 1X, 2X, 4X, 10X, 20X, 40X and 100X Oil



CFI Plan DL 10X, 20X, 40X and 100X Oil

Water Dipping Series

Sharper tips and broad approach angles provide improved accessibility for manipulator control. Aberrations are corrected even in the infrared range for high-magnification objectives, making them suitable for multi-photon imaging using infrared light.



CFI Plan Fluor 10XW, CFI75 LWD 16XW, CFI Apochromat NIR 40XW/60XW and CFI Plan 100XC W

Use	Model	NA	W.D. (mm)	Cover glass thickness	Spring loaded	Brightfield	Darkfield	DIC	Phase	Polarizing	Fluorescence		Near- infrared DIC
Use	Model	I NA	W.D. (IIIII)	Cover glass trickness	Spring loaded	brightheid	Darkileid	DIC	contrast	Polarizing	UV	Visible light	Near-Illiared Dio
	1X	0.04	3.20	_		0				•		•	
	2X	0.06	7.50	_		0				•		•	
	4X	0.10	30.00	_		0				•		0	
	10X	0.25	10.50	-		<u>©</u>				•		0	
Brightfield (CFI Plan)	20X	0.40	1.20	0.17			$\bigcirc \bullet$					\circ	
Brightileio (GFI Plan)	40X	0.65	0.56	0.17	✓	0	$\bigcirc lacktriangle$			•		0	
	50X Oil	0.90	0.35/0.18	-/0.17	✓	0	•			•		0	
	100X Oil	1.25	0.20	0.17	✓	0				•		0	
	NCG 40X	0.65	0.48	0	✓		$\bigcirc lacktriangle$			•		0	
	NCG 100X	0.90	1.00	0	✓	0	•			•		0	
	DL 10X	0.25	10.50	_		0	\triangle		© PH1	•		•	
Phase contrast (CFI Plan)	DL 20X	0.40	1.20	0.17		0	$\bigcirc lacktriangle$		© PH1	•		•	
Phase contrast (CFI Plan)	DL 40X	0.65	0.56	0.17	✓	0	$\bigcirc lacktriangle$		O PH2	•		•	
	DL 100X Oil	1.25	0.20	0.17	✓	0			© PH3	•		•	
DIC (CFI Plan Fluor)	10X W	0.30	3.50	0			\triangle	0		0	0	0	0
ID DIC (CEL Ann)	NIR 40X W	0.80	3.50	0		0	•	0		0	•	0	0
IR-DIC (CFI Apo)	NIR 60X W	1.00	2.80	0		0	•	0		0		0	0
DIC (CFI Plan)	100XC W	1.10	2.50	0		0	•	0		0		0	0
DIC (CFI75)	LWD 16X W *	0.80	3.00	0		0	•	0		0	0	0	0

* Dedicated for FN1 and Ni-E focusing nosepiece type

CFI Achromat series

This series of objectives provide dramatic correction for chromatic aberration, spherical aberration and coma. Image flatness is significantly improved.

Nikon specifically developed ADL series for phase contrast observations by using its proprietary apodization process to improve the objective's phase ring. Imaging cell division is often impeded by unwanted halos due to the sample thickness. ADL mitigates this effect for clearer observation of mitotic events.



CFI 4X and 10X, CFI LWD 20X, CFI 40X, CFI NCG 60X and CFI 100X Oil CFI DL 10X, CFI LWD DL 20X, CFI DL 40X and 100X Oil





CFI ADL 10XF, CFI LWD ADL 20XF, 40XF and 40XC

Use	Model	NA	W.D. (mm)	Cover glass thickness	Spring loaded	Brightfield	Darkfield	DIC	Phase contrast	Polarizing	Fluorescence UV Visible light	Ti2-E PFS
	4X	0.10	30.00			0				•	O	
	10X	0.25	7.00	<u>=</u>		<u></u>				•	O	
	LWD 20X	0.40	3.90	0.17		0	$\bigcirc lacktriangle$			•	0	
	40X	0.65	0.65	0.17	<mark>✓</mark>	0	$\bigcirc left$			•	O	
Brightfield (CFI)	LWD 40XC	0.55	2.70-1.70	0-2.00		0	$\bigcirc lacktriangle$			•	0	
	60X	0.80	0.30	0.17	<mark>✓</mark>	0	•			•	O	
	NCG 60X	0.80	0.30	0.17	1	0	0			•	0	
	100X Oil	1.25	0.23	0.17	✓	0				•	0	
	100XS Oil	0.50-1.25	0.23	0.17	✓	0	$\circ \bullet$			•	0	
	DL 10X	0.25	7.00	-		0	\triangle		© PH1	•	•	
	LWD DL 20X	0.40	3.90	0.17		0	$\bigcirc lacktriangle$		© PH1	•	•	
	LWD DL 20XF	0.40	3.10	1.20		0			© PH1	•	•	
Phase contrast (CFI)	DL 40X	0.65	0.65	0.17	1	0	$\bigcirc lacktriangle$		© PH2	•	•	
	LWD DL 40XC	0.55	2.70-1.70	0-2.00		0	0		© PH2	•	•	
	DL 100X Oil	1.25	0.23	0.17	1	0			© PH3	•	•	
	BM 10X	0.25	7.00	0.70		0			© PH1	•	•	
	ADL 10XF	0.25	6.20	1.20		0			⊚ PH1	•	•	
	LWD ADL 20XF	0.40	3.10	1.20		0			⊚ PH1	•	•	
Apodized phase contrast (CFI)	LWD ADL 40XF	0.55	2.10	1.20		0			© PH1	•	•	
	LWD ADL 40XC	0.55	2.70-1.70	0-2.00		0	0		© PH2	•	•	

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. July 2024



Optics product page

/ WARNING

© 2024 NIKON CORPORATION

TO ENSURE CORRECT USAGE, READ THE CORRESPONDING MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT.

Company names and product names appearing in this brochure are their registered trademarks or trademarks. N.B. Export of the products* in this brochure is controlled under the Japanese Foreign Exchange and Foreign Trade Law. Appropriate export procedure shall be required in case of export from Japan. *Products: Hardware and its technical information (including software)

















NIKON CORPORATION

Head office https://www.healthcare.nikon.com/en/

Manufacturer

1-5-20, Nishioi, Shinagawa-ku, Tokyo 140-8601, Japan 471, Nagaodai-cho, Sakae-ku, Yokohama, Kanagawa 244-8533, Japan

Nikon Instruments Inc.

1300 Walt Whitman Road, Melville, N.Y. 11747-3064, U.S.A. phone: +1-631-547-8500; +1-800-52-NIKON (within the U.S.A. only) fax: +1-631-547-0299

https://www.microscope.healthcare.nikon.com/

Nikon Europe B.V.

Stroombaan 14, 1181 VX Amstelveen, The Netherlands phone: +31-20-7099-000

https://www.microscope.healthcare.nikon.com/en_EU/

Nikon Precision (Shanghai) Co., Ltd.

CHINA phone: +86-21-6841-2050 fax: +86-21-6841-2060 (Beijing branch) phone: +86-10-5831-2028 fax: +86-10-5831-2026 (Guangzhou branch) phone: +86-20-3882-0550 fax: +86-20-3882-0580

https://www.nikon-precision.com.cn/

Nikon Canada Inc.

CANADA phone: +1-905-625-9910 fax: +1-905-602-9953

Nikon France, Succursale de Nikon Europe B.V.

FRANCE phone: +33-1-4516-4516

Nikon Deutschland, Zweigniederlassung der Nikon Europe B.V.

GERMANY phone: +49-211-9414-888

Nikon Italy, Branch of Nikon Europe B.V.

ITALY phone: +39-055-300-9601

Nikon Europe B.V., Amstelveen, Zweigniederlassung Schweiz (Egg/ZH)

SWITZERLAND phone: +41-43-277-2867

Nikon UK, Branch of Nikon Europe B.V.

UNITED KINGDOM phone: +44-208-247-1717

Nikon Österreich, Zweigniederlassung der Nikon Europe B.V.

AUSTRIA phone: +43-1-972-6111

Nikon Singapore Pte. Ltd.

SINGAPORE phone: +65-6559-3651 fax: +65-6559-3668

Nikon Australia Pty Ltd

AUSTRALIA phone: +61-2-8767-6900

Nikon Instruments Korea Co., Ltd.

KOREA phone: +82-2-6288-1900 fax: +82-2-555-4415

Nikon India Private Limited

INDIA phone: +91-124-4688-500



Nikon EU Declaration of Conformity

This European Declaration of Conformity is issued under the sole responsibility of the manufacturer.

MANUFACTURER		
Name of Company	Address	SRN
Nikon Corporation	471, Nagaodai-cho, Sakae-ku, Yokohama, Kanagawa	JP-MF-000029301
	244-8533 Japan	

AUTHORIZED REPRESENTATIVE									
Name of Company	Address	SRN	Telephone/Email						
Nikon Europe B.V.	Stroombaan 14, 1181 VX Amstelveen,	NL-AR-000028107	+31-20-7099-000						
	The Netherlands		MDR.eu@nikon.com						

PRODUCT IDENTIFICATION								
Product / Trade Name	Product Code	Basic UDI-DI						
ECLIPSE Si RS	MCA77200	4549921AA000MQ						
Intended Purpose								
This microscope and accessories are optical instruments used to enlarge images of specimens, preparations,								
and cultures for medical purposes.								

IVDR RISK CLASS / STANDARDS / COMMON SPECIFICATIONS								
Device Classific	ation	Standards	Common Specifications					
Class	Α	EN 61010-1:2010/A1:2019/AC:2019-04	N/A					
		EN 61010-2-101:2017						
		EN 62366-1:2015						
		EN 62304:2006						
		EN 62471:2008						
Rule	5	EN 61326-1:2013						
		EN 61326-2-6:2013						
		EN IEC 63000:2018						
		EN ISO 14971:2012						
		EN ISO 13485:2016						

Nikon Corporation declares that the above-mentioned products meet the provision of the following EU legislation:

- In Vitro Diagnostic Medical Device Regulation (IVDR) (EU) 2017/746
- RoHS Directive (2011/65/EU, 2015/863/EU)

We, Nikon Europe B.V., Stroombaan 14, 1181 VX Amstelveen, The Netherlands, as the authorized representative, declare the conformity.

COMPANY REPRESENTATIVE: TAKAHARU SASAOKA

TITLE: Director & Executive Vice President

Healthcare Division Head

PLACE: AMSTELVEEN, THE NETHERLANDS

SIGNATURE:

DATE: I November, 2022



KoPa Capture Pro Software User Manual



Content

Chapter 1: Software Installation	1 -
1.1 Environmental requirements for software installation	1 -
1.2 Installation steps	1-2 -
1.3 Software connection to the camera method	2-3 -
Chapter 2: Software Instructions	4 -
2.1 Operation interface	4 -
2.2 Shortcut toolbar	4 -
2.2.1 Shortcut tools	4-5 -
2.2.2 Automatic depth-of-field fusion function for high content images	5 -
2.2.3 Combine channels	6 -
2.2.4 Combined color images	6 -
2.3 Working mode bar	7 -
2.4 Camera property control	7 -
2.5 Measuring tools	8 -
2.5.1 Calibration	8-9 -
2.5.2 Select measurement tool for measurement	9-10 -
2.6 Drawing tools	10 -
2.7 Thumbnail toolbar	11 -
2.8 Software setup	11 -

Chapter 1: Software Installation

1.1 Environmental requirements for software installation

System requirements:

CPU type: i5 10th Generation or later version;

Memory capacity ≥ 16GB or more;

Hard drive capacity ≥ 512GB or more;

System: Genuine Microsoft Windows 10 (64 bit) or later version;

Graphics card: Core display or discrete graphics card.

Note: Some functions in the software require the computer with

Microsoft Word 2003 or later version (for output measurement results to Microsoft Word function)

Microsoft Excel 2003 or later version (for output measurement results to Microsoft Excel function)

Microsoft Outlook 2003 or later version (for sending pictures via email function)

1.2 Installation steps


Step1.Run the file "KoPa Capture Pro Install". When window pops up, please select the installation guide language.


Note: The installation guide language is independent of the software interface language. If you need to change the software interface language, please select the "Language" function in the "Settings" menu to modify.

Step 3. When the window "Select Destination Location" pops up, click "Browse" to choose the file path for installation (usually default), and then click " vocation" to continue.


Step 4. When following window appears, select the shortcut you need, and then click the button " ... "...







Step 5.Confirm information like the "Destination Location" of software installation. After confirmation, please click the button "_______".



Step 6. An installation progress bar will appear during the software installation procedure. The software installation necessitates the registration of some runtime libraries, which might be intercepted by some antivirus software. If such interception pops up, please allow the procedure to continue.

Step 7. An installation progress bar will appear during the software installation procedure. When the following window appears, the software has been installed successfully. Then click the button " to complete the installation. After closing the window, check the icon " on your computer desktop. If you fail to find it, please find it from the path "Start"—"All programs".




1.3 Software connection to the camera method

The software supports connection to the camera via USB, WiFi and network connections.

1.3.1 USB connection method

Just unplug the camera switch to USB gear and connect the camera USB cable to the PC's USB port.








1.3.2 Wireless connection method (only valid for cameras with WiFi capability)

Step 1: Confirm that the computer supports the 5G WiFi IEE 802.11ac protocol;

Step 2: WiFi embedded camera or WiFi camera, power on and switch to WiFi gear. As shown in the figure below:




If you are using a smart embedded display camera, smart display camera, smart embedded camera, smart camera, you only need to turn on the power.



Step 3: After the WiFi camera is started, search for the camera's WiFi name WiFiCamera_5G_xxxxxx or WiFi5Camera_xxxxxx in the network connection, the default connection password is 12345678, the display shows "Connected" that is successfully connect-ed to the camera WiFi, start the software to get real-time images.


Chapter 2: Software Instructions

2.1 Operation interface



2.2 Shortcut toolbar

2.2.1 Shortcut tools



Û	Removal tool / Eraser tool	Delete or erase the selected "object" with a single click.			
\square	Compare with multiple windows	 □ Full screen □ Home screen □ Dual screen comparison □ Four screen comparison Four screen comparison			
	Flip	Flip the image on the currently selected screen.			
	Mirror	Mirror the image on the currently selected screen.			
6	Take a picture	Take a picture on the currently selected screen.			
	Screenshot	Screenshot on the entire computer desktop.			
00	Record	Record on the currently selected screen.			
	Screen record	Screen record on the entire computer desktop.			
AUTO	Automatic depth-of-field fusion function for high content images	Automatic extraction of the clearest areas of the captured image for fusion, take one picture, two archives.			
4	Core	Equal scale cropping of images.			
	Combine channels	Assign fluorescence channels to selected images.			
	Combined color images	Composite overlay of selected color fluorescence images.			

2.2.2 Automatic depth-of-field fusion function for high content images

Automatic depth-of-field fusion function for high content images works with USB or WiFi connection. Break through the limitation of insufficient depth-of-field in high magnification objective lenses, and to adjust the focal length can obtain a greater depth of field, thus obtaining a sharper image than a real-time single-frame image, support taking one picture, two archives.



Operation steps:

Step 1. Click " button, a dual screen appears, the left screen is in line with the focal plane under the eyepiece, and the right screen is the result of high content fusion.


Step 2.Adjust the microscope coarse/fine focus knob, the depth-of-field fusion in real time on the right screen. If you switch the field of view midway, you can click " U button to refresh.

Step 3.Click " button to automatically save two pictures on the left and right screen, close the current window to exit, click " button to enter the file manager and export pictures.


2.2.3 Combine channels

Fluorescent channels can be assigned quickly






Fluorescence channels can be specified for imported images (as shown in the figure below)




Allows direct input of X, Y, and brightness values for fine adjustment.



Note: Please import images with the same resolution, otherwise the image import will fail.

2.2.4 Combined color images


Color fluorescent images can be quickly combined.



Note: Please import images with the same resolution, otherwise the image import will fail.

Allows direct input of $\boldsymbol{X},\,\boldsymbol{Y},$ and brightness values for fine adjustment.

Ô	Live image taking
	Preview window setting: double window to display original image and combine channels image separately, single window to display combine channels image only
•	Image Zoom
	Image reduction
K Z Z X	Adapts to screen size
<u>*</u>	Import images




2.3 Working mode bar

Preview resolution 4000×3000 1920×1080 2592×1944 3840×2160 #000×3000	Preview resolution	Any of the resolutions in the drop-down list can be set for preview.
Preview format H264 H264 MJPG	Preview format	You can switch between MJPG and H264 preview formats. The advantage of H264 format is that the image quality is more transparent, but it requires a higher computer configuration. The advantage of MJPG format is that it requires a lower computer configuration, but the picture quality is not as good as H264.

2.4 Camera property control



Adjust the corresponding image property parameters as needed to achieve the desired image effect.




Staining tape	Users can select different exclusive types of stained pathology sections to obtain matching image effects and more accurate color reproduction. BF type 1: for bright-field, red or gold-based sections. BF type 2: for bright-field, cyan-dominated sections. FL type: for fluorescence observation.				
Brightness	Manually drag the adjustment bar to adjust the image brightness.				
Exposure	When checked, the camera will automatically expose according to the environment used. When unchecked, manual exposure can be performed through the adjustment bar, supporting direct input of values in the box.				
White Balance	Manual white balance adjustment can be made through the adjustment bar, supporting direct input of values in the box. Click on "R" will restore the default value of the R channel alone. Click on "B" will restore the default value of the B channel alone				
Gain	Manually drag the adjustment bar to adjust the image gain. Support for entering values directly in the box. Click on "Gain" will restore the default value of gain alone.				
Contrast	Manually drag the adjustment bar to adjust the image contrast. Support for entering values directly in the box. Click on "Contrast" will restore the default value of contrast alone				
Hue	Manually drag the adjustment bar to adjust the image hue. Support for entering values directly in the box. Click on "Hue" will restore the default value of hue alone.				
Saturation	Manually drag the adjustment bar to adjust the image saturation. Support for entering values directly in the box. Click on "Saturation" will restore the default value of saturation alone.				
Sharpness	Manually drag the adjustment bar to adjust the image sharpness. Support for entering values directly in the box. Click on "Sharpness" will restore the default value of sharpness alone.				
Gamma	Manually drag the adjustment bar to adjust the image gamma. Support for entering values directly in the box. Click on "Gamma" will restore the default value of gamma alone.				
Export image properties	Exporting image properties to local disk.				
Import image properties	Import image properties from local disk.				
Restore Default values	Postare all image property parameters to their default values				

2.5 Measuring tools



Provides calibration function as well as measurement function for dynamic or still image in the preview window.





2.5.1 Calibration


Step 1: Please place the micrometer under the microscope, the example below uses a micrometer with 1DV= 0.01mm.



Step 2: Click on " | | ' | ' to bring up the calibration table as shown below.



Step 3: When using the mouse to draw a straight line on the micrometer image and setting the scale length, selecting a longer scale length will give more accurate results. For example, selecting 10 small scale lengths will give you more accuracy than selecting only 1 scale length. After releasing the mouse, the image value of the line drawn with the mouse will be automatically updated in the "Benchmark" of the calibration table, as shown in the following figure.



Step 4: Enter a name in the calibration table, such as 10X. In the calibration table, enter the actual length that just drawn on the micrometer, for example, the sample figure is drawn 100 DV, that is, 1mm, or 1000µm, then enter the "actual length" box to fill in the specified 1000, "unit" select "µm". Then click "Add" to add this calibration value to the calibration table to be used. Add the calibration value for other objectives of different magnifications in this way.



Notes.

- ① "Add": The information in the right box will be added to the list on the left.
- ② "Edit": The calibration value selected in the left list will be modified.
- ③ "Delete": The calibration value selected in the left list will be deleted.
- ④ "Apply": The calibration value selected in the left list will be called.

2.5.2 Select measurement tool for measurement

Firstly, select the calibration value according to the actual objective used in the calibration table and click on "Apply". The following figure shows.:



Then select the measurement tools to measurement as follows:


←→	Linear distance measurement	$\begin{array}{ c c } \hline & & & \\ \hline & & & \\ \hline \end{array}$	Concentric circle measurement
\odot	Circular measurement	Ф -	Concentric radius circle center distance drawing circle measurement
	Rectangle measurement		Ring measurement
4	Three-point angle measurement	2 3 1 K	Manual count
//	Parallel line spacing measurement	<u>A</u>	Font
//	Center distance measurement of double parallel lines	†	Scale mark
\mathcal{N}	Polyline measurement	لسبا	Scale bar
\bigcirc	Polygon measurement	Line type ✓	
	Arc measurement		Line type
上	Three-point vertical line measurement		
4	Four-point angle measurement	Line width	line width
	Ellipse measurement	Transparency + 0	Transparency
	Circle radius measurement	Color	Colour
\bigcirc	Three point drawing circle measurement		

The results of each measurement will be displayed on the right side of the software. The user can export the measurement results.

Click the export tool in the upper right display bar to export data and images to PDF, Word, Excel, printer and mail (Outlook only). Export to PDF, printer and mail functions are only available for still images.

Select Export to Word, as shown below: Enter file name, select path, and click "Save".


The exported documents are as follows:




Serial No.	Measure item	Measured value
1	Circular measurement	Radius=21.175 um
		Perimeter=133.046 um
		Area=1408.611 um ²
2	Concentric circle measurement	Radius1=19.674 um
		Perimeter1=123.616 um
		Area1=1216.025 um ²
		Length=60.056 um
		Radius2=19.507 um
		Perimeter2=122.569 um
		Area2=1195.504 um ²
3	Linear distance measurement	Length=76.050 um

2.6 Drawing tools








2.7 Thumbnail toolbar

Right-clicking on a thumbnail will display the action menu as shown in the figure below.



Open: Open the image in the software default way.

Open directory: Open the directory where the selected image is located.

Copy: Copy the currently selected image.

Paste: Paste the image that has been copied. (Note: Paste can only be done within the thumbnail toolbar).


Delete: Permanently delete the selected image and permanently delete the source file.

One-click deletion: permanently delete all thumbnails and permanently delete the source files.

Rename: Rename the selected image.

Refresh: Refresh the current image thumbnail area.


2.8 Software setup





KoPa WiFi Lab App User Manual





Content

1.1 Smart terminal system requirements	- 1 -
1.2 APP download and installation	- 1 -
1.3 Capture images by using the APP	- 1 -
1.3.1 The method of scan the connection code	- 1 -
1.3.2 Manual connection method	- 2 -
1.4 APP function introduction	- 2 -
1.4.1 Preview window2	?-5 -
1.4.2 Folder Management5	5-6 -
1.4.3 APP Settings	- 6 -

1.1 Smart terminal system requirements

Note: smart phones and tablets are collectively referred to as smart terminals in the following.

Please confirm that the smart terminal device hardware must support the 5G WiFi IEEE802.11ac protocol, otherwise it will not be able to acquire the image correctly.

System	System version	CPU	Memory RAM	Storage ROM	Protocol
Android	5.0 and later version	Dual core 1.7GHz and later version	3GB or more	32GB or more	5G WiFi IEE802.11ac
iOS	11.0 and later version	Dual core 1.8GHz and later version	2GB or more	32GB or more	

1.2 APP download and installation

Method 1: Scan the camera's APP QR code with the smart terminal's browser, and download and install [KoPa WiFi Lab] according to your cell phone system.

Method 2: Enter the following download link directly on the browser of your smart terminal: https://cn.ostec.com.cn/downloads/kopa-wifi-lab

Download and install [KoPa WiFi Lab] according to your cell phone system.

Method 3: Android users outside of mainland China can search and download [KoPa WiFi Lab] from Google Play, the Google App store.

iOS users can search and download [KoPa WiFi Lab] from the Apple App Store.

Note! APP installation process will prompt to allow permissions, please click all allow, otherwise the APP will not be able to use normally.




1.3 Capture images by using the APP

1.3.1 The method of scan the connection code:


Click the button " on the [KoPa WiFi Lab] navigation interface and scan the QR code on the camera body to automatically connect to the microscope screen without entering a password.





1.3.2 Manual connection method:

- 1) Search for the camera's WiFi SSID: WiFiCamera_5G_xxxxxx or WiFi5Camera_xxxxxx in the WLAN of the smart terminal; default connection password: 12345678.
- 2) Enter the App [KoPa WiFi Lab] navigation interface, and click the button " " to connect to the microscope screen manually.








1.4 APP function introduction



Α	Preview	Click and enter the image preview window.		
В	File folder	View photo / video files.		
С	C Scanning Scan the camera's serial number SSID QR code acquire the image. Note:To ensure preview speed, it is recommended that no more than 13 smart devices (mobile phoror tablet) connect to the same camera at the same time.			
D	Settings	APP settings.		
Е	E User instructions Retrieve / hide user instructions.			

1.4.1 Preview window



(2)Measurement tools

	Rectangular	(MA)	Linear measurement
\bigcirc	Rounded radius	[++[++]	Calibration
(4)	Protractor		

(1)Annotation tools

	Line	Т	Add text
	Single-arrow		Font size
	Round		Colour
	Oval		Eraser
de	Hand-draw	0	Rotate
K	Select		Add a picture
	Delete		

KoPa WiFi Lab App User Manual - 2 -

Use the APP for calibration and measurement (mouse access to cell phone is recommended for calibration and measurement).

Step 1: Place the calibration scale within the microscope's field of view;



Name	Length	Unit	Pixels	Selected
10X	1000	um	1073	\checkmark

Step 2: Click on the Calibration button " ;;

Step 3: Select the Add button "+ ";





Step 4: Enter the name, the actual length of the calibration scale, and select the unit.

When you draw on the ruler, the pixels are automatically entered as shown below.

Click "OK" to complete the calibration;

Step 5: Click on the calibration value matching the objective and use the Select

button " 🔭 ";

Step 6: Use the measurement tool of the preview window to measure.




(3)Image processing tools

AUTO	Automatic depth-of-field fusion function for high content images	₹↓ △→k	Flip / Mirror	180°	180°Rotation
	Take picture		Record		File management

Automatic depth-of-field fusion function for high content images

Automatic depth-of-field fusion function for high content images works with USB or WiFi connection.

Break through the limitation of insufficient depth-of-field in high magnification objective lenses, and to adjust the focal length can obtain a greater depth of field, thus obtaining a sharper image than a real-time single-frame image, support taking one picture, two archives.



Operation steps:


Step 1. Click " button, a dual screen appears, the left screen is in line with the focal plane under the eyepiece, and the right screen is the result of high content fusion.

Step 2.Adjust the microscope coarse/fine focus knob, the depth-of-field fusion in real time on the right screen. If you switch the field of view midway, you can click " " button to refresh.

Step 3.Click button to automatically save two pictures on the left and right screen, close the current window to exit, click button to enter the file manager and export pictures.


(4)Camera control tools

Click the arrow button on the left side of the preview window to bring up the camera control bar.



1) Image ratio

Support switching 4:3 /16:9 image ratio.



2) Camera staining type


Users can select different exclusive types of stained pathology sections to obtain matching image effects and more accurate color reproduction.

Type A: for bright-field, red or gold-based sections;

Type B: for bright-field, cyan-dominated sections;


Type C: for fluorescence observation.

Note: Type C will only be displayed if the camera's firmware type supports type FL. Please switch the firmware type from "KoPa Capture Pro" or "KoPa WiFi Lab AO".



3) Camera properties adjustment

Support adjusting Subject Brightness, auto/manual Exposure, Gain, auto/manual White Balance (RB channel is adjusted separately), Contrast, Saturation, Chroma, Sharpness, Gamma, Restore to Default.



1.4.2 Folder Management


(1) Images management

Click on "Select" in the upper right corner to make single or multiple selections and then click the button at the bottom, from left to right, respectively:

One-click export to local album;

Note: Please select Allow APP to access your album by setting your smart devices (mobile phone or tablet) "Setting - Privacy - Photo", otherwise it will prompt "Export fail".

Share to social networks; One-click delete; Search image file by name.




Click to enter any image, the button at the bottom from left to right:

Send to the mailbox (the smart devices needs to be installed in advance with the mailbox);

The previous image; The next image; Share a single image to the social network;

Export the image to the local album; Delete the picture.



\$\text{Scitor}\$
\$\text{Scitor}\$
\$\text{302200066460}\$
\$\text{302200066460}\$
\$\text{302200066400}\$
\$\text{30220



Click on the file name to rename.




Click "Select" in the top right corner and then click the button at the bottom, from left to right, respectively:

One-click Export to local album;


Note: Please select Allow APP to access your album by setting your smart devices (mobile phone or tablet) "Setting - Privacy - Photo". otherwise it will prompt "Export fail".

One-click Delete.



1.4.3 APP settings

Select camera	When there are two or more cameras in the LAN, you can select the cameras to be connected through the list.		
Export QR code	Electronic digital QR code exportable.		
Export photo to album	The photos taken by the APP will be automatically backed up to your phone album after you check the box.		
Always show guidelines	The operation guide will show every time you launch the APP after you check the box.		
Show scale bar	Check the box to show the scale in the preview window, uncheck it to hide the scale.		
Allow switching image quality mode in high content mode	When checked, two image quality mode functions, speed priority and quality priority, will appear each time the high content mode is opened to switch.		









Certificate of Registration

品質マネジメントシステム - ISO 9001:2015

This is to certify that: 株式会社ニコン

ヘルスケア事業部

横浜製作所 〒244-8533 神奈川県 横浜市栄区

長尾台町471

NIKON CORPORATION Healthcare Business Unit

Yokohama Plant 471, Nagaodai-cho, Sakae-ku, Yokohama,

Kanagawa 244-8533 Japan

認証登録番号: FM 730353

上記組織が認証登録番号FM 730353を保有し、また下記認証登録範囲について ISO 9001:2015 の要求事項に適合した品 質マネジメントシステムを実施していることをここに証します。

顕微鏡、顕微鏡用レンズ及びアクセサリの設計開発、製造、販売、修理 Design and development, manufacture, sales, and repair of microscope, microscope lens and accessories.

For and on behalf of BSI:

Michael Lam - Managing Director Assurance, APAC

初回認証登録日: 1993-10-29

最新更新日: 2023-10-04

発効日: 2023-11-28

有効期限日: 2026-11-27

Page: 1 of 2





...making excellence a habit.™

認証登録番号: FM 730353

所在地 認証登録範囲

株式会社ニコン ヘルスケア事業部 横浜製作所 〒244-8533 神奈川県 横浜市栄区 長尾台町471 NIKON CORPORATION Healthcare Business Unit Yokohama Plant 471, Nagaodai-cho, Sakae-ku, Yokohama, Kanagawa 244-8533 Japan

顕微鏡、顕微鏡用レンズ及びアクセサリの設計開発、製造管理、修理 Design and development, manufacture control and repair of

microscope, microscope lens and accessories.

株式会社ニコン ヘルスケア事業部 本社 〒108-6290 東京都 港区 港南2-15-3 NIKON CORPORATION, Healthcare Business Unit Head office 2-15-3, Konan, Minato-ku, Tokyo 108-6290 Japan 顕微鏡、顕微鏡用レンズ及びアクセサリの販売 Sales of microscope, microscope lens and accessories.

Page: 2 of 2





Certificate of Registration

OUALITY MANAGEMENT SYSTEM - ISO 13485:2016 & EN ISO 13485:2016

This is to certify that: NIKON CORPORATION

Healthcare Business Unit

Yokohama Plant 471, Nagaodai-cho, Sakae-ku, Yokohama,

Kanagawa 244-8533 Japan 株式会社ニコン ヘルスケア事業部

横浜製作所 〒244-8533 神奈川県 横浜市栄区 長尾台町471

Holds Certificate No: MD 711119

and operates a Quality Management System which complies with the requirements of ISO 13485:2016 & EN ISO 13485:2016 for the following scope:

Design, Manufacture and Servicing of Biological Microscope 生物顕微鏡の設計、製造、付帯サービス

For and on behalf of BSI:

Graeme Tunbridge, Senior Vice President Medical Devices

Original Registration Date: 2019-11-20

Latest Revision Date: 2023-10-04

Effective Date: 2023-11-15 Expiry Date: 2026-11-14

Page: 1 of 2

UKAS MANAGEMENT SYSTEMS 0003

...making excellence a habit."

This certificate was issued electronically and remains the property of BSI and is bound by the conditions of contract. An electronic certificate can be authenticated <u>online</u>.

Printed copies can be validated at www.bsigroup.com/ClientDirectory or telephone 045-414-3022

Certificate No:

MD 711119

Location

Registered Activities

Microscope

Design, Manufacture Control and Servicing of Biological

生物顕微鏡の設計、製造管理、付帯サービス

NIKON CORPORATION

Healthcare Business Unit

Yokohama Plant

471, Nagaodai-cho,

Sakae-ku, Yokohama,

Kanagawa

244-8533

Japan

株式会社ニコン

ヘルスケア事業部

横浜製作所

〒244-8533

神奈川県

横浜市栄区

長尾台町471

Sales of Biological Microscope 生物顕微鏡の販売

NIKON CORPORATION,

Healthcare Business Unit

Head office

2-15-3, Konan,

Minato-ku,

Tokyo

108-6290 Japan

株式会社ニコン

ヘルスケア事業部

本社

〒108-6290

東京都

港区

港南2-15-3

Original Registration Date: 2019-11-20

Latest Revision Date: 2023-10-04

Effective Date: 2023-11-15 Expiry Date: 2026-11-14

Page: 2 of 2

This certificate was issued electronically and remains the property of BSI and is bound by the conditions of contract. An electronic certificate can be authenticated online.

Printed copies can be validated at www.bsigroup.com/ClientDirectory or telephone 045-414-3022

Information and Contact: BSI, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP. Tel: + 44 345 080 9000 BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK. A Member of the BSI Group of Companies.