



## CP10M0N0

BAKERY OVEN 10 TRAYS 600X400 - GN 1/1  
MECHANICAL CONTROL



## FUNCTIONAL CHARACTERISTICS

|                              |                  |
|------------------------------|------------------|
| Display                      | Analogic         |
| Supply                       | Electric         |
| Timer                        | Linear           |
| Number of motors             | 3                |
| Motor speeds                 | 1                |
| Max cooking temperature (°C) | 260 °C           |
| Core probe                   | -                |
| Cooking chamber material     | AISI304          |
| Opening door                 | Right handle     |
| Chimney                      | 50 mm open       |
| Humidification               | Direct injection |
| Air Injection                | -                |
| Version                      | Standard         |

## STANDARDS

|               |    |
|---------------|----|
| Certification | CE |
|---------------|----|

## TRAYS

|               |                      |
|---------------|----------------------|
| Trays rack    | Wire PA-BIV 10/80 mm |
| Max tray load | 4 kg                 |

## DIMENSIONS

|                                     |                  |
|-------------------------------------|------------------|
| Oven size with handle WxDxH (mm)    | 817 x 888 x 1308 |
| Oven size without handle WxDxH (mm) | 817 x 825 x 1308 |
| Chamber size WxDxH (mm)             | 660 x 490 x 948  |
| Unit weight (Kg)                    | 128              |

## PACKAGING

|                                 |                     |
|---------------------------------|---------------------|
| Packaging                       | PALLET + CARTON BOX |
| Packaging size WxDxH (mm)       | 895 x 970 x 1460    |
| Unit weight with packaging (Kg) | 144                 |
| Crate packaging size (optional) | -                   |

## ELECTRICAL DATA

|                     |         |
|---------------------|---------|
| Heaters 5kW 50/60Hz |         |
| Power               | 15,8kW  |
| Frequency           | 50/60Hz |



|                 |              |
|-----------------|--------------|
| Power supply    | 380-415V 3N~ |
| Amperage        | 25,2A        |
| Power cord req. | 5G4          |

#### WATER CONNECTION REQUIREMENTS

|                                    |                     |
|------------------------------------|---------------------|
| Humidification Water Inlet         | 3/4" M Gas threaded |
| Washing Water Inlet                | -                   |
| Water drain                        | 30 mm               |
| Max water hardness                 | 5°f                 |
| Water pressure requirement min-max | 150-200 kPa         |

#### CONSUMPTION

|                            |                          |
|----------------------------|--------------------------|
| Humidification Water (L/h) | 22,4 l/h max consumption |
| Rinse Water @2barG         | -                        |
| Short Washing Water @2barG | -                        |
| Long Washing Water @2barG  | -                        |
| Short Washing Detergent *  | -                        |
| Long Washing Detergent *   | -                        |
| Long Washing Detergent *   | -                        |

#### CONNECTIVITY

|           |   |
|-----------|---|
| USB       | - |
| Bluetooth | - |
| Wi-Fi     | - |
| Cloud     | - |

#### ACCESSORIES

|                       |                                                                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Self clean system kit | -                                                                                                                                   |
| Oven stand            | TA8274H17X - TA8274H30X<br>TA8274H40X - TA8274H40S<br>TA8274H49X - TA8274H49S<br>TA8274H70X - TA8274H70S<br>TA8274H80X - TA8274H80S |
| Stand wheel kit       | R100                                                                                                                                |
| Hood (Air)            | POCPMAF1<br>POCPMAF2                                                                                                                |
| Hood (Water)          | POCPMWF1<br>POCPMWF2                                                                                                                |
| External Core probe   | -                                                                                                                                   |
| Sous vide probe       | -                                                                                                                                   |



|                            |                                  |
|----------------------------|----------------------------------|
| Proofer                    | CA8212M0<br>CA8212MH<br>CA8212DH |
| Stacking kit for 2 ovens   | SKCP66                           |
| Smoker                     | SMK02                            |
| Blast Chiller              | -                                |
| Blast chiller stacking kit | SK43                             |
| Water softner cover        | WS10                             |
| Water softner 6800L        | WS11                             |
| Water softner 12000L       | WS12                             |
| Water pressure adapter     | WPA                              |
| Water shower kit           | S1                               |
| Detergent 6 Kg             | DT2                              |
| Detergen 10 Kg             | DT4                              |

