



i-SENSYS X 1440i Series

# TRANSFORM PRINTING AND SCANNING PROCESSES WITH COMPACT YET POWERFUL MULTI-FUNCTION DEVICES



PRODUCTIVITY



SECURITY



CONNECTIVITY



COMPACT DESIGN



CONTROL &  
MAINTENANCE



SUSTAINABILITY

**Canon**

---

# i-SENSYS X 1440i Series

## PRODUCTIVITY

- Intuitive display with tablet like operability
- Fast print and scan speeds
- Automatic double-sided printing
- Up to 900 sheets paper input

## CONNECTIVITY

- Connect to cloud directly from the device for simple storage solutions or through Canon's uniFLOW Online for secure advanced scan workflows
- Print and scan from mobile devices wherever you are

## CONTROL AND MAINTENANCE

- Cloud based output management for centralised control
- Flexible user management solutions
- Remote access to device control functions
- Toner status tool reduces downtime

## SECURITY

- Embedded User Authentication secures access to device
- Encrypted Secure Print function prevents unauthorised viewing of printed material
- Encrypted PDF protects you documents
- Verify System at Start-up enhances device integrity

## COMPACT DESIGN

- Small footprint, ideal as a desktop configuration
- All-in-one cartridge with increased toner yield
- Optional cassettes for enhanced input capacity
- Easy access to replace consumables

## SUSTAINABILITY

- Low TEC (Typical Electrical Consumption) decreases power consumption to save energy and lower running costs
- Sleep mode and low melting point toner reduce energy consumption further
- Auto Duplex Print saves on paper wastage

## QUICK FACTS


### i-SENSYS X 1440iF:

- Print, Copy, Scan, Send and Fax
- 5-inch/12.7cm TFT LCD touchscreen
- Print Speed: 40ppm (A4)
- Automatic double-sided printing
- Scan speed: up to 100ipm
- uniFLOW compatibility
- Network, Wi-Fi, USB and QR code connectivity
- Max paper input capacity: 900 sheets

### i-SENSYS X 1440i:

- Print, Copy, Scan and Send
- 5-inch/12.7cm TFT LCD touchscreen
- Print Speed: 40ppm (A4)
- Automatic double-sided printing
- Scan speed: up to 100ipm
- uniFLOW compatibility
- Network, Wi-Fi, USB and QR code connectivity
- Max paper input capacity: 900 sheets

## TAILORED SOLUTIONS TO MEET EVERY CHALLENGE



Canon's Digital Transformation Services (DTS), bring together our leading hardware and software into an integrated technology ecosystem, designed to support your transformation journey. This offering combines Managed Print Services and Workspace Collaboration solutions, to help you gain transparency and control over the entire document lifecycle.

# TECHNICAL SPECIFICATIONS

# i-SENSYS X 1440i Series

## PRODUCT NAME

**Machine type** Mono Laser All-In-One  
**Available functions** i-SENSYS X 1440iF:Print, Copy, Scan and Fax  
 i-SENSYS X 1440i:Print, Copy, Scan

## PRINTER

**Print speed** Single sided: Up to 40 ppm (A4)  
 Up to 65.4 ppm(A5-Landscape)  
 Double sided: Up to 33.6 ipm (A4)

**Printing method** Monochrome laser beam printing

**Print resolution** Up to 1200 x 1200 dpi

**Warm-up time** Approx. 14 seconds or less from power on

**First Print Out Time** Approx: 5.0 seconds

**Printer languages** UFRII, PCL 5e<sup>2</sup>, PCL6, Adobe® PostScript3

**Fonts** 93 PCL fonts  
 136 PostScript fonts

**Print margins** 5 mm-top, bottom, left and right  
 10 mm-top, bottom, left and right (Envelope)

**Toner saver mode** Yes

**Advanced printing features** Encrypted Secure Print  
 Secure Print  
 Print from USB memory key (JPEG/TIFF/PDF)  
 Print from Cloud: uniFLOW Online, Dropbox, GoogleDrive, OneDrive (PDF/JPEG)  
 Microsoft Universal Print support  
 Barcode Print<sup>5</sup>  
 iOS: AirPrint, Canon PRINT Business app  
 Android: Mopria certified, Canon PRINT Business app, Canon Print Service Plug-in

## COPIER

**Copy speed** Single sided (A4): Up to 40 ppm  
 Double sided (A4): Up to 33.6 ipm

**First Copy Output Time (FCOT)** Approx. 6.1 seconds or less

**Copy resolution** Up to 600 x 600 dpi

**Copy modes** Text, Text/Photo (Default),Text/Photo (High Quality), Photo

**Double sided copying** 2-sided to 2-sided (Automatic)

**Multiple copy** Up to 999 copies

**Reduction / Enlargement** 25-400% in 1% increments

**Other features** Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy

## SCANNER

**Type** Colour

**Scan resolution** Optical: Up to 600 x 600 dpi  
 Enhanced: Up to 9600 x 9600 dpi

**Scan speed** Single sided mono: 50ipm (300x300dpi)  
 Single sided colour: 40ipm (300x300dpi)  
 Double sided mono: 100ipm (300x300dpi)  
 Double sided colour: 80ipm (300x300dpi)  
 Single sided mono: 40ipm (300x600dpi)  
 Single sided colour: 20ipm (300x600dpi)  
 Double sided mono: 80ipm (300x600dpi)  
 Double sided colour: 40ipm (300x600dpi)

**Colour scanning depth** 24 bit/24 bit (input/output)

**Greyscale** 256 levels

**Compatibility** TWAIN , WIA, ICA

**Max. scan width** 216mm

**Scan to E-mail** TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF<sup>1</sup>/PDF (Digital signature)<sup>2</sup>/PDF A-1b

**Scan to PC** TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF<sup>2</sup>/PDF (Digital signature)<sup>2</sup>/PDF A-1b

**Scan to USB memory key** TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF<sup>1</sup>/PDF (Digital signature)<sup>2</sup>/PDF A-1b

**Scan to FTP** TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF<sup>2</sup>/PDF (Digital signature)<sup>2</sup>/PDF A-1b

**Scan to Cloud<sup>1</sup>** TIFF/JPEG/PDF/PNG<sup>5</sup>

**iFAX** ITU-T.37

**FAX** i-SENSYS 1440iF only

**Modem speed** 33.6 Kbps (Up to 3 seconds/page<sup>6</sup>)

**Receive mode** Fax only, Fax/Tel Auto Switch, Answer Mode, Manual

**Fax resolution** Standard: 200 x 100 dpi

Fine: 200 x 200 dpi

Super fine: 200 x 400 dpi

Ultra fine: 400 x 400 dpi

**FAX memory** Up to 512 pages<sup>6</sup>

**Speed dials** Up to 281dials  
**Group dials/destinations** Max. 299 dials / Max. 299 destinations  
**Sequential broadcast** Max. 310 destinations

**Memory backup** Permanent fax memory backup (Backup with flash memory)

**Double sided faxing** Yes (Transmit and Receive)

**Other features** Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports

## MEDIA HANDLING

**Scanner type** Platen, 2-sided ADF (single pass)

**Paper input (Standard)** 250-sheet cassette  
 100-sheet multi-purpose tray  
 50-sheet ADF

**Paper input (Option)** 550-sheet cassette

**Maximum paper input capacity** 900-sheet

**Paper output** 150-sheet

**Media types** Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope

**Media sizes** Cassette (Standard and optional):  
 A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolschap, 16K, Custom sizes: Min. 105 x 148 mm Max. 216.0 x 355.6 mm.

**Multi-purpose tray:**  
 A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolschap, 16K, Indexcard, Envelope (COM10, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 216.0 x 355.6 mm.

**ADF:**  
 A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 48 x 85.0 mm Max 216 x 355.6 mm

**Media weights** Cassette (standard and optional): 60 to 120 g/m<sup>2</sup>  
 Multi-purpose tray: 60 to 199 g/m<sup>2</sup>  
 ADF: 50 to 105 g/m<sup>2</sup>

**Double sided printing** A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolschap Custom size - Min. 210 x 279.4 mm Max. 216.0 x 355.6 mm 60 to 120 g/m<sup>2</sup>

## INTERFACE & SOFTWARE

**Interface type** USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

**Operating System compatibility** Windows® 11 / Windows® 10 / Server® 2022 / Server® 2019 / Server® 2016 / Server® 2012R2 / Server® 2012 Mac OS X version 10.13 & up  
 Linux<sup>7</sup>

**Network Protocol** Print:  
 TCP/IP (LPD/Port9100/IPP/IPPS/WSD)  
 Scan:  
 Push Scan: File: FTP (TCP/IP), SMB3.0 (TCP/IP)  
 E-mail/I-Fax: SMTP (send), POP3 (receive)  
 Pull Scan: TCP/IP

**Management:** SNMPv1, SNMPv3 (IPv4,IPv6)

**Security:** TLS1.3, IPsec, IP address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS)

**Security (wireless):**  
 Infrastructure Mode:  
 WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA-EAP(AES), WPA2-EAP(AES)  
 Access Point Mode:  
 WPA2-PSK(AES)

**Software and printer management** MF Scan Utility, Remote User Interface (RUI), Remote operation software, Department ID Management, Toner Status Tool,

iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices

eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.

Universal Log-in Manager / uniFLOW online / uniFLOW online Express / uniFLOW Compatibility Application Library



# TECHNICAL SPECIFICATIONS

# i-SENSYS X 1440i Series

## GENERAL FEATURES

<b>Recommended Monthly Print Volume</b>	750 - 4,000 pages per month
<b>Duty cycle</b>	Max. 80,000 pages per month <sup>8</sup>
<b>Processor Speed</b>	1200MHz
<b>Memory</b>	1GB
<b>Storage</b>	4GB eMMC
<b>Control panel</b>	12.7 cm LCD Colour Touch Screen
<b>Dimensions with trays (W x D x H)</b>	420 mm x 460 mm x 375 mm
<b>Installation space (W x D x H)</b>	689 mm x 1,081 mm x 824 mm
<b>Weight</b>	Approx. 15.6 Kg
<b>Operating environment</b>	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
<b>Power Source</b>	220-240V(±10%) 50/60Hz (±2Hz)
<b>Power Consumption</b>	Maximum: Approx. 1,280 W Active printing: Approx. 480W Standby: Approx. 8 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 0.32 kWh/week <sup>12</sup> For detailed information relating to Lot26 regulation, please go to: <a href="http://www.canon-europe.com/For_Work/Lot26/index.aspx">http://www.canon-europe.com/For_Work/Lot26/index.aspx</a>
<b>Noise Levels</b>	Sound Pressure <sup>9</sup> : Active: 53 dB Standby: Inaudible <sup>10</sup>  Sound Power <sup>9</sup> : Active: Duplex 68dB / Simplex 67dB Standby: Inaudible <sup>10</sup>

## CONSUMABLES

**Cartridges** TONER T13 (10,600 pages<sup>11</sup>)

## ACCESSORIES/ OPTIONS

**Items**

i-SENSYS X 1440iF:  
CST.Feeding Module-AH1 (550-sheet cassette)  
TEL 6 Kit Long Cord (Telephone handset)  
Barcode Printing Kit-E1E  
MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW)  
Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW)  
MiCard Attachment Kit-B1  
Send PDF Security Feature Set-E1

i-SENSYS X 1440i:  
CST.Feeding Module-AH1 (550-sheet cassette)  
Barcode Printing Kit-E1E  
MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW)  
Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW)  
MiCard Attachment Kit-B1  
Send PDF Security Feature Set-E1

## Notes:

- <sup>[1]</sup> Subscription to a uniFLOW Online and/or third party cloud service is required.
- <sup>[2]</sup> A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.
- <sup>[3]</sup> Accessory - Barcode Printing Kit-E1E - is required
- <sup>[4]</sup> Accessory - Send PDF Security Feature Set-E1 is required
- <sup>[5]</sup> Scan by MF Scan Utility or Canon PRINT Business app
- <sup>[6]</sup> Based on ITU-T Standard Chart No. 1
- <sup>[7]</sup> Web distribution only. Linux support printing only.
- <sup>[8]</sup> Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
- <sup>[9]</sup> Declared noise emission in accordance with ISO 9296
- <sup>[10]</sup> Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779
- <sup>[11]</sup> Based on ISO/IEC 19752
- <sup>[12]</sup> As per US ENERGY STAR® version 3.0.

## Software & Solutions



## Compatibility



Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

English edition  
© Canon Europa N.V., 2024