

### Favorit Ultra XFE SAE 5W-40 API SN/CF



#### Packages:

1L, 4L, 5L (plastic and metal), 20L, 60L, 208L

#### Meets the requirements and specifications:

SAE 5W-40

API SN/CF

ACEA A3/B4

MB 229.3

VW 502.00/505.00

[EN] Favorit Ultra XFE SAE 5W-40 API SN/CF multipurpose multigrade synthetic engine oil designed to be used in petrol and diesel engine vehicles. The contemporary additive set ensures maximum protection against wear and the extraordinary cleanliness of the engine separate parts under hard operation conditions. Has optimal viscosity at wide-ranging temperatures. Provides easy engine starting at low temperatures. Effectively protects against wear and carbon deposits.

[RU] Favorit Ultra XFE SAE 5W-40 API SN/CF всесезонное синтетическое моторное масло, предназначенное для использования в бензиновых и дизельных двигателях автомобилей. Современный пакет присадок гарантирует прочную смазочную пленку в самых жестких условиях эксплуатации. Обеспечивает легкий пуск двигателя автомобиля при низких температурах. Обладает оптимальной вязкостью в широком диапазоне температур. Эффективно защищает от износа и нагарообразования.

**Precautions:** Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

**Storage conditions:** Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

#### Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm <sup>2</sup> /c at 40 °C	STB ISO 3104-2003	78,2
Kinematic viscosity mm <sup>2</sup> /c at 100 °C	STB ISO 3104-2003	12,81
Viscosity index	STB 1797	164,22
Flash poin, °C	GOST 4333	226
Pour point, °C	GOST 20287	-40
TBN, g KOH/kg	GOST 11362	7,2
Density at 20°C, kg/m <sup>3</sup>	GOST 3900	852

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.