

S_{IDA}-LENS PMMA Intraocular Lens
PRODUCT SPECIFICATIONS

Product Category	Intraocular Lens
Type	PMMA One-Piece
Features	Posterior Chamber Lens with 2 Dialing Holes
Brand name	S _{IDA} -LENS
Model	SDALP
Optic Design	Equiconvex
Optic Size	6.00 mm
Overall Length	12.50 mm
Haptic Angle	Mod. C
Refractive Index	1.489
A-constant	118.4
AC Depth	4.80
Diopter Range	Total diopter range -10 to +40 +6.0 to +10.0: in 0.5 – 1.0 step; +10.0 to +30.0: in 0.5 step;
Intended Use	It is intended for the replacement of human crystalline lens. Single use only.
Additional Details	UV-radiation absorbing & bio-compatible
Certification	CE ₀₆₅₃
Classification	Class IIb, according to Annex II of Council Directive 93/42/EEC
Sterilization Method	EtO
Conformity	MEDDEV 2.4/1 Rev. 9 - June 2010 Rule 5
Applicable Standards	ISO 9001, ISO 13485, ISO 14971, ISO 11607, ISO 10993, ISO 11135, ISO 14155, ISO 14630, ISO 11979, ISO 15223
Shape	
Packing	Individually packed. Each box also contains: Implant ID card & spare labels for documentation