

Heating cleaning bath "Ultrasons-HD"

DIGITAL ELECTRONIC REGULATION OF TEMPERATURE AND TIME FOR TEMPERATURES FROM AMBIENT +5°C TILL 80°C

Optimum cleaning efficiency



It comes complete with a universal basket, lid with handle and drain device.

Bath Part. No. 3000865 (5 Litres capacity) is also supplied with basket for small items.

FEATURES

Double body container, completely made of stainless steel and with waste drain device.

CONTROL PANEL

Illuminated main switch.

Start-stop push button.

Increase/decrease time push button in minutes (from 0' to 60').

Increase/decrease temperature push button in °C.

MODEL

| Part No. | Capacity litres | • | (Width sable) | n/Depth cm | • | t/Wid terior) | | oth Power Generator \ | Power V Heater W | Weight Kg |
|----------|--------------------|----|------------------|---------------|----|------------------|----|--------------------------|---------------------|--------------|
| 300086 | 5 | 15 | 24 | 14 | 27 | 31 | 18 | 120 | 75 | 3,8 |
| 3000860 | 6 | 15 | 30 | 15 | 27 | 35 | 18 | 180 | 75 | 5,8 |
| 3000867 | 7 10 | 15 | 30 | 24 | 35 | 38 | 28 | 240 | 225 | 8,2 |
| 3000868 | 3 22 | 15 | 50 | 30 | 27 | 58 | 35 | 600 | 375 | 15 |
| 3000869 | 40 | 20 | 50 | 40 | 40 | | 50 | 900 | 1000 | 25 |

It comes complete with a universal basket, small basket for small items, lid with handle and drain device.



Heated Ultrasonic baths "Ultrasons-H"

AJUSTABLE TEMPERATURE FROM AMBIENT +5 °C HASTA 75 °C.

APPLICATIONS

For long pieces cleaning (especially for pipettes).



Note: For cleaning long objects whose length may exceed that of the tank, such as tubes, pipettes, etc, it has been proved that they are submitted to the same cavitation effect by introducing them in a test tube filled with liquid and placed vertically in the cleaner.

FFATIIRES

Evenly distributed heating element, adhered to the tank for maximum heat transfer. CONTROL PANEL

Adjustable thermostat heater.

Heater "on" indicator lamp.

Timer switch from 0-15 minutes or continuous operation.

In operation on indicator lamp.

MODEL

| Part No. | Capacity litres | | Width able) | | | t/Wid terior) | | oth Power Generator W | Power Heater W | Weight Kg |
|----------|--------------------|----|----------------|----|----|------------------|----|--------------------------|-------------------|--------------|
| 3000839 | 9 | 15 | 50 | 14 | 30 | 56 | 20 | 200 | 800 | 11 |

ACCESSORIES

Basket, Height 12/Width 46/Depth12 cm. Part No 6005144 3 Lid with concentric reduction ring. Part No 6005134

Lid with handle, Part No 6005124

See page: 91





Ultrasonic pipette cleaner "Ultrasons-P"

FEATURES

Designed for automatically cleaning and rinsing pipettes, mounted inside a basket, pipettes are ultrasonically cleaned and rinsed.

Minimum rinsing time by using a water siphon action through the inside of the pipettes.

Metallic areas in contact with liquid are made of AISI 316 stainless steel.

The outer casing is made of AISI 304 stainless steel.

Cylindrical vessel in transparent acrylic, with lid to avoid splashing.

Connector(1") water inlet and siphon-drain tube.

Basket with handle in polypropylene for the easy handling and carrying of the pipettes.

CONTROL PANEL

Timer from 0-15 minutes or continuous operation.

Indicator lamp showing when the bath is in operation.

MODE

| Part No. | Capacity | Ø / Height | Height / Widht/ Depth | Power | Weight |
|----------|----------|-------------|-----------------------|-------|--------|
| | litres | (usable) cm | (exterior) cm | W | Kg |
| 3000910 | 10 | 15 64 | 84 34 40 | 250 | 15 |