



Approved Coolants

Coolant Specifications

The cooling system must be filled with a ready-mixed coolant containing antifreeze and corrosion-inhibiting additives.

Coolant identification

A sticker behind the grille states the information on the coolant used.

Approved Coolants

The table below lists the current suppliers that meet DAF specification 74002; the mixtures available are 40% glycol and 60% water and also 50% glycol and 50% water.

The cooling system must not be filled with coolants other than those specified in this overview.

Brand name	Supplier
DAF Xtreme Longlife Coolant	DAF Trucks N.V.
TRP Long Life Coolant	DAF Trucks N.V.
Havoline XLC	Arteco
DELO XLC Antifreeze / Coolant	Chevron / Texaco
Havoline Xtended Life Coolant	Chevron / Texaco
Caltex Extended Life Coolant	Caltex
Glacelf Auto Supra/Coolelf Auto Supra	Total
NIS a.d. Novi Sad	Nisotec Antifriz Long Life 100
Maxigel Plus/Ultracooling Plus	Renault Truck Oils
BP Procool	BP
Castrol Radicool SF Premix	Castrol
Castrol Radicool SF	Castrol
Inugel Optimal/Inugel Optimal Ultra	Motul
Yacco LR Organique	Yacco
Petrol Antifriz Koncentrat	Petrol
Protex Long Life/Coolmix LL	Orvema
Protex Long Life	Orvema
Coolmix LL -38	Orvema
Technocooling SMB	SMB Auto
York 718	York SAS
Coolant Maxmaster Truckcool	Platinum Oil Wielkopolskie Centrum Dystrybucji

Brand name	Supplier
OPET EXTENDED LIFE ANTIFREEZE	OPET FUCHS Madeni Yağ A.Ş.
Maintain Fricofin LL	Fuchs Europe Schmierstoffe GMBH
Fricofin LL 50/50	Fuchs Europe Schmierstoffe GMBH
Coolant concentrate Maxmaster Redcool	Platinum Oil Wielkopolskie Centrum Dystrybucji
Glysantin G 30-91	BASF
Polar Premium Longlife Antifreeze	Telko
Zero Longlife Antifreeze	Telko
Kuehlerfrostschutz KFS 12 Plus	LIQUI MOLY
Kuehlerfrostschutz KFS 2001 Plus	LIQUI MOLY
PrixMax MEG95	PrixMax Australia Pty Ltd.
Langzeit-Kuehlerfrostschutz GTL 12 Plus	LIQUI MOLY
Coolant Ready Mix RAF 12 Plus	LIQUI MOLY
Repsol Guard Refrigerante Organico MQ	Repsol lubricantes y especialidades, S.A.
Shell Engine Coolant Longlife	Kemetyl Group Ltd
Shell Premium Antifreeze Longlife	Kemetyl Group Ltd
Kemetyl Glycocol Longlife Antifreeze 774 D-F	Kemetyl Group Ltd
Kemetyl Carix Premium Longlife	Kemetyl Group Ltd
Sheron Antifreeze Maxi D	DF Partner s.r.o.
EVOX Premium Concentrate	MOL-LUB Kft
Glixol Extra Long Life	Organika CAR S.A.
Glixol Extra Long Life -37	Organika CAR S.A.
Glixol G12+ Long Life	Organika CAR S.A..
Glixol G12+ Long Life-37	Organika CAR S.A..
Glixol Long Life G12/12+	Organika CAR S.A.
Glixol Long Life G12/12+	Organika CAR S.A.
Petrygo Bus-37	Orlen Oil Sp. Z o.o.
Orlen Petrygo Plus	Orlen Oil Sp. Z o.o.
AVIATICON Finkofreeze F30	Finke Mineralölwerk GmbH
AntiFreeze SP12	Kroon Oil (NL)
AntiFreeze SF12+ 100	Gazpromneft
Coolant SP12	Kroon Oil (NL)
Coolant Longlife G12+	Shell

Note: For all vehicle series with an XE, PE, MX, PR, MX-11 or MX-13 engine and intarder or arctic package, coolants with a mixture of 50% glycol and 50% water must be used.