

EU DECLARATION OF CONFORMITY



Translation of the German original

Module H / N° CE-0062-PED-H-SAM 001-25-DEU-rev-A

For the following products, SAMSON hereby declares under its sole responsibility:

Devices	Series	Type	Version
Three-way valve	-	2119	DIN EN, body, EN-GJL-250 and 1.0619, DN 150, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619, DN 100 to 150, PN 25, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 150, PN 40, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 6, Class 150, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 2 to 6, Class 300, fluids G2, L2, L1 ¹⁾
Self-operated regulator	-	3222	DIN EN, body, CC499K, DN 50, PN 25, all fluids
Three-way valve	-	3260	DIN EN, body, EN-GJL-250, DN 250 to 300, PN 16, fluids G2, L2 ¹⁾
Globe valve	V2001	3531	DIN EN, body, 1.0619 and 1.4408, DN 50 to 80, PN 25, all fluids
Three-way valve		3535	ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 3, Class 150, all fluids
Control valve	-	3214	DIN EN, body, EN-GJL-250, DN 150 to 400, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 100 to 150, PN 25, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619, DN 32 to 400, PN 40, all fluids
			ANSI, body, A126 B, NPS 6 to 10, Class 125, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC, NPS 2½ to 10, Class 150, all fluids
			ANSI, body, A216 WCC, NPS 1½ to 10, Class 300, all fluids
Self-operated regulator	42	2423	DIN EN, body, EN-GJL-250, DN 150 to 250, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 150, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 100 to 150, PN 25, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 250, PN 16, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 50 to 250, PN 25, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 32 to 250, PN 40, all fluids
			ANSI, body, A126 B, NPS 6 to 10, Class 125, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 10, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 1½ to 10, Class 300, all fluids
Self-operated regulator	42	2422	DIN EN, body, EN-GJL-250, DN 150 to 400, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 100 to 150, PN 25, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 400, PN 16, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 200 to 400, PN 25, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 32 to 400, PN 40, all fluids
			DIN EN, body, 1.0460, DN 40 to 50, PN 40, all fluids
			DIN EN, body, 1.6220+QT, DN 65 to 250, PN 16, all fluids
			DIN EN, body, 1.6220+QT, DN 200 to 250, PN 25, all fluids
			DIN EN, body, 1.6220+QT, DN 32 to 250, PN 40, all fluids
			ANSI, body, A126 B, NPS 6 to 16, Class 125, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 16, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 1½ to 16, Class 300, all fluids
			Self-operated regulator
ANSI, body, A352 LCC, NPS 2½ to 10, Class 150, all fluids			
ANSI, body, A352 LCC, NPS 1½ to 10, Class 300, all fluids			

4000525465 | English | 1.0 | Revision: 03

Devices	Series	Type	Version
Self-operated regulator	42	2421RS	DIN EN, body, 1.0619 and 1.4408, DN 65 to 150, PN 16, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 50 to 150, PN 25, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 32 to 150, PN 40, all fluids
			DIN EN, body, 1.4571 and 1.4401/1.4404, DN 50, PN 25, all fluids
			DIN EN, body, 1.4571 and 1.4401/1.4404, DN 32 to 50, PN 40, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 6, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 1½ to 6, Class 300, all fluids
Self-operated regulator	40	2405	DIN EN, body, 1.0619, 1.4571, 1.4404, 1.4408, 1.0460, DN 32 to 50, PN 40, all fluids
			ANSI, body, A105, A182 F316L, A351 CF8M, A216 WCC, NPS 1½ to 2, Class 300, all fluids
Self-operated regulator	40	2406	DIN EN, body, EN-GJL-250, DN 150, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 32 to 150, PN 40, all fluids
			DIN EN, body, 1.0460 and 1.4404, DN 32 to 50, PN 40, all fluids
			ANSI, body, A126 B, NPS 6, Class 125, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 6, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 1½ to 6, Class 300, all fluids
			ANSI, body, A105 and A182 F316L, NPS 1½ to 2, Class 300, all fluids
Self-operated regulator	41	2412 2417	DIN EN, body, EN-GJS-400-18-LT, DN 100, PN 25, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 32 to 100, PN 40, all fluids
			DIN EN, body, 1.0460, 1.4571 and 1.4404, DN 32 to 80, PN 40, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 4, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 1½ to 4, Class 300, all fluids
			ANSI, body, A105 and A182 F316L, NPS 1½ to 3, Class 300, all fluids
Self-operated regulator	-	2404-1	DIN EN, body, EN-GJL-250, DN 150, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 32 to 150, PN 40, all fluids
			ANSI, body, A126 B, NPS 6, Class 125, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 6, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 1½ to 6, Class 300, all fluids
Self-operated regulator	-	2404-2	DIN EN, body, EN-GJL-250, DN 150 to 400, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 400, PN 16, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 400, PN 40, all fluids
			ANSI, body, A126 B, NPS 6 to 16, Class 125, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 16, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 10, Class 300, all fluids
Self-operated regulator	-	2331 2337	DIN EN, body, EN-GJL-250, DN 250, PN 16, fluids G2, L2 ¹⁾
			DIN EN, body, 1.0619, DN 250, PN 16, fluids G2, L2 ¹⁾
			DIN EN, body, 1.0619, DN 200 to 250, PN 25, fluids G2, L2 ¹⁾
			DIN EN, body, 1.0619, DN 125 to 250, PN 40, fluids G2, L2 ¹⁾
Self-operated regulator	-	2333 2335	DIN EN, body, EN-GJL-250, DN 150 to 400, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 100 to 150, PN 25, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 400, PN 16, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 200 to 400, PN 25, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 400, PN 40, all fluids
			ANSI, body, A126 B, NPS 6 to 16, Class 125, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 16, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 16, Class 300, all fluids

Devices	Series	Type	Version
Self-operated regulator	-	2334	DIN EN, body, EN-GJL-250, DN 150 to 400, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 150, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 100 to 150, PN 25, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 400, PN 16, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 200 to 400, PN 25, all fluids
			DIN EN, body, 1.0619 and 1.4408, DN 65 to 400, PN 40, all fluids
			ANSI, body, A126 B, NPS 6 to 16, Class 125, fluids G2, L2, L1 ¹⁾
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 16, Class 150, all fluids
			ANSI, body, A216 WCC and A351 CF8M, NPS 2½ to 16, Class 300, all fluids
Self-operated regulator	-	2373 2375	DIN EN, body, 1.4469 and 1.4470, DN 32 to 50, PN 40, all fluids
			ANSI, body, A995 5A and A995 4A, NPS 1½ to 2, Class 300, all fluids
Strainer	2N/2NI	2602	DIN EN, body, EN-GJL-250, DN 150 to 250, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 150, PN 16, fluids G2, L2, L1 ¹⁾
			DIN EN, body, EN-GJS-400-18-LT, DN 100 to 150, PN 25, fluids G2, L2, L1 ¹⁾
			DIN EN, body, 1.0619, DN 100 to 250, PN 16, all fluids
			DIN EN, body, 1.0619, DN 200 to 250, PN 25, all fluids
			DIN EN, body, 1.0619, DN 32 to 250, PN 40, all fluids
			DIN EN, body, 1.4408, DN 65 to 100, PN 16, all fluids
			DIN EN, body, 1.4408, DN 32 to 100, PN 40, all fluids

¹⁾ Gases according Article 4(1)(c.i), second indent
Liquids according Article 4(1)(c.ii)

Conformity with the following requirement:

Directive of the European Parliament and of the Council on the harmonization of the laws of the Member States relating to the making available on the market of pressure equipment	2014/68/EU	of 15 May 2014
Conformity assessment procedure applied for liquids according to Article 4(1)	Module H	Certificate no.: N°CE-0062-PED-H-SAM 001-25-DEU-rev-A by Bureau Veritas 0062

The manufacturer's quality management system is monitored by the following notified body:

Bureau Veritas Services SAS, 4 place des Saisons, 92400 Courbevoie, France

Technical specifications applied: EN 16668 (incl. EN 12516-2, EN 12516-3), ASME B16.34

Manufacturer: SAMSON AKTIENGESELLSCHAFT, Weismüllerstraße 3, 60314 Frankfurt am Main, Germany

Frankfurt am Main, 20 February 2026

Signiert von:

ppa. Runkwitz, Steffen

8E1B9A2A1804470

ppa. Steffen Runkwitz
Vice President
Global Sourcing

Signiert von:

i.V. P. Scheermesser

D5A19C45AD26414

i.V. Peter Scheermesser
Director
Product Maintenance and Engineered Products