



Performance Specification		
No.minal Pressure	PN16	Test Medium
Shell Test	(2.4MPa)	Water
Seal Test	(1.8MPa)	
Air Seal Test	(0.6MPa)	Air
Suitable Temperature	-30~120℃	
Suitable Media	Water/Steam/Oil/Gas	

DN	L	B	C	D	t	n-h	f	d
DN15	35	φ95	φ65	φ45	10	4-M12	2	φ15
DN20	38	φ105	φ75	φ55	11	4-M12	2	φ20
DN25	42	φ115	φ85	φ65	12	4-M12	2	φ25
DN32	55	φ135	φ100	φ78	14.5	4-M16	2	φ32
DN40	62	φ145	φ110	φ85	15	4-M16	2	φ40
DN50	73	φ160	φ125	φ100	16.5	4-M16	2	φ50
DN65	95	φ180	φ145	φ120	18	4-M16	2	φ65
DN80	118	φ195	φ160	φ135	18.5	8-M16	2	φ80
DN100	140	φ215	φ180	φ155	18.5	8-M16	2.5	φ100
DN125	165	φ245	φ210	φ182	20.5	8-M16	2.5	φ125
DN150	192	φ280	φ240	φ206	22	8-M20	2.5	φ150

14	Nut	201
13	Washer	201
12	Lever	201
11	Gland	201
10	Screw	201
9	Nut	201
8	PacKing	PTFE
7	GasKet	PTFE
6	Stem	201
5	Ball	201
4	SeatSeal	PTFE
3	Bonnet	WCB
2	Gasket	PTFE
1	Body	WCB
No.	Parts	Material



Float ball valve

TYPE:IN-GAZ FLF