

## OFERTĂ COMERCIALĂ

Avem onoarea sa va prezentăm următoarea schema de preturi:

Data 20.01.2022

### Sistem de conferinta CU fir si votare V1

<u>No</u>	<u>Denumirea bunurilor</u>	<u>Cant.</u>	<u>Pret f/TVA, MDL</u>	<u>Pret cu TVA, MDL</u>	<u>Suma f/TVA, MDL</u>	<u>Suma cu TVA, MDL</u>
1	<p><b>Unitate centrala pentru sistem de conferinta DSP Networked Conference controller VIS-DCP2000-D</b>            Full Digital Networked DSP Conference Processor            One CAT5e cable to transmit up 64 channels audio and other signals            The microphone sensitivity of each unit and 16 level equalizer EQ can be adjusted independently            The 16-level equalizer EQ to achieve sound or the whole conference field adjustment, limiter to prevent the sound suddenly become loud or low; noise gate of human voice can be identified; support AGC/AFC/ Mix (Auto-mix) technology            Interfaces            Front panel USB recording interface            3.5mm headphone for monitoring            1x RCA audio input            1x XLR audio input            1x RCA audio output            1x XLR audio output            6x Phoenix interface audio output            2x RJ45 digital audio connection            2x RJ45 for chairman unit, delegate unit, unit translators and other connection            1x DP9 male interface for external control            1x DP9 female interface for camera            1x three-pin phoenix interface for camera control keyboard            1x RJ45 for computer connection or network switcher            1x grounding screw            1x 100 ~ 240V DC Power Interface            Technical Parameters            Power 220V AC            Static power consumption 12W            Maximum power consumption 150W            Frequency Response 20Hz ~ 20KHz            Noise ratio (S / N) &gt; 80dB            Total harmonic distortion &lt;0.05%            Channel Crosstalk &gt; 80dB            Rackmountable            Inclus in set toate cablurile și accesoriile de instalare și interconectare            Garantie 36 luni</p>	1 buc	21 225.00	25 470.00	21 225.00	25 470.00
2	<p><b>Microfon presedinte CAT5 connection DSP digital discussion chairman unit. incl. mic VIS-DVC-T + Microfon tip gooseneck VIS-M600</b></p>	1 buc	6 135.00	7 362.00	6 135.00	7 362.00

	<p>Hot plug and play, Cat5 Wired Desktop Conference Gooseneck Microphone 600mm lenght Touchable buttons: MIC ON/OFF, Priority &amp; Apply Answer</p> <p>5 keys voting, 64 channels 3.5mm stereo earphone jack (*2pcs) 48 kHz audio sampling rate 20Hz~20KHz response frequency Anti RF interference from cell phone or similar devices Automatic Gain Control / Adaptive Feedback Cancellation / Active Noise Control / Auto-Mix Cardioid directional microphone capsule with anti-wind microphone foam, with two-color LED indicator Must realize camera auto tracking (preset) function Garantie 36 luni</p>					
3	<p><b>Microfon delegat CAT5 connection DSP digital discussion delegate unit. incl. mic VIS-DVD-T + Microfon tip gooseneck VIS-M600</b></p> <p>Hot plug and play, Cat5 Wired Desktop Conference Gooseneck Microphone 600mm lenght Touchable buttons: MIC ON/OFF</p> <p>5 keys voting, 64 channels 3.5mm stereo earphone jack (*2pcs) 48 kHz audio sampling rate 20Hz~20KHz response frequency Anti RF interference from cell phone or similar devices Automatic Gain Control / Adaptive Feedback Cancellation / Active Noise Control / Auto-Mix Cardioid directional microphone capsule with anti-wind microphone foam, with two-color LED indicator Must realize camera auto tracking (preset) function Garantie 36 luni</p>	26 buc	5 955.00	7 146.00	154 830.00	185 796.00
4	<p><b>Microfon delegat CAT5 connection DSP digital discussion delegate unit. incl. mic VIS-DID-T + Microfon tip gooseneck VIS-M600</b></p> <p>Hot plug and play, Cat5 Wired Desktop Conference Gooseneck Microphone 600mm lenght Touchable buttons: MIC ON/OFF</p> <p>3.5mm stereo earphone jack (*2pcs) 48 kHz audio sampling rate 20Hz~20KHz response frequency Anti RF interference from cell phone or similar devices Automatic Gain Control / Adaptive Feedback Cancellation / Active Noise Control / Auto-Mix Cardioid directional microphone capsule with anti-wind microphone foam, with two-color LED indicator Must realize camera auto tracking (preset) function Garantie 36 luni</p>	3 buc	4 980.00	5 976.00	14 940.00	17 928.00
<b>SubTOTAL</b>					<b>197 130.00</b>	<b>236 556.00</b>

### Sistem de sonorizare

<u>Nº</u>	<u>Denumirea bunurilor</u>	<u>Cant.</u>	<u>Pret f/TVA, MDL</u>	<u>Pret cu TVA, MDL</u>	<u>Suma f/TVA, MDL</u>	<u>Suma cu TVA, MDL</u>
1	<b>Amplificator AMC MMA240X</b> Putere de iesire – 240 W Posibilitate impartire semnal in maxim 5 zone Intrari: 3 x balanced XLR, 3 x stereo RCA, 6 x 6,3mm jack socket, 1 x 3,5mm TRS Jack. Iesire: 6 x phoenix, 2 x 6.3mm Jack Frequency response – 80 Hz - 15 kHz THD –mai putin 0,5% la 1kHz putere S/N ratio - 75 Db Equalizer - 125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz, ± 12 dB Phantom power – 15V max. Cu posibilitate de instalat pe masa sau in rack pentru boxe de tip 40hm, 25V, 70V si 100V reglare putere sunet intrari si master Inclus in set toate cablurile și accesoriiile de instalare și interconectare GARANTIE: 12 luni	1 buc	10 695.00	12 834.00	10 695.00	12 834.00
2	<b>Speaker AMC iPlay 5T</b> Putere - 35 W (8 Ω) Transformator (100V) - 30 W - 16 W - 8 W - 4 W - 8 Ω Sensibilitate - 89 dB (1 W/1 m) Diapazonul de frecvente - 120 Hz – 20 kHz Dimensiuni fizice - 240 mm x 165 mm x 160 mm Material: Carcasă din polipropilenă cu grilă din aluminiu, Suport de tip U din oțel pentru montare pe perete GARANTIE: 12 luni	8 buc	1 090.00	1 308.00	8 720.00	10 464.00
3	<b>Preamplificator-mixer AMC iMix 63</b> Tip rackmount, Intrari: 6 x universal combi XLR, 3 x stereo RCA Iesiri: 1 x balanced stereo XLR, 1 x stereo RCA, 2 x 6,3 mm TRS jacks Frecventa de raspuns: 20 Hz - 22 kHz THD: 0,03 % @ 1 kHz Alimentare phantom: +18V Inclus in set toate cablurile și accesoriiile de instalare și interconectare Garantie 12luni	1 set	3 435.00	4 122.00	3 435.00	4 122.00
<b>SubTOTAL</b>					<b>22 850.00</b>	<b>27 420.00</b>

### Sistem de distribuire semnal video

<u>Nº</u>	<u>Denumirea bunurilor</u>	<u>Cant.</u>	<u>Pret f/TVA, MDL</u>	<u>Pret cu TVA, MDL</u>	<u>Suma f/TVA, MDL</u>	<u>Suma cu TVA, MDL</u>
1	<b>Smart TV 75" LED TV Hisense H75A7100F</b> (3840x2160 UHD, SMART TV, PCI 1500Hz, DVB-T/T2/C/S2) (75" DLED 3840x2160 UHD, PCI 1500 Hz, SMART TV (VIDAA U4.0 OS), 3 HDMI 2.0, 2 USB, Display color depth 8bit+FRC, HDR10,	2 buc	16 275.00	19 530.00	32 550.00	39 060.00

	HLG,, Wi-Fi (802.11ac, dual-band (2.4G and 5G), DVB-T/T2/C/S2, OSD Language: ENG, RU, RO, Speakers 2x7W Dolby Audio, VESA 400x300, 25.6 Kg) Garantie 24 luni					
2	<b>Suport TV Gembird WM-80RT-01</b>	2 buc	630.00	756.00	1 260.00	1 512.00
3	Matrice HDMI - M5 series Seamless Modular Matrix Switcher, incl.: VW-VL0808 - Digital HD combo matrix 8x8 cabinet; MX-HM4I - 4-channel HDMI input card with audio; MX-HM4O - 4-channel HDMI output card.	1 buc	37 080.00	44 496.00	37 080.00	44 496.00
4	<b>Cablu HDMI 30m CCBP-HDMI-AOC-30m OPTICAL (TV1)</b>	1 buc	1 500.00	1 800.00	1 500.00	1 800.00
5	<b>Cablu HDMI 10m</b>	2 buc	180.00	216.00	360.00	432.00
<b>SubTOTAL</b>					<b>72 750.00</b>	<b>87 300.00</b>

### Manopera

<u>Nº</u>	<u>Denumirea bunurilor</u>	<u>Can t.</u>	<u>Pret f/TVA, MDL</u>	<u>Pret cu TVA, MDL</u>	<u>Suma f/TVA, MDL</u>	<u>Suma cu TVA, MDL</u>
1	<b>Manopera</b> (servicii de instalare, trasare, setare si punere in functiune a echipamentului audio-video, inclusiv materiale, cabluri si accesorii)	serv	14 800.00	17 760.00	14 800.00	17 760.00
<b>SubTOTAL</b>					<b>14 800.00</b>	<b>17 760.00</b>
<b>TOTAL PER OFERTA</b>					<b>307530.00</b>	<b>369036.00</b>

**Total per oferta, fara TVA – 307.530,00 MDL**

**Total per oferta, inclusiv TVA 20% – 369.036,00 MDL**

**Termenul de garantie a echipamentului oferit – 24 luni din ziua darii in primire.**

**Livrarea se efectueaza in termen de pana la 60 zile din data comenzii ferme.**

Numele: Eugeniu Rudenco

Functia: Director

Semnătura: \_\_\_\_\_

L.S.

