





EC Certificate

Full Quality Assurance System
Directive 98/79/EC on In Vitro Diagnostic Medical Devices (IVDD), Annex IV excluding (4, 6)
(List A and B and devices for self-testing)

No. V1 104507 0003 Rev. 06

Manufacturer: ACON Laboratories, Inc.

5850 Oberlin Drive, #340 San Diego CA 92121

USA

Product Category(ies): Blood glucose measuring systems for self testing

and self-testing devices for clinical chemistry, hematology and pregnancy and ovulation

The Certification Body of TÜV SÜD Product Service GmbH declares that the aforementioned manufacturer has implemented a quality assurance system for design, manufacture and final inspection of the respective devices / device families in accordance with IVDD Annex IV. This quality assurance system conforms to the requirements of this Directive and is subject to periodical surveillance. For marketing of List A devices an additional Annex IV (4) certificate is mandatory. All applicable requirements of the testing and certification regulation of TÜV SÜD Group have to be complied with. For details and certificate validity see: www.tuvsud.com/ps-cert?q=cert:V1 104507 0003 Rev. 06

Report no.: SH22743EXT01

 Valid from:
 2022-05-04

 Valid until:
 2025-05-26

Date, 2022-05-04

Christoph Dicks
Head of Certification/Notified Body



EC Certificate

Full Quality Assurance System Directive 98/79/EC on In Vitro Diagnostic Medical Devices (IVDD), Annex IV excluding (4, 6) (List A and B and devices for self-testing)

No. V1 104507 0003 Rev. 06

On Call Plus Blood Glucose Monitoring System, Model(s):

On Call Plus Blood Glucose Test Strips,

On Call EZ II Blood Glucose Monitoring System.

On Call Advanced Blood Glucose Monitoring System,

On Call Advanced Blood Glucose Test Strips.

On Call Chosen Blood Glucose Test Strips,

On Call Vivid Blood Glucose Monitoring System (OGM-101),

On Call Vivid Blood Glucose Test Strips (OGS-101),

On Call Sharp Blood Glucose Monitoring System (OGM-

121),

On Call Sharp Blood Glucose Test Strips (OGS-121)

On Call Plus II Blood Glucose Monitoring System (OGM-

On Call Plus II Blood Glucose Test Strips (OGS-171),

On Call Extra Blood Glucose Monitoring System (OGM-191).

On Call Extra Blood Glucose Test Strips (OGS-191),

On Call GK Dual Blood Glucose & Ketone Monitoring

System (OGM-161),

On Call Blood Ketone Test Strips (OGS-161),

Urinalysis Reagent Strips (Urine),

UTI Urinary Tract Infection Test Strips.

Cholesterol Monitoring System (CCM-111),

CHOL Total Cholesterol Test Devices (CCS-111).

TRIG Triglycerides Test Devices (CCS-112),

HDL High Density Lipoprotein Test Devices (CCS-113),

3-1 Lipid Panel Test Devices (CCS-114),

Cholesterol CTRL Control Devices,

Cholesterol Monitoring System (CCM-101),

CHOL Total Cholesterol Test Strips (CCS-101).

PT/INR Monitoring System (CCM-151),

PT/INR Test Strips (CCS-151),

Hemoglobin Testing System (CCM-141),

Hemoglobin Test Strips (CCS-141),

hCG Pregnancy Rapid Test Cassette (Urine),

Pregnancy Rapid Test Midstream,

On Call Extra Mobile Blood Glucose Monitoring System

(OGM-281),

On Call Sure Blood Glucose Monitoring System (OGM-211),

On Call Sure Sync Blood Glucose Monitoring System (OGM-

212),

On Call Sure Blood Glucose Test Strips (OGS-211),

GIMA Blood Glucose Monitoring System,

GIMA Bluetooth Blood Glucose Monitoring System.

GIMA Blood Glucose Test Strips,

On Call GU Dual Blood Glucose & Uric Acid Monitoring



TÜV SÜD Product Service GmbH is Notified Body with identification no. 0123





EC Certificate

Full Quality Assurance System
Directive 98/79/EC on In Vitro Diagnostic Medical Devices (IVDD), Annex IV excluding (4, 6)
(List A and B and devices for self-testing)

No. V1 104507 0003 Rev. 06

System (OGM-201),

On Call Blood Uric Acid Test Strips (OGS-201),

LH Ovulation Rapid Test Cassette (Urine),

Ovulation Rapid Test Midstream,

Ovulation & Pregnancy Test Combo Pack,

On Call Extra Voice Blood Glucose Monitoring System (OGM-291).

Early Detection Pregnancy Test,

Digital Pregnancy Test,

Go-Keto Blood Glucose & Ketone Monitoring System (OGM-161)

Go-Keto Blood Ketone Test Strips (OGS-161),

Go-Keto Blood Glucose Test Strips,

On Call Extra GM Blood Glucose Monitoring System(OGM-191)

On Call Extra GM Blood Glucose Test Strips (OGS-191),

On Call Plus GM Blood Glucose Monitoring System,

On Call Plus GM Blood Glucose Test Strips,

Go-Keto Urinalysis Reagent Strips

Facility(ies): ACON Laboratories, Inc.

5850 Oberlin Drive, #340, San Diego CA 92121, USA

ACON Laboratories, Inc.

10125 Mesa Rim Road, San Diego CA 92121, USA

AZURE Institute, Inc.

10125 Mesa Rim Road, San Diego CA 92121, USA

Acon Laboratories Inc.

Guerrero Negro 9942 Parque Industrial Pacifico IV, 22644 Tijuana

B.C. CP, MEXICO

Declaration of Conformity

ACON Laboratories, Incorporated 5850 Oberlin Drive #340 San Diego, CA 92121, USA

We, the manufacturer, declare under our sole responsibility that the *in vitro* diagnostic device:

Mission® Urinalysis Reagent Strips (U031-XX1)

classified as Others in the directive 98/79/EC,

meets all the provisions of the directive 98/79/EC on in vitro diagnostic medical devices which apply to it

The self-declaration is according to Annex III (excluding Section 6) of the Directive.

Authorized Representative: Medical Device Safety Service GmbH Schiffgraben 41 30175 Hannover, Germany

Signed this 11 day of February, 2020 in San Diego, CA USA

Qiyi Xie, MD, MPH
Senior Staff, Regulatory Affairs & Clinical Affairs
Acon Laboratories, Inc.

Declaration of Conformity

ACON Laboratories, Incorporated 5850 Oberlin Drive, #340 San Diego, CA 92121, USA

We, the manufacturer, declare under our sole responsibility that the *in vitro* diagnostic device:

Device Name	REF Number	Model Number
Mission® Liquid Urine Control	U021-011	n/a
SPINREACT Liquid Urine Control	U021-013A	n/a
Insight® Liquid Urine Control	U021-015	n/a
Mission® Liquid Diptube Urine Control	U021-071	n/a
Insight® Liquid Diptube Urine Control	U021-075	n/a

classified as Others in the directive 98/79/EC,

meets all the provisions of the directive 98/79/EC on in vitro diagnostic medical devices which apply to it

The self-declaration is according to Annex III (excluding Section 6) of the Directive.

Authorized Representative: Medical Device Safety Service GmbH Schiffgraben 41 30175 Hannover, Germany

Signed this 22 day of October, 2021 in San Diego, CA, USA

Qiyi Xie, MD, MPH Senior Staff, Regulatory Affairs & Clinical Affairs Acon Laboratories, Inc.







Product Service

Certificate

No. Q5 104507 0001 Rev. 03

Holder of Certificate: ACON Laboratories, Inc.

5850 Oberlin Drive, #340 San Diego CA 92121

USA

Certification Mark:



Scope of Certificate: Design and Development, Manufacture and distribution of In Vitro Diagnostic Test Kits and Reagents for the

Determination of Infectious Diseases, Clinical
Chemistry, Drugs of Abuse, Tumor/Cardiac Marker,
Fertility/Pregnancy and Blood Glucose Monitoring

System, Lancing Devices and Lancets

The Certification Body of TÜV SÜD Product Service GmbH certifies that the company mentioned above has established and is maintaining a quality management system, which meets the requirements of the listed standard(s). All applicable requirements of the testing and certification regulation of TÜV SÜD Group have to be complied with. For details and certificate validity see: www.tuvsud.com/ps-cert?q=cert:Q5 104507 0001 Rev. 03

Report No.: SH22743A01

 Valid from:
 2022-09-15

 Valid until:
 2025-09-06

Date. 2022-09-15 Christoph Dicks

Head of Certification/Notified Body





Certificate

No. Q5 104507 0001 Rev. 03

Applied Standard(s): EN ISO 13485:2016

Medical devices - Quality management systems -

Requirements for regulatory purposes

(ISO 13485:2016) DIN EN ISO 13485:2016

Facility(ies): ACON Laboratories, Inc.

5850 Oberlin Drive, #340, San Diego CA 92121, USA

Address holder for registration only

ACON Laboratories, Inc.

10125 Mesa Rim Road, San Diego CA 92121, USA

Manufacture and distribution of

In Vitro Diagnostic Test Kits and Reagents for the Determination of Infectious Diseases, Clinical Chemistry, Drugs of Abuse, Tumor/Cardiac Marker, Fertility/Pregnancy and Blood Glucose

Monitoring System, Lancing Devices and Lancets

ACON Laboratories, Inc.

6865 Flanders Dr., Suite B, San Diego CA 92121, USA

Storage of

In Vitro Diagnostic Test Kits and Reagents for the Determination of Infectious Diseases, Clinical Chemistry, Drugs of Abuse, Tumor/Cardiac Marker, Fertility/Pregnancy and Blood Glucose Monitoring System, Lancing Devices and Lancets

AZURE Institute, Inc.

10125 Mesa Rim Road, San Diego CA 92121, USA

Design and Development of

In Vitro Diagnostic Test Kits and Reagents for the Determination of Infectious Diseases, Clinical Chemistry, Drugs of Abuse, Tumor/Cardiac Marker, Fertility/Pregnancy and Blood Glucose Monitoring System, Lancing Devices and Lancets

Acon Laboratories Inc.

Guerrero Negro 9942 Parque Industrial Pacifico IV, 22644 Tijuana B.C. CP, MEXICO

Manufacture of

blood glucose test strips, antigen rapid test and IgG/IgM antibody rapid test for infectious disease.

•



10125 Mesa Rim Road. · San Diego, CA 92121 · USA Tel: (858) 875-8000 · Fax: (858) 875-8099 · E-mail: info@aconlabs.com

November 11th 2016

CERTIFICATION LETTER

This letter is to certify that, Vitalie Goreacii, employed by Sanmedico SRL located at: Republic of Moldova, city Chisinau, str. Petricani 88/1 of. 10, MD-2059, have received all required training and is enabled and authorized to provide services with installation, commissioning, and maintenance to the products listed below:

Mission® U120 Urine Analyzer

Mission® U120 Ultra Urine Analyzer

Mission® U500 Urine Analyzer

Mission® PT/INR Coagulation Monitoring System

Mission® Cholesterol Monitoring System

Mission® Ultra Cholesterol Monitoring System

Mission® HB Hemoglobin Testing System

Mission® Plus HB Hemoglobin Testing System

OnCall® Glucose Meter

For further questions or inquiries regarding this matter, please refer to the contact information below.

Sincerely

Jassy Alvarenga

International Account Manager

ACON Laboratories, Incs.A.

jalvarenga@aconlabs.com

+1 858 875 8085

Mission® Urinalysis Reagent Strips and Urine Analyzers



Urinalysis Reagent Strips

Simple and Accurate


- Analytical sensitivity better than or comparable to market leaders
- · High quality color chart ensures accurate visual reading

- · Compatible for visual and analyzer reading
- · More than 30 different combinations available

Multiple Packaging Options and Long Shelf Life

- Canister Packaging
 Available in 25, 50, 100 and 150 strips per kit
 - · 2 year shelf life for unopened canisters which offers cost savings and convenience for high volume testing
- 3 month shelf life for strips in opened canisters Pouch Packaging New!
- · Single-strip Pouch
 - Individually packaged strips with 1, 3, 6 and 20 strips and 1 color chart per kit for OTC or low volume testing
- . Unique packaging maintains 2 year shelf life for all strips in the kit compared to 3 months for remaining strips in an opened canister
- Multi-strip Pouch
- · Canister Refill Kits with 25 strips/pouch uniquely packaged to save cost for low volume testing and extended shelf life by using the canister for refills





Ste	Step 1: Immerse strip into urine Step 2: Remove excess urine					ne S	Step 3: Obtain results by analyzer or visual reading															
Catalog No of		Type of Strip ◆		String pay Reading Method Analyzer-Read				Parameters														
Catalog No.	No. of Parameters	For Visual Reading	For Analyzer Reading (U120/U500)	Strips per Canister	Pouch Packaging*	Visual	U120	U500	Strips: Standard (S) or Additional (A)	ASC	GLU	BIL	KET	sg	BLO	рН	PRO	URO	NIT	LEU	ALB	CRE
U031-131	13	13C	NA	100"	✓	1	NA	NA	Α	*	*	*	*	*	*	*	*	*	*	*	*	*
U031-111	11		11A	100	4	1	1	1	S	*	*	*	*	*	*	*	*	*	*	*		
		12	10U	100		4	~	1	S		*	*	*	*	*	*	*	*	*	*		
U031-101	10		10A		¥ .	1	1	~	Α	*	*	*	*	*	*	*	*	*	*			
			10C	100"		1	~	1	S		*		*	*	*	*	*		*	*	*	*
U031-091	9		9U	100	✓	~	1	1	S		*	*	*	*	*	*	*	*	*			
			8U			1	1	1	Α		*	*	*		*	*	*	*	*			
U031-081	8		8N	100	¥	~	1	1	S		*		*	*	*	*	*		*	*		
11001 071			8S	100		1	V	1	A		*			*	*	*	*	*	*	*		
U031-071	7		7N	100	√	1	1	1	A		*		*		*	*	*		*	*		
U031-061	6	6N	6NE 6UE	100	✓	4	V	4	A		*	*			*	*	*	100	*	*		\blacksquare
		6U 5B	5BE	_		4	V	4			*	*	*	*	*	*	*	*	*			
		5N	5NE	-		4	1	1	1	-	*		*		*	*	*		*	*		Н
U031-051	5	5N 5S	5SE	100		*	_		*	*	*	*	-		*		\vdash					
		5U	5UE	1		_	-		1	_	•	*		Ĥ	*	-		*	*	*	\vdash	\vdash
		48	4SE			1	1	1			*	-		*	-	*	*		_			
		4B	4BE	1000000) 8	1	~				*				*	*	*					
01022201200	9	4K	4KE			1	1	1			*		*			*	*					
U031-041	4	4G	4GE	100	×	1	1		Α		*				*		*			*		
		4N	4NE		2	1	1	1	3						*		*		*	*		
		4P	4PE			1	1	1			*		t				*		*	*		
		3P	3PE			1	V	1			*					*	*					
U031-031	3	3K	3KE	100	√	1	V	1	A		*		*				*					
0031-031		3G	3GE] 100	*	1	1	~	^		*		*			*						
		3N	3NE			1	~	V							*				*	*		
		2G	2GE			1	1	1			*						*					
		2K	2KE			1	✓	1			*		*									
12022017220	020	2N	2NE	1722	N	1	V	1							*					*		
U031-021	2	2B	2BE	100	*	1	V	1	A		*		*									
		2U	2UE			4	1	1											*	*		
		28	2SE			1	V	1						*		*						
		2C	2CE	100*		4	V	4								-					*	*
		1B	1BE			4	Y								*							\vdash
11034 044		1P	1PE	100	,	1	V	¥	ă.				-	-	-	*	_	-				\vdash
U031-011	1	1G	1GE	100	*	1	V	✓	Α		*			_		-	_					\vdash
		1K	1KE	-		4	Y	V					*	_	_	_			_	_		\vdash
		1R	1RE			✓	✓	1				Ц.		_			*					ш



12-13 Parameters: 5 mm x 121 mm U120/U500 Strip Size

1-11 Parameters: 5 mm x 108 mm; "E" means extended strip length for 1-6 Parameters

- Visual Strip Size 1-6 Parameters: 5 mm x 80 mm; 7-11 Parameters: 5 mm x 108 mm;
 - Not available in canisters of 150 strips
 - ▲ Single-strip Pouch available in 1,3, 6 and 20 strip kit
 Canister Refill Kit, with 25 strips per pouch or canister, available in 3-pouch and 1- canister kit, or 4-pouch kit



Also available in canisters of 25, 50 and 150 strips

U120 Urine Analyzer



- Accurate

 Up to 120 tests/hour in Continuous Test Option
- · Capable of reading 1 strip at a time in Single Test Option
- · Test modes include Routine, STAT and QC
- · Automatic calibration for accurate results and easy operation

- Can read up to 4 Strip combinations with 8, 9, 10, 11 parameters, additional strips with 1-11 parameters available upon request

- Convenient Operation
 Saves and recalls the last 2,000 results automatically
- · Audible beep signals operator to dip strips in urine
- · Can print up to 3 copies per test for convenient reviewing and easy record keeping
- · Option to print results on sticker paper for quick and simple record management

Easy Data Management

- Includes RS232C port for easy data transfer to an external computer or LIS
 Optional Barcode Reader to record patient ID

Unique Lockout Functions new!

- Strip Lockout
 - Prevents using strips of another brand on the U120 Urine Analyzer
 - · Requires barcode reader scan or manual entry of the canister code
- User Lockout

 - Eliminates unapproved users from testing
 Up to 10 lab operators can perform testing, but only the lab administrator can change analyzer settings
- QC Lockout
 - · Prevents testing without passing QC
 - Prevents testing without passing acceptable of the control of

 - . If QC tests fail, analyzer will switch to STAT mode and list "E" at the end of each test number

Specifications

Feature	Specif	Specifications					
Analyzer Type	Manual						
Methodology	Reflectance Photometry						
Detection	Photosensitive Diode						
Throughput	Single Test Option: 60 tests/hour Continuous Test Option: 120 tests/hour						
Test Modes	Routine, STAT and QC						
Lockout Functions	Strip Lockout: Available Upon Request; User/QC Lockout: Included with option to turn ON/OF						
Memory	Last 2,000 results	**					
Strip Incubation Time	1 Minute						
Wavelength of Monochromatic LED	525 nm and 635 nm						
Standard Strips	8, 9, 10, 11 Parameters (5 mm x 108 mm)						
Additional Strips Available	1-11 Parameters (5 mm x 108 mm); see URS Parameters						
Total Combinations Per Analyzer	4 Combinations						
Analyzer Ports	Standard RS232C Port for Barcode Rea USB Port for Data Transfer 25 Pin Parallel Port for External Printer						
Capabilities	Internal Thermal Printer (included) Optional External Printer (not included)	RS232C Barcode Reader (optional) USB or RS232C Data Transfer Cable (optional)					
Major Readable Barcodes	Code 128, Code 39, Codabar (NW-7), Inte EAN 8, EAN 13	rleaved 25, UPC-A, UPC-E,					
Calibration	Automatic						
Available Languages on the Screen	English and additional language(s)						
Operating Conditions	0-40°C (32-104°F); ≤85% RH						
Storage Conditions	-5-50°C (23-122°F); ≤90% RH						
Power Source	100-240 VAC, 50-60 Hz						
Dimensions (L x W x H)	27.2 cm x 26.9 cm x 14.6 cm (10.7" x 10	1.6" x 5.7")					
Display Dimensions (L x W)	10.8 cm x 5.7 cm (4.2" x 2.2")						
Weight	2.6 kg (5.7 lbs)						

Ordering Information

Product Name	Catalog No.	Co	mponents		Kit Box Dimensions (L x W x H) & Weight	Carton Dimensions (L x W x H) & Weight	Number of Kits/Carton
U120 Urine Analyzer	U111-101√ [†]	1 Urine Analyzer 11-101à 1 Strip holder		2 Fuses (2.0A) 1 Power Cord	42.0 cm x 41.5 cm x 3	4	
0 120 Offile Arialyze	U111-101*1	2 Printer Paper Roll	s	1 Quick Start Guide 1 Instruction Manual	16.4" x 16.2" x 12.	1"; 176.4 oz	
U120 Urine Analyzer	U111-111√ [†]	1 Urine Analyzer 1 Strip holder		2 Fuses (2.0A) 1 Power Cord	44.5cm x 44.5cm x 40.0cm; 5.5 kg		- 27
with Barcode Reader	Omin	2 Printer Paper Roll 1 Barcode Reader (1 Serial Splitter Cable (RS232C) 1 Quick Start Guide 1 Instruction Manual	17.5" x 17.5" x 15.	7"; 194 oz	1
Barcode Reader	U221-111√ [†]	1 Barcode Reader (I	RS232C)	1 Serial Splitter Cable (RS232C)	23.6 cm x 10.8 cm x 7.8 cm; 0.482 kg 9.3" x 4.3" x 3.1"; 17.0 oz	63.0 cm x 37.0 cm x 30.0 cm; 12.0 kg 24.8" x 14.6" x 11.8"; 423.3 oz	22
Printer Paper Rolls	11101 101	4 Printer Paper Rolls	Thermal F	Paper (0.06 m x 20 m); 200 results/roll	12.0 cm x 12.0 cm x 6.5 cm; 0.36kg 4.7" x 4.7" x 2.6"; 12.7oz	63.0 cm x 37.0 cm x 30.0 cm; 19.4 kg 24.8" x 14.6" x 11.8"; 684.3 oz	50
r linter raper itolis	U121-101	4 Filiter Faper Kolls	Sticker Pa	aper (0.06 m x 9 m): 100 results/roll	12.0 cm x 12.0 cm x 6.5 cm; 0.4 kg 4.7" x 4.7" x 2.6"; 14.1 oz	63.0 cm x 37.0 cm x 30.0 cm; 21.4 kg 24.8" x 14.6" x 11.8"; 684.3 oz; 754.9 oz	
U120 Data Transfer Kit	U221-131 ^à	1 Data Transfer Cable	(RS232C)	1 Package Insert	16.0 cm x 13.0 cm x 3.5 cm; 0.147 kg 6.3" x 5.1" x 1.4"; 5.2 oz	25.0 cm x 21.0 cm x 15.0 cm; 1.36 kg 9.8" x 8.3" x 5.9"; 48.0 oz	8

U500 Urine Analyzer



Accurate and Efficient

• Up to 500 tests/hour for medium/large volume sample testing
• Professional accuracy equivalent to market leader
• Automatic strip detection and alignment for better efficiency
• Test modes include Routine, STAT and QC

Easy to Operate

Large touch screen LCD offers simple menu navigation

Uniquely designed strip platform/waste tray unit for easy one-step cleaning

CONVENIENT

Automatic calibration and waste disposal reduce hands-on time

Can read strips with 8, 9, 10, 11 parameters, additional strips with 1-11 parameters available upon request

Strip selection of up to 4 combinations for analyzer reading

Stories up to 2,000 records and automatically flags abnormal results

Capable of printing results on sticker paper for quick and easy record management

Data Management Capability
Includes R\$232C port for easy data transfer to an external computer or LIS
Optional Barcode Reader to record patient ID
Unique Lockout Functions Coming Soon!

Strip Lockout
 Prevents using strips of another brand on the U500 Urine Analyzer
 Requires barcode reader scan or manual entry of the canister code

User Lockout

Eliminates unapproved users from testing
 Up to 10 lab operators can perform testing, but only the lab administrator can change analyzer settings.

QC Lockout
 Prevents testing without passing QC

QC tests can be performed once every 8 hours, day, week or month
 Analyzer will alert when to run QC test

If QC tests fail, analyzer will switch to STAT mode and list "E" at the end of each test number

Specifications

Feature	Specifications						
Analyzer Type	Semi-Automatic						
Methodology	Reflectance Photometry						
Detection	Photosensitive Diode	Photosensitive Diode					
Throughput	500 tests/hour (Measuring cycle: 7 seconds/test)						
Test Modes	Routine, STAT and QC						
Lockout Functions	Strip Lockout: Available Upon Request; User/QC Lockout: Included with option to turn ON/OFF						
Memory	Last 2,000 Records						
Strip Incubation Time	1 Minute						
Wavelength	525 and 635 nm						
Standard Strips	8, 9, 10, 11 Parameters (5 mm x 108 mm)						
Additional Strips Available	1-11 Parameters (5 mm x 108 mm); see URS Parameters						
Total Combinations Per Analyzer	4 Combinations						
Waste Disposal Capacity	Up to 150 Strips						
Analyzer Ports	Standard RS232C Port for Barcode Read 25 Pin Parallel Port for External Printer	ler or Data Transfer					
Capabilities	Internal Thermal Printer (included) Optional External Printer (not included)	RS232C Barcode Reader (optional) RS232C Data Transfer Cable (optional)					
Major Readable Barcodes	Code 128, Code 39, Codabar (NW-7), Interle	eaved 25, UPC-A, UPC-E, EAN 8, EAN 13					
Calibration	Automatic						
Available Languages on the Screen	English and additional language(s)						
Operating Conditions	0-40°C (32-104°F); ≤85% RH						
Storage Conditions	-5-50°C (23-122°F); ≤90% RH						
Power Source	100-240 VAC, 50-60 Hz						
Dimensions (L x W x H)	36.6 cm x 28.3 cm x 19.5cm (14.4" x 11.1" x 7.7")						
Display Dimensions (LxW)	11.5 cm x 9.0 cm (4.5" x 3.5")	Africa					
Weight	4.0 kg (8.8 lbs)						

Ordering Information

Product Name	Catalog No.	Components		Kit Box Dimensions (L x W x H) & Weight	Carton Dimensions (L x W x H) & Weight	Number of Kits/Carton		
transaction recommendation of the con-	112	1 Urine Analyzer 1 Strip Platform/Waste	2 Fuses (2.0A) Tray 1 Power Cord		51.0 cm x 42.0 cm x 3	8.5 cm; 7 kg		
U500 Urine Analyzer	U211-101√	2 Printer Paper Rolls		1 Instruction Manual	20.1" X 16.5" x 15.	2"; 246.9 oz	1	
U500 Urine Analyzer		4 Onio Platform Market Tray						1
with Barcode Reader	02111111	2 Printer Paper Roll: 1 Barcode Reader (F		Serial Splitter Cable (RS232C) Instruction Manual	21.7" x 21.7" x 21.			
Barcode Reader	U221-111à	1 Barcode Reader (I	RS232C)	1 Serial Splitter Cable (RS232C)	23.6 cm x10.8 cm x 7.8 cm; 0. 482 kg 9.3" x 4.3" x 3.1"; 17.0 oz	63.0 cm x 37.0 cm x 30.0 cm; 12 kg 24.8" x 14.6" x 11.8"; 423.3 oz	22	
Printer Paper Rolls	LIADA ADA	4 Printer Paper Rolls	Thermal P	aper (0.06 m x 20 m): 200 results/roll	12.0 cm x 12.0 cm x 6.5 cm; 0.360 kg 4.7" x 4.7" x 2.6"; 12.7oz	63.0 cm x 37.0 cm x 30.0 cm; 19.4 kg 24.8" x 14.6" x 11.8"; 684.3 oz	50	
Filiter Faper Itolis	U121-101			per (0.06 m x 9 m): 100 results/roll	12.0 cm x 12.0 cm x 6.5 cm; 0.40 kg 4.7" x 4.7" x 2.6"; 14.10z	63.0 cm x 37.0 cm x 30.0 cm; 21.4 kg 24.8" x 14.6" x 11.8"; 684.3 oz; 754.9 oz	19/8/	
U500 Data Transfer Kit	U221-131√	1 Data Transfer Cable	(RS232C)	1 Package Insert	16.0 cm x 13.0 cm x 3.5 cm; 0.147kg 6.3" x 5.1" x 1.4"; 5.2 oz	25.0 cm x 21.0 cm x 15.0 cm; 1.36 kg 9.8" x 8.3" x 5.9"; 48.0 oz	8	

We also offer other rapid diagnostic and medical products:

Blood Glucose Monitoring Systems, Immunoassay EIA/ELISA and more.

✓ CE Marked for sale in the European Community † Cleared for US 510(k)



ACON Laboratories, Inc., 10125 Mesa Rim Road, San Diego, CA 92121, U.S.A. • Tel: 1-858-875-8000 • Fax: 1-858-200-0729 • E-mail: info@aconlabs.com Please visit our website for details: www.aconlabs.com

Mission® **Urine Controls**



visual and analyzer urinalysis with Mission® Liquid and Dry Strip Urine

Mission® Urine Controls

Reliable

- Use with Mission* and Mission* Expert Urinalysis Reagent Strips and Urine Analyzers for optimum quality control
- Validate urinalysis results and prevent procedure errors
- Control Level 1 provides negative results for LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ASC, ALB and
- Control Level 2 provides positive results for LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ALB*** and CRE*** with negative results for ASC

Quick and Convenient Testing

- Ensures accurate results for all parameters
- Obtain quick results in any setting

Two Types of Urine Controls Available **Liquid Urine Control**

- Ready-to-use without dissolving in distilled water
- 24 months shelf life for unopened controls at 2-8°C
- Two Packaging Options
- Dropper Tip Bottles-Current packaging now available in separate positive and negative levels!
 Dropper tip bottles provide efficient use of the control solution
- · Easily drop the control solution onto each reagent pad using the dropper tip bottle
- Control can be used up to 40 times within 30 days at room temperature
- Diptube-New packaging available in separate positive and negative levels!
 Diptube packaging allows for quick testing similar to using a urine specimen
 Simply dip the strip into the control solution and read results

 - · Control can be used up to 20 times within 30 days at room temperature

Dry Strip Urine Control

- Portable for use anywhere with no refrigeration required
 Dissolve the dry strip urine control in distilled water, dip urine strip in the control solution, then compare to color chart
- Each control solution can be used for up to 12 tests at 2-30°C within 8 hours for all parameters
- 24 months shelf life at 2-30°C for unopened controls



Specifications

Features			Specifications				
Product Name		Liquid Urine Control	Liquid Diptube Urine Control	Dry Strip Urine Control			
Test Parameters		1	LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GI	-U, ASC, ALB, CRE (13)			
Solution Detection	Level 1		Negative: LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ASC, ALB, CRE				
Levels Level 2			Positive: LEU, NIT, URO, PRO, pH, BLO, SG, KET, BIL, GLU, ALB and CRE, Negative ASC				
Compatible Urine Strips			Mission® Urinalysis Reagent Strips, Mission® Expert Urinalysis Reagent Strips				
Reading Time/Stabi	lity	Refer to insert	Refer to insert	Refer to insert			
Storage Temperatur	re	2-8°C	2-8°C	2-30°C			
Unopened Control Shelf Life 24 months		24 months	24 months	24 months			
Opened Control Stability 30 days at 15-30°C or until the expiration date at 2-8°C			30 days at 15-30°C or until the expiration date at 2-8°C	2-30°C: 3 months for Dry Strip; 8 hours for Control Solution for all parameters			
Maximum Tests per	Unit	20 or 40 tests/bottle	20 tests/diptube	12 tests/control solution of 1 dry strip			

Ordering Information

Product Name	Catalog No.	Components	Kit Box Dimensions (LxWxH) & Weight	Carton Dimensions (LxWxH) & Weight	# Kits/Cartor
		Level 1: 3 x 10 mL /bottle; Level 2: 3 x 10 mL/bottle	85 mm x 55 mm x 60 mm; 107 g	400 mm x 270 mm x 345 mm; 5.2 kg	198
	100010010000000000000000000000000000000	Level 1: 3 x 5 mL/bottle; Level 2: 3 x 5 mL/bottle	85 mm x 55 mm x 60 mm; 75 g	400 mm x 270 mm x 345 mm; 4.2 kg	198
	U021-011: Combo	Level 1: 1 x 10 mL/bottle; Level 2: 1 x 10 mL/bottle 55 mm x 28 mm x 60 mm; 41 g		400 mm x 270 mm x 345 mm; 6.6 kg	228
1+		Level 1: 1 x 5 mL/bottle; Level 2: 1 x 5 mL/bottle	55 mm x 28 mm x 60 mm; 31 g	400 mm x 270 mm x 345 mm; 5.5 kg	228
Liquid Urine Control √T		6 x 10 mL/bottle	85 mm x 55 mm x 60 mm; 107 g	400 mm x 270 mm x 345 mm; 5.2 kg	198
	U021-021: Level 1;	6 x 5 mL/bottle	85 mm x 55 mm x 60 mm; 75 g	400 mm x 270 mm x 345 mm; 4.2 kg	198
	U021-031: Level 2	2 x 10 mL/bottle	55 mm x 28 mm x 60 mm; 41 g	400 mm x 270 mm x 345 mm; 6.6 kg	228
		2 x 5 mL/bottle	55 mm x 28 mm x 60 mm; 31 g	400 mm x 270 mm x 345 mm; 6.6 kg 400 mm x 270 mm x 345 mm; 5.5 kg 385 mm x 255 mm x 320 mm; 4.7 kg 385 mm x 255 mm x 320 mm; 3.5 kg	228
	11004 074 0	Level 1: 2 x 12 mL/diptube; Level 2: 2 x 12 mL/diptube	130 mm x 55 mm x 55 mm; 101 g	385 mm x 255 mm x 320 mm; 4.7 kg	30
Liquid Diptube .	U021-071: Combo	Level 1: 1 x 12 mL/diptube; Level 2: 1 x 12 mL/diptube	130 mm x 55 mm x 55 mm; 62 g	385 mm x 255 mm x 320 mm; 3.5 kg	30
Urine Control 1	U021-081: Level 1;	4 x 12 mL/diptube	130 mm x 55 mm x 55 mm; 101 g	385 mm x 255 mm x 320 mm; 4.7 kg	30
	U021-091: Level 2	2 x 12 mL/diptube	130 mm x 55 mm x 55 mm; 62 g	g 400 mm x 270 mm x 345 mm; 5.2 kg g 400 mm x 270 mm x 345 mm; 4.2 kg g 400 mm x 270 mm x 345 mm; 6.6 kg g 400 mm x 270 mm x 345 mm; 5.5 kg g 400 mm x 270 mm x 345 mm; 5.5 kg g 400 mm x 270 mm x 345 mm; 5.2 kg g 400 mm x 270 mm x 345 mm; 4.2 kg g 400 mm x 270 mm x 345 mm; 6.6 kg g 400 mm x 270 mm x 345 mm; 5.5 kg g 385 mm x 255 mm x 320 mm; 4.7 kg g 385 mm x 255 mm x 320 mm; 4.7 kg g 385 mm x 255 mm x 320 mm; 3.5 kg g 385 mm x 255 mm x 320 mm; 3.5 kg g 385 mm x 255 mm x 320 mm; 3.6 kg g 280 mm x 280 mm x 260 mm; 3.6 kg	30
	11004 044 0	Level 1: 1 x 25 strips/canister; Level 2: 1 x 25 strips/canister	100 mm x 51 mm x 110 mm; 126 g	280 mm x 280 mm x 260 mm; 3.6 kg	24
Dry Strip Urine Control à	U021-041: Combo	Level 1: 1 x 10 strips/canister; Level 2: 1 x 10 strips/canister	100 mm x 51 mm x 110 mm; 106 g	280 mm x 280 mm x 260 mm; 3.1 kg	24
3.0023003	U021-051: Level 1;	2 x 25 strips/canister	100 mm x 51 mm x 110 mm; 126 g	280 mm x 280 mm x 260 mm; 3.6 kg	24
	U021-061: Level 2	2 x 10 strips/canister	100 mm x 51 mm x 110 mm; 106 g	280 mm x 280 mm x 260 mm; 3.1 kg	24

√ CE Marked for sale in the European Community (€ † FDA 510(k) Cleared

We also offer other rapid diagnostic and medical products for:

Blood Glucose Monitoring Systems, Clinical Chemistry including Urinalysis, Immunoassay EIA/ELISA and more.

Contact us for worldwide distribution and custom manufacturing (OEM) opportunities



ACON Laboratories, Inc., 10125 Mesa Rim Road, San Diego, CA 92121, U.S.A. • Tel: 1-858-875-8000 • Fax: 1-858-200-0729 • E-mail: info@aconlabs.com Please visit our website for details: www.aconlabs.com © 2011 ACON Laboratories, Inc. 1150531002