

COMMUNICATION



106R-000384

issued by : Ministry of Transport
L.Svobody 1222/12
110 15 Praha 1
Czech Republic

concerning: ^{1/}


~~APPROVAL GRANTED~~
APPROVAL EXTENDED
~~APPROVAL REFUSED~~
~~APPROVAL WITHDRAWN~~
~~PRODUCTION DEFINITELY DISCONTINUED~~

of a type of pneumatic tyre for agricultural vehicles pursuant to Regulation No. 106

Approval No.: 106R-000384

Extension No. : I.

1. Manufacturer's name or trade mark (s) of the tyre: **PETLAS**
2. Tyre type designation by the manufacturer: **TA-110**
3. Manufacturer's name and address: **PETLAS TYRE INDUSTRY
AND TRADE COMPANY
Kindam Mah.
Ankara-Kayseri Cad. No. 2/1
Kirsehir
TURKEY**
4. If applicable, name and address of manufacturer's representative: **N/A**
5. Summarized description:
 - 5.1. Size of tyre: **see tyre dimensions list**
 - 5.2. Category of use: **Tractor - Drive wheel - standard tread**
 - 5.3. Structure: ~~diagonal (bias-ply)/bias belted~~/**radial** ^{1/}
 - 5.4. Speed category symbol: **A8**
 - 5.5. Load-capacity index: **see tyre dimensions list**
 - 5.5.1. for traction (implement only): -
 - 5.5.2. for trailer (implement only): -



5.6. Whether the tyre is to be fitted with or without an inner tube **TUBE-TYPE / TUBELESS**

5.7. The supplementary service description, if applicable: **see tyre dimensions list**

6. Technical Service and, where applicable, test laboratory approved for purposes of approval or of verification of conformity:

**IGTT a.s.
Šternberská 446, Louky,
763 02 ZLÍN
CZECH REPUBLIC**

7. Date of report issued by that service: -

8. Number of report issued by that service: -

9. Reason(s) of extension (if applicable): **Supplementary service description added**

10. Any remarks: -

11. Place: **Praha**

12. Date: **29.07.2016**

13. Signature: **Marek Brázda**

14. Annexed to this communication is a list of documents in the approval file deposited at the Administrative Services having delivered the approval and which can be obtained upon request

^{1/} Strike out what does not apply.



Annex No.1

Tyre dimensions list from the same range

280/85 R20 TA-110 TL 112 A8 / 109 B	106R-000384
280/85 R24 TA-110 TL 115 A8 / 112 B	
280/85 R28 TA-110 TL 118 A8 / 115 B	
320/85 R20 TA-110 TL 119 A8 / 116 B	
320/85 R24 TA-110 TL 122 A8 / 119 B	
320/85 R28 TA-110 TL 124 A8 / 121 B	
320/85 R32 TA-110 TL 126 A8 / 126 B	
320/85 R36 TA-110 TL 128 A8 / 125 B	
320/85 R38 TA-110 TL 143 A8 / 143 B	
340/85 R24 TA-110 TL 125 A8 / 122 B	
340/85 R28 TA-110 TL 127 A8 / 124 B	
340/85 R36 TA-110 TL 132 A8 / 129 B	
340/85 R38 TA-110 TL 133 A8 / 130 B	
380/85 R24 TA-110 TL 131 A8 / 128 B	
380/85 R28 TA-110 TL 133 A8 / 130 B	
380/85 R30 TA-110 TL 135 A8 / 132 B	
380/85 R34 TA-110 TL 137 A8 / 137 B	
380/85 R38 TA-110 TL 139 A8 / 136 B	
420/85 R24 TA-110 TL 137 A8 / 134 B	
420/85 R28 TA-110 TL 139 A8 / 136 B	
420/85 R30 TA-110 TL 140 A8 / 137 B	
420/85 R34 TA-110 TL 142 A8 / 139 B	
420/85 R38 TA-110 TL 144 A8 / 141 B	
460/85 R30 TA-110 TL 145 A8 / 142 B	
460/85 R34 TA-110 TL 147 A8 / 144 B	
460/85 R38 TA-110 TL 149 A8 / 146 B	
460/85 R38 REINFORCED TA-110 TL 149 A8 / 146 B	
520/85 R38 TA-110 TL 155 A8 / 152 B	
520/85 R38 REINFORCED TA-110 TL 155 A8 / 152 B	
520/85 R42 TA-110 TL 157 A8 / 157 B	
520/85 R42 REINFORCED TA-110 TL 162 A8 / 162 B	
520/85 R46 TA-110 TL 158 A8 / 155 B	
650/85 R38 TA-110 TL 173 A8 / 173 B (WC TYRE)	

