



TRD88



- Deeper tread depth, longer service life.
- Rugged block design for improved traction performance and cut & tear resistance.
- Open wide groove design brings good self-cleaning and heat dissipation .
- High-strength carcass ply and belt package design, good durability.
- Designed for all position of short-haul trucks, dump trucks, and trailers. Suitable for mining service.



Size	PR	Loading Index		Speed Rating	Tread Depth (mm)	Rim Width	Alternative Rim	New Tire Inflated Dimensions (mm)		Max Load (Kg)		Pressure (KPa) Single/Dual	Tube	Static Radius Under Load (mm)	Min. Dual Tire Space (mm)
		Single	Dual					Section Width	Overall Diameter	Single	Dual				
7.50R20	14	130	128	K	14.0	6.00	6.50	215	935	1900	1800	830	TT	435	254
8.25R20	14	136	134	K	15.5	6.50	7.00	236	974	2240	2120	830	TT	452	278
8.25R20	16	139	137	K	15.5	6.50	7.00	236	974	2430	2300	930	TT	452	278
9.00R20	14	141	139	K	15.5	7.00	7.50	259	1019	2575	2430	790	TT	471	306
9.00R20	16	144	142	K	15.5	7.00	7.50	259	1019	2800	2650	900	TT	471	306
10.00R20	16	146	143	K	16.5	7.50	8.00	278	1054	3000	2725	830	TT	486	328
10.00R20	18	149	146	K	16.5	7.50	8.00	278	1054	3250	3000	930	TT	486	328
11.00R20	16	150	147	K	17.0	8.00	8.50, 8.00V	293	1085	3350	3075	830	TT	499	346
11.00R20	18	152	149	K	17.0	8.00	8.50, 8.00V	293	1085	3550	3250	930	TT	499	346
12.00R20	18	154	151	K	17.5	8.50	8.50V, 9.00	315	1125	3750	3450	830	TT	516	372
12.00R20	20	156	153	K	17.5	8.50	8.50V, 9.00	315	1125	4000	3650	900	TT	516	372
8R22.5	14	130	128	L	14.0	6.00	6.75	203	935	1900	1800	830	TL	440	231
9R22.5	14	136	134	L	15.5	6.75	7.50	229	974	2240	2120	830	TL	457	261
10R22.5	14	141	139	L	15.5	7.50	6.75	254	1019	2575	2430	790	TL	476	290
10R22.5	16	144	142	L	15.5	7.50	6.75	254	1019	2800	2650	900	TL	476	290
11R22.5	14	144	142	L	16.5	8.25	7.50	279	1054	2800	2650	720	TL	491	318
11R22.5	16	146	143	L	16.5	8.25	7.50	279	1054	3000	2725	830	TL	491	318
295/80R22.5	16	152	148	L	17.0	9.00	8.25	298	1044	3550	3150	850	TL	487	335
12R22.5	16	150	147	L	17.0	9.00	8.25	300	1085	3350	3075	830	TL	504	342
12R22.5	18	152	149	K	17.0	9.00	8.25	300	1085	3550	3250	930	TL	504	342