

XBO R 180W/45C OFR



Product features and benefits

- High luminance / radiance with intense point source
- Broad, continuous spectral distribution
- High color rendering > 95
- High arc stability
- DC operation

Areas of application

- Endoscopy
- Microscopy
- Surgical Headlamps
- Fiber Illumination
- Solar Simulation
- Imaging & scanning

Technical data

General product information

Product Number	69183
Product Name	XBOR180W45COFR 2/CS 1/SKU
Ordering Abbreviation	XBO R 180W/45C OFR
Brand Name	OSRAM
General Description	180 watt, xenon short arc, with reflector
Application	Lightguide / Boroscopy, Fiber Optic, Minimal Invasive Surgery, Endoscopy
Product Remark	<ul style="list-style-type: none">- C=Base with Cable- OFR=Ozone Free- p (Operating Position) = Horizontal- This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp.- The focus lies 45mm in front of the mounting rim (working distance).

Electrical data

Nominal Wattage	180 W
Current (A)	12 A
Type of Current	DC

Light technical data


Beam Angle (degree)	44 deg
Working Distance a (mm)	45 mm
Color Temperature	6000 K
Color Rendering Index	>90
Average Rated Life - Horizontal (hr)	500 hr

Physical attributes

Base	Leads with AMP 350809-1 connec
Bulb Shape	T17
Maximum Overall Length (mm)	90 mm
Length l1 (mm)	90 mm
Length l1 max. (mm)	90 mm
Diameter d (in)	2.520 in
Diameter d (mm)	64.00 mm
Reflector Coating	64.00

Additional product data

Operating Position	p 15
Maximum Base Temperature (°C)	230 C
Forced Cooling	Required
Hot Restart	Yes
Class	C (gas)



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69183	4050300432199	Folding box (SKU)	1	3.4 in x 3.4 in x 4.3 in	0.4 lb
69183	4050300432205	Shipping box (Case)	2	7.3 in x 5 in x 3.9 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.