



*Trinocular phase contrast microscope,
1000x, W-PLAN objectives*

| | | |
|---|-----------------------------------|---|
| Observation Method - Transmitted Light | Brightfield | Yes |
| | Phase contrast (Positive type) | Yes |
| | Darkfield | Yes |
| | Simple polarized light | As optional |
| Main Body | Type | Upright |
| | Construction material | Aluminum die-cast |
| | Trasportation handle | Yes |
| Head | Type | Trinocular (Siedentopf) |
| | Split ratio | 50/50 |
| | Inclination | 30° |
| | 360° rotating | Yes |
| | Interpupillary distance (mm) | 48-75 |
| | Dioptric adjustment | On left tube |
| | Fixing screw for eyepieces | Yes |
| | Tube inner diameter (mm) | 23 |
| Eyepieces | Field number (mm) | 20 |
| | Magnification | 10x |
| | Pointer | As optional |
| | Micrometric scale | As optional |
| | Diameter of micrometer glass (mm) | 21 |
| | High eyepoint (for glass wearers) | Yes |
| | Rubber cup | Yes |
| Nosepiece | Positions | Quintuple |
| | Reversed | Yes |
| | Bi-directional | Yes |
| | Rotation on ball bearings | Yes |
| | Objective thread | RMS |
| Objectives | Optical system | 160 |
| | Anti-fungus treatment | Yes |
| | Parfocal distance (mm) | 45 |
| | Standard magnifications | 40x-1000x |
| | Type | W-PLAN |
| | | W-PLAN 4x/0.10, W.D. 15.8 mm |
| | | W-PLAN PH 10x/0.25, W.D. 12.2 mm |
| | | W-PLAN PH 40x/0.65, W.D. 0.37 mm |
| | | W-PLAN PH 100x/1.25 (Oil), W.D. 0.13 mm |
| | | |
| Stage | Type | Double layer |
| | Dimensions (mm) | 150x139 |
| | Moving mechanism | Rackless |
| | Moving range (mm) | 75x33 |
| | Material | Anti-scratch painting |
| | Specimen holder | Yes |
| | Slide number | 1 |
| | X-Y Vernier scale | Yes |
| | Vernier scale accuracy (mm) | 0.1 |

| | | |
|--------------------------------------|---------------------------|---|
| Condenser - Multiple Position | Type | Abbe. Brightfield - Phase contrast - Darkfield (dry) |
| | Number of positions | 5 (BF, 10x/20x, 40x, 100x, DF) |
| | Numerical aperture (N.A.) | 1.25 |
| | Removable | Yes |
| | Diaphragms | Iris |
| | Centrable | Yes |
| | Focusable | By rack and pinion |

| | | |
|------------------------|--|-----------------------|
| Focusing System | Type | Coaxial coarse & fine |
| | Coarse total travel (mm) | 25 |
| | Fine total travel (per single rotation) (mm) | 0.2 |
| | Fine graduations | 100 |
| | Fine resolution (µm) | 2 |
| | Upper stop to prevent contact | Yes |
| | Adjustable tension | Yes |
| | Flat knob for ergonomy | Yes |

| | | |
|---------------------------------|-------------------------|--------------------------|
| Transmitted Illumination | Kohler illumination | Fixed (full as optional) |
| | Type | X-LED |
| | X-LED type | X-LED3 |
| | Light source power (W) | 3.6 |
| | Brightness control | Manual |
| | Lifetime (hours) | > 65,000 |
| | Temperature (K) | 6,300 |
| | Max. required power (W) | 6 |

| | | |
|--|----------------------|-------------------------|
| Power Supply for Transmitted Illumination | Type | External |
| | Microscope connector | Jack, 2.1 mm |
| | Power plug type | Multi-plug (EU, UK, US) |
| | Input voltage | 100/240 Vac, 50/60 Hz |
| | Output voltage | 6 Vdc 2.5 A |

| | | |
|-----------------------------|-------------------------|--------------------------------|
| Accessories Included | Dust cover | Yes |
| | Immersion oil (10ml) | Yes |
| | Tension adjustment tool | Yes |
| | Allen wrench | Yes |
| | Centering telescope | Yes |
| | Green filter | Yes |
| | User Manual | Digital version (downloadable) |

| | | |
|-------------------------------|--|---|
| Additional Information | | External rechargeable battery pack (as optional). |
|-------------------------------|--|---|

| | | |
|---------------------------|-------------|-----|
| Product Dimensions | Height (mm) | 405 |
| | Width (mm) | 235 |
| | Depth (mm) | 370 |

| | | |
|-----------------------|------|-----|
| Product Weight | (kg) | 7.8 |
|-----------------------|------|-----|