

# DURACELL®

## TECHNICAL DATA SHEET

Type no.	DP 225 SHD
Article no.	018725030801
EAN/GTIN no.	9005753086340
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	225 Ah (K20)
Cold start current	1150 A (EN)
Dimensions and weights	
Box	C
Length max.	517mm
Width max.	273mm
Box height max.	212mm
Total height max.	240mm
Battery weight	Ca. 59,0 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	18
Pallet ID	Euro pallet
Items per layer	6
Features	
Base hold-down	B00
Layout	3
Terminal	1
Separator	PE bag separator with glass nonwoven
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - V3 - E3
Maintenance <sup>1)</sup>	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage <sup>2)</sup>	max. 14,8 V



<sup>1)</sup> All the listed values relate to room temperature +25° C

<sup>2)</sup> Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

Duracell Automotive c/o Banner GmbH

Banner Straße 1, A-4021 Linz, tel.: +43/(0)732/38 88-0, Fax DW-21599

e-mail: info@duracell-automotive.com, www.duracell-automotive.com



[duracell-automotive.com](http://duracell-automotive.com)