

**Lot 113, Incubator (termostat) 20 - 35L****Model propus: EN 300, Nuve, Turcia**

Parametri solicitati	Parametri oferiti
<p>Incubator (termostat) 20 - 35 l Cod 250300 Descriere "Incubatoarele termostat, dispozitiv de laborator care se utilizează pentru menținerea îndelungată la temperatură constantă a probelor pentru a amplifica mostre testate de acizi nucleari pentru utilizarea în tehnici de secvențiere. " Parametru Specificație Descriere termostat utilizat în laborator Capacitate internă a camerei diapazon 20 - 35 Litri Domeniul de temperatură, diapazon programabil <math>\geq (37 - 60^{\circ}\text{C})</math> Rezoluția de programare <math>\leq 1</math> grad Timp de funcționare, diapazon minim 1 - 999 minute, neîntrerupt Afișaj LCD sau LED Control Microprocesor Usa dubla obligatoriu Usa internă din sticla obligatoriu Construcția interioară din oțel inox Alarmă vizuala și sonora divergență față de temperatura setată Alimentarea 220 V, 50 Hz</p>	<p>Incubator (termostat) 20 - 35 l Cod 250300 Descriere "Incubatoarele termostat, dispozitiv de laborator care se utilizează pentru menținerea îndelungată la temperatură constantă a probelor pentru a amplifica mostre testate de acizi nucleari pentru utilizarea în tehnici de secvențiere. " Parametru Specificație Descriere termostat utilizat în laborator Capacitate internă a camerei diapazon 20 - 35 Litri Domeniul de temperatură, diapazon programabil + <math>5^{\circ}\text{C}</math> peste ambient / <math>80^{\circ}\text{C}</math> Rezoluția de programare <math>\leq 1</math> grad Timp de funcționare, diapazon minim 1 – 99 ore 59 minute, neîntrerupt Afișaj LED Control Microprocesor Usa dubla obligatoriu Usa internă din sticla obligatoriu Construcția interioară din Anodic-oxidated Aluminium Alarmă vizuala și sonora divergență față de temperatura setată Alimentarea 220 V, 50 Hz</p>



# EN SERIES

## Incubators



- Excellent incubation conditions for the applications in microbiology and biology; clinical diagnostic laboratories in the fields of medical, biotechnology and veterinary sciences; and quality control laboratories of different industries such as pharmaceutical, food, dairy, beverage and cosmetics
- Very homogeneous temperature distribution by natural air convection: Minimum turbulence and no cross contamination
- Anodic-oxidated aluminium chamber
- Frameless inner glass door for the observation of the samples without any temperature drop
- Reliable and accurate N-Prime™ programmable PID microprocessor control system
- User friendly control panel including large bright LED displays for temperature and time
- Easy programming with one button, just turn and push
- Password protected menu to secure the operation
- Programmable alarm limits
- Data recording on memory stick by means of USB port up to 125 days
- Programmable delayed start function
- Adjustable independent safety thermostat which takes over control in case of any failure

**N-prime**

## TECHNICAL SPECIFICATIONS

	EN 300	EN 400	EN 500
Temperature Range	Ambient Temp + 5°C / 80°C		
Temperature Sensor	Fe-Const		
Control System	N-Prime™ Programmable Microprocessor		
Temperature Set and Display Sensitivity	0,1°C		
Temperature Variation (up to 40 °C)	± 0,5°C		
Temperature Fluctuation	± 0,1°C		
Programmable Alarm Limits	± 0,5°C / 5°C		
Timer	1 minute – 99,9 hours + Hold Position		
Delayed Start Timer	1 minute – 99,9 hours		
Selectable Recording Frequency on Memory Stick	10 or 30 seconds, 1, 5, 30 or 60 minutes		
Useful Volume, litres	22	48	120
Number of Shelves ( Standard/ Max.)	2/6	2/7	2/10
Internal Material	Anodic-oxidated Aluminium		
External Material	Epoxy - Polyester Powder Coated Steel		
Power Consumption	100 W	250 W	350 W
Power Supply	230 V, 50/60 Hz		
Internal Dimensions (WxDxH) mm.	300x240x300	420x320x360	500x490x500
External Dimensions (WxDxH) mm.	555x380x460	705x475x540	785x635x680
Packing Dimensions (WxDxH) mm.	640x470x640	790x570x760	870x740x860
Net / Packed Weight kg.	26 / 31	39 / 45	60 / 70

## ACCESSORIES

- R 01 014 Aluminium Shelf for EN 300  
R 01 136 Mesh type shelf for EN 400  
R 01 135 Mesh type shelf for EN 500  
K 23 031 Shelf carrier for EN 300  
K 23 047 Shelf carrier for EN 400  
K 23 046 Shelf carrier for EN 500

Note: 2 pcs. shelf carrier should be ordered for each shelf



**NUVE SANAYİ MALZEMELERİ İMALAT VE TİCARET A.Ş.**

Saracalar Mah. Saracalar Kümeevleri No: 4/2 Akyurt 06750 ANKARA / TURKEY t. +90 312 399 28 30 f. +90 312 399 21 97  
nuve.com.tr sales@nuve.com.tr

ISO 9001: 2008  
ISO 13485: 2003

