



[Start](#) / [Products & Accessories](#) / [Consumables](#) / **[AkuPak LITE/ AkuPak LITE XD](#)**



AkuPak LITE/ AkuPak LITE XD

AkuPak LITE

Rechargeable lithium ion battery (LiFePO₄), rechargeable battery with charge level display and external charging contacts. Energy content 33 Wh, Nominal operating voltage of 13.2 VDC, nominal capacity 2.5Ah. Life span up to 4 years after production date.

Rechargeable with **DefiMonitor XD** product family, the Charger base and with Clip Charger.

AkuPak LITE XD

Rechargeable lithium ion battery (LiFePO₄), rechargeable battery with charge level display. Energy content 33 Wh, Nominal operating voltage of 13.2 VDC, nominal capacity 2.5 h. Life span up to 4 years after production date.

Rechargeable with **DefiMonitor XD** product family; **not rechargeable with Charger Basis & Clip Charger!**

Productdetails


All specifications apply to a fully charged new AkuPak LITE/ AkuPak XD and a temperature of 20 degrees Celsius \pm 5 degrees Celsius. AkuPak LITE/ AkuPak XD typically lasts up to the earlier of 4 years or 1,000 charging cycles under the following conditions: The AkuPak LITE/ AkuPak XD is inserted to the device, the device only stays in standby mode and is not used, but only performs usual self-tests at the intervals recommended by Metrax. The environmental temperature is at all times at 23 degrees centigrade (\pm 2 degrees centigrade), so that the lifetime will be significantly lower if the devices are stored at outside temperatures. Due to various parameters that might influence the lifespan of the AkuPak LITE/ AkuPak XD, Metrax does not assume any liability with regard to the lifespan of the AkuPak LITE/ AkuPak XD.

Compatible with



HeartSave AED-M

HeartSave 6/6S



ClipCharger



DefiMonitor XD