



No.	Description	Materials
1	Plate	Fe
2	M10*120 bolt	Fe
3	L-bracket	Fe
4	Silicone insulator	Silicone
5	Fixed bending board	Fe
6	Connector	Copper alloy
7	Upper housing	Fe
8	Attach hook	Fe
9	Fuse holder	Glass fiber
10	Open eye	brass
11	Attach hook	brass
12	Lower housing	brass
13	Lifting eye	brass

TECHNICAL CHARACTERISTICS

1. Rated operating Line Voltage: 15KV
2. Maximum equipment voltage: 17.5KV
3. Rated frequency: 50Hz
4. Power frequency withstand voltage (1 min) :
 - Phase to earth: 50KV
 - Across isolating distance: 76KV
5. Impulse withstand voltage (1.2/50 μs, dry) :
 - Phase to earth: 110KV
 - Across isolating distance: 115KV
6. Rated current: 200A
7. Rated interrupt capacity: 10KA
8. Creepage distance: 525mm
9. Standard IEC 60282-2

15KV Drop Out FUSE(Silicon type)

		HRW12-15/200			
		POLYMERIC FUSE CUTOUT		S	1:1
		DRAWING		ZHEJIANG LANGAO POWER TECHNOLOGY CO.,LTD	